

UC-NRLF



\$B 392 310

PRACTICAL LITHOGRAPHY

A. SEYMOUR

REESE LIBRARY
OF THE
UNIVERSITY OF CALIFORNIA.

Class

MAR 15 1907

PRACTICAL LITHOGRAPHY





ALOIS SENEFELDER.

The Inventor of Lithography. Born 1781—Died 1834.

PRACTICAL LITHOGRAPHY

BY

ALFRED SEYMOUR

AUTHOR OF "MODERN PRINTING INKS AND COLOUR PRINTING" "RULE OF THUMB IN THE
WORKSHOP" "SOME WORK-A-DAY NOTIONS" ETC. ETC.

WITH FRONTISPIECE AND THIRTY-THREE ILLUSTRATIONS



LONDON
SCOTT, GREENWOOD & CO.
19 LUDGATE HILL, E.C.

NEW YORK
D. VAN NOSTRAND COMPANY
23 MURRAY STREET
1903

[All Rights remain with Scott, Greenwood & Co.]

NE 2425
S5

RESE

INTRODUCTION

“ALOIS SENEFELDER never benefited much by his discovery of the elementary principles of lithography, but none of those to whom it has given profitable occupation will remember without some feeling the patient and persistent efforts of the struggling actor and dramatist who, only after the greatest sacrifices and hardships, laid the germ of this splendid development, and watched and guarded its growth.” There is one characteristic feature of the discovery of lithography for which Senefelder ought to receive the fullest credit. Unlike other discoveries of industrial and scientific value, there can be no doubt whatever as to its origin. Senefelder’s claim has never been disputed, yet “the payment of a debt of gratitude to the fact is easily overlooked when the wheel of history has made another turn.”

It has been again and again suggested that the blighting influences of Commercialism have robbed lithography of many of its traditional features and a few, at least, of its best and most artistic qualities as a reproductive art. This same commercial spirit, however, has inspired and encouraged a charming variety of effect both in colour and design, and lithography of to-day, in almost every form of its manifestation, is infinitely more attractive and capable of considerably more expressive power than could ever have been hoped for before commercial utility and value demanded a full recognition. Pleasing and harmonious effects, which are almost

invariably sought after in lithography, need not be inartistic; and it is quite possible for the technique of the lithographic draughtsman to translate original work without a serious depreciation of its pictorial and artistic value.

While expressing a sincere hope that this volume may be of considerable assistance to his fellow-craftsmen, the writer wishes to emphasise the fact that resourcefulness and intelligent application are faculties which may be encouraged and amplified but cannot be imparted even by volumes of text.

A mere formal acknowledgment of assistance cordially rendered by the editors of the *British Printer* and *The Caxton Magazine* and *Press*, Messrs. Penrose & Co., and other firms whose blocks are *prima facie* evidences of their interest, does not adequately express the appreciation with which it has been accepted and made use of.

A. S.

LONDON, *December* 1903.

CONTENTS



	PAGE
INTRODUCTION	v
LIST OF ILLUSTRATIONS	xi

CHAPTER I

ELEMENTARY DETAILS

Concerning Stones—Character and Texture—Some Simple Elements— Preparation of Stones—Planing and Levelling—Grinding Grained Stones—Descriptive Treatment—American Method	1-7
---	-----

CHAPTER II

LITHOGRAPHIC TRANSFER INKS

Various Forms—Distinguishing Features—Formulæ—Writing Transfer Ink—Stone-to-stone Transfer Ink—Copperplate Transfer Ink— A Modification	8-11
---	------

CHAPTER III

LITHOGRAPHIC TRANSFER PAPERS

Essential Features—Varnish Transfer Paper—Damp-stone Transfer Paper—French Transparent Transfer Paper—Copperplate Transfer Paper—An Alternative Recipe—Granulated Papers—Photo-litho Transfer Paper	12-16
--	-------

CHAPTER IV

COPPERPLATE TRANSFER PRINTING

The Copperplate Press—The Operation—Charging the Engraved Plate— Cleaning-off and Polishing—Making the Impression—Useful Notions	17-19
---	-------

CHAPTER V

THE LITHOGRAPHIC PRESS

Mechanical Principles — Constructive Details—Scraper — Tympan— Practical Suggestions—Elastic Bedding	20-23
---	-------

CHAPTER VI

LITHOGRAPHIC PRESS WORK

	PAGE
Preparing the Design—Treatment of an Ink Drawing—Chalk Drawings—Alterations—Value of Impressions—Offsets—The Lithographic Hand-roller—Proving—Registration—General Features—Transferring—A Commercial Necessity—Arrangement—Choice of Paper—Transference to Stone—Preparing the Forme	24-33

CHAPTER VII

MACHINE PRINTING

The Printing Machine—The Halligan—Some Mechanical Phases—Speed—Pressure—Levelling the Stones—Cylinder Brake—Inking Rollers—Damping	34-40
--	-------

CHAPTER VIII

MACHINE PRINTING—*continued*

Register—Atmospheric Conditions—The Key—The Gripper—Starting the Machine—Fixing the Stone—Strength of Colour—Grit—Making Ready—Regulation of Speed	41-46
--	-------

CHAPTER IX

LITHOGRAPHIC COLOUR PRINTING

A Commercial Value—Peculiar Features—Colour Sequence—Controlling Elements—A Question of Register—Suitable Paper	47-51
---	-------

CHAPTER X

LITHOGRAPHIC COLOUR PRINTING—*continued*

Printing Inks—Varnish—Reducing Medium—Relative Values—Some Useful Hints—Bronze Blue—Vermilion—Ink Mixing—Ceramic Transfers—Colour Transparencies	52-56
--	-------

CHAPTER XI

SUBSTITUTES FOR LITHOGRAPHIC STONES

Metal Plates—Preparation—Manipulation—Descriptive Details—Machine Printing—The Printing Bed—Rotary Printing Machine	57-66
---	-------

CONTENTS

ix

CHAPTER XII

TIN-PLATE PRINTING

	PAGE
Its Evolution—Transfer and Direct Transfer Printing—The Coated Paper—Reversed Designs—Sequence of Printing—Printing Inks—Purity of Tone—Drying	67-71

CHAPTER XIII

TIN-PLATE PRINTING—*continued*

Direct Tin Printing—The Machine—Peculiarities of Impression—Cylinder Covering—Colour Sequence—Printing Inks—Drying Racks—Air-drying <i>versus</i> Stoving	72-79
---	-------

CHAPTER XIV

TIN-PLATE DECORATION

Suitable Designs—A Variety of Effects—Gold Lacquer—Super-position of Colours—Embossed Effects—Embossing Plates—Lacquers	80-83
---	-------

CHAPTER XV

PHOTO-LITHOGRAPHY

Early Experiments—An Analysis—The Direct Process—Transfer Process—Line and Half-tone—Some Difficulties—A Natural Grain—Ink Photo-screen Effects—Essential Features	84-88
--	-------

CHAPTER XVI

PHOTO-LITHOGRAPHY—*continued*

The Copy—Gradations of Tone—"Scraper Boards"—Description and Effect—Shading Mediums—Crayon Drawings—Half-tone Copy	89-95
--	-------

CHAPTER XVII

PHOTO-LITHOGRAPHY—*continued*

A Copying Table—Exposure—Illumination—Photo-litho Transfers—The Paper—Printing—Developing—A Direct Process	96-101
--	--------

INDEX	102-104
-----------------	---------

ILLUSTRATIONS

	PAGE
ALOIS SENEFELDER	<i>Frontispiece</i>
STONE-PLANING MACHINE	4
STONE-POLISHING MACHINE	5
COPPERPLATE PRESS	17
HOT PLATE	18
LITHOGRAPHIC PRESS	21
DETAILS OF LITHOGRAPHIC PRESS	22
LITHOGRAPHIC HAND PRESS	23
LITHOGRAPHIC HAND ROLLER	28
REGISTER LINES	30
ARRANGEMENT OF TRANSFERS	32
TRANSFERRING BOARD	32
LITHOGRAPHIC PRINTING MACHINE	35
HALLIGAN MACHINE	36
PRESSURE MECHANISM	38
INKING ROLLERS	39
DAMPING ROLLERS	40
GRIPPER	42
TRIMMED EDGES	43
COUNTER SHAFTING	44
MOTOR DRIVING	45
PLATE-GRAINING MACHINE	59, 60
PLATE BED	62
ALUMINIUM ROTARY MACHINE	63
ALUMINIUM ROTARY SECTION	66
TIN-PLATE PRINTING MACHINE	73
TIN-PLATE RACKS	78, 79
METHOD OF STACKING PLATES	79
SCRAPER BOARD WORK	91
SCRAPER BOARD TEXTURES	93
PHOTOGRAPHIC COPYING BOARD	97



PRACTICAL LITHOGRAPHY



CHAPTER I

ELEMENTARY DETAILS

Concerning Stones—Character and Texture—Some Simple Elements—Preparation of Stones—Planing and Levelling—Grinding Grained Stones—Descriptive Treatment—American Method.

THERE are a vast number of details in connection with lithography and lithographic printing which are indisputably elementary in their character. It would be impossible, however, to regard them as non-essential, and a just appreciation of their value and influence must of necessity enter into any comprehensive exposition of the craft.

Stone as a printing medium.—The value of the Bavarian limestone was one of those fortunate discoveries which tended to materialise lithography as a graphic art, and may even be regarded as a fundamental principle, the practical value of which is only equalled by its far-reaching effects.

Other printing surfaces have been discovered and developed, with more or less substantial results, yet without depreciating their merits, it will be but a fair recognition to concede the premier position to the Solenhofen and other limestones of a like nature.

The homogeneity and porosity of these stones render them peculiarly suitable for lithographic purposes, and it undoubtedly reflects a vast amount of credit upon Senefelder that even at the outset he should select a medium so well adapted and in every way so eminently suitable for graphic reproduction.

I have already, and almost inadvertently, indicated the peculiar value of the Bavarian stone, for homogeneity and porosity of texture are absolutely essential properties, and upon these is based almost every theory which has assisted in the development of this craft. These properties, in conjunction with a suitable greasy pigment, provide the requisite materials for that cause and effect which require and compel consideration.

The simple elements of lithography may be very briefly described, and in this direction at least we must follow certain well-defined lines which may be regarded as well-worn ruts, the consideration of which offers little that is new.

A brief review of the theories of chemical and mechanical affinities is best calculated to impress upon the mind the elementary principles of the lithographer's art.

The penetrative power of a greasy pigment, together with the porous nature of the litho-stone, may be regarded as the cause by which the lithographer produces as an effect a design or impression which, to some extent, enters into the texture of the stone—the homogeneity of which checks any tendency to *spread*. This fatty matter may be applied in one or two ways, either, as a transfer from some other printing surface, or as a direct drawing with pen, brush, or crayon.

The first question for consideration will be the initial preparation of the litho-stones. These preparatory operations—which have for their object the levelling, polishing, and cleaning of the stones—were at one time entirely per-

formed by hand labour, but are now accomplished with much greater facility and in a more effective manner by machinery. The importance of each individual operation will be more readily appreciated when once its purpose is clearly understood. A litho-stone having a *perfectly level* surface is necessary in order to enable the printer to secure a firm and uniform pressure over the whole design when printing therefrom. A *smooth, polished* surface will readily receive the finest designs, and retain all their original characteristics. A *clean* surface is an absolute necessity, *i.e.* a chemically clean surface free from grease or any foreign matter which would be likely to enter into the texture of the stone and by so doing injure any greasy drawing or transfer which might be made thereon.

These are simple, elementary principles, and as such are probably familiar to every reader, but the frequent result of familiarity is a dangerous tendency to underestimate the importance of everyday causes and effects. If, therefore, such a reference as the above to common details serves to convey some intelligent idea of their place and true value, then no apology whatever will be necessary for their insertion in this volume. It has already been stated that, in the preparation of litho-stones, the superseding of hand labour by machinery has effected considerable and important changes.

Several machines, all of more or less practical value, have been introduced to the trade. One of the more recent developments, a stone-planing machine, possesses many features of real merit (Fig. 1).

The stone is securely fixed on a perfectly true bed and passes slowly to and fro beneath the blades of powerful cutting knives. These blades are arranged in an inverted V-shape and locked in an oscillating framework. By an automatic action they are almost imperceptibly lowered at

each traverse of the machine, when they lightly cut away the surface of the stone until the old work is completely removed and a smooth level face is assured. The chief objection to this type of machine is that in course of time the knives become worn and slightly irregular, and it is but reasonable to suppose that when a number of small stones have been operated upon and immediately afterwards a full-sized stone is planed, such irregularities will be very pronounced and detrimental.

Many machines have been designed on the simple grind-




FIG. 1.

ing principle, but one type differs from its contemporaries and offers several distinct advantages over them (Fig. 2).

This machine is constructed on hand-polishing lines, *i.e.* the movements are to some extent mechanical arrangements of hand-polishing principles. The size of stone makes no difference whatever, and the results are in the main uniform and satisfactory. The inconveniently sharp edges, such as are produced by the planing machine, are unknown,—the wear and tear on the stone is perceptibly lessened, and the power required to drive such a machine is not by any means a serious matter.

When a planing machine does not enter into the operation, and grinding by hand is therefore necessary, sharp,

clean sand should be used as a grinding medium. To secure some degree of uniformity in the grain, and at the same time remove all the larger particles of grit, pass the sand first through a fine sieve. The harder qualities of sand have, of course, the greatest cutting power, and therefore are the most suitable for this purpose.




FIG. 2.

When hand-grinding is resorted to, a continuous elliptical motion of one stone over the other with a slight twist from the wrist will prove most effective.

To finish the grinding, and as far as possible remove the deeper sand scratches, work off the sand in the form of a *sludge*. Unless this operation is carefully and patiently performed, scratches of considerable depth may appear on

various parts of the stone's surface. These, in the subsequent polishing, may offer a strong temptation to the operator to work over one part of the stone more than another, so as to effect the removal of such scratches with greater rapidity. The almost certain result of this would be an uneven surface, which would in many ways prove troublesome to the printer.

The graining of stones.—This is a matter concerning the preparation of stones which must not be overlooked. The introduction of shading mediums and other contrivances of a similar character has considerably minimised the importance of the grained stone, inasmuch as it cannot now be regarded as an indispensable feature of lithography. It is, however, still of inestimable value, and will probably always find a place and purpose in the practice of lithography, despite its depreciation owing to present-day limitations.

Recognising, then, the possibility of its retention, at least for some time to come, as a suitable printing surface upon which the lithographic draughtsman can work with undoubted facility of execution and effect, we must perforce include a brief description of its preparation in this chapter.

First of all, level the stone and to some extent polish it, after which the graining may be proceeded with. A glass muller about 6 or 7 inches in diameter makes an excellent "grainer." Failing this, a handy substitute will be found in the form of a small litho-stone, hard in texture, and with a smooth, level surface. Use as a graining medium sharp, clean silver sand only, passing it carefully through a sieve according to the size or depth of the grain required. Sprinkle a little of this sand uniformly over the stone under treatment, together with a few drops of clean water. With a continuous circular movement pass the graining muller from end to end of the stone, exerting a firm and uniform pressure. Repeat this operation again and again, adding

sand and water as required. Considerable time coupled with intelligent application will be necessary to carry out this work successfully. Should the sand become too much worn before its renewal the grain will in proportion lose its "tooth" or sharpness. On the other hand lies the danger of producing a grain which is too harsh or pronounced. Therefore much depends upon the skill and judgment of the operator. A safe plan is to ascertain the progress at any time when a satisfactory result might be reasonably expected. The best way to accomplish this is by washing from the face of the stone any accumulation of sand, and drying it, so that a test can be made with the actual grade of crayon to be used in the subsequent drawing. A powerful current of clean, cold water affords the best means for removing every trace of sand from the finished stone, and will leave it in a condition of almost complete readiness for the draughtsman; a good drying is then all that is necessary. Good results have been claimed for a method of graining which was introduced by the Americans a few years ago. In this process the grain is produced by sprinkling the surface of the stone with sand and rolling it with small glass balls. These balls having a limited area in which to work exert a continuous cutting power without any tendency to produce scratches. Some mechanical arrangement is necessary to impart this continuous rolling movement to the glass balls and to maintain a uniform speed. It is quite easy to understand that with such a process, carried out under favourable conditions, very fine results might be produced with great rapidity.

CHAPTER II

LITHOGRAPHIC TRANSFER INKS

Various Forms—Distinguishing Features—Formulæ—Writing Transfer Ink—Stone-to-stone Transfer Ink—Copperplate Transfer Ink—A Modification.

GIVEN a perfectly clean and smooth polished stone as described in the previous chapter, the next important point is the composition of the fatty matter wherewith a design or drawing is applied.

As already stated, the active principle in any suitable transfer medium of this character is invariably the same, no matter what form its composition takes. For applying with pen or brush it must possess soluble properties, and of necessity be reduced to a liquid form. Such soluble properties, however, must not interfere with its fatty properties, these latter being essential features.

In crayon or *chalk* drawing the composition must be employed in a concrete form, as a crayon, the hardness and texture of which will be controlled (1) by the character of the work to be carried out; (2) by the character of surface to be operated upon.

Transfers from other printing surfaces can only be made when the composition used is in the form of a pigment, and reduced to a convenient working consistency.

These, then, comprise the varieties of transfer mediums which are likely to be required in most phases of commercial lithography. Others are, of course, employed for specific

purposes and under peculiar conditions; but these, again, are more or less modifications of existing formulæ, prepared to meet particular requirements.

The ink used for transferring impressions from one printing surface to another, *e.g.*, the re-transferring of work from stone to stone, may with a very slight alteration serve for type to stone transfer; but a considerable departure must be effected to produce a satisfactory photo-litho transfer ink, while a composition of a peculiarly distinctive character will be requisite for the successful production of transfers from copperplate engravings, as well as for a transfer ink for writing and drawing on stone or transfer paper. This writing transfer ink must be soluble in water, yet without becoming slimy; otherwise it will not work freely with the pen or brush. It must also dry quickly, and without any tendency to smear.

A plate transfer ink must neither melt nor drag when applied to the hot plate. It must, of course, soften sufficiently to fill in the lines of the engraving, and should so harden as it cools that it cannot easily be dragged away during the cleaning and polishing operations. See Chap. IV. page 19.

Each and all of the above inks must be excessively greasy and penetrative, but without having the slightest tendency to spread superficially. The ingredients and methods of preparation specified in the succeeding paragraphs are not given as standard formulæ, but in corroboration of statements made, and as practical illustrations of the character and purpose of transfer inks and compositions generally.

Transfer ink.—Writing transfer ink, for writing or drawing on stone or transfer paper, may consist of equal quantities of:—

Castile soap,
Wax,

Tallow,
Shellac.

with the addition of carbon black or black printing ink as a colouring matter. Another reliable formula is:—

Soap	4 parts
Tallow	3 „
Wax	6 „
Shellac	4 „
Carbon black	1 „

Whichever formula is adopted the method of preparation is the same combination.

Free the soap from all moisture by drying, and thus facilitate its combining with the other ingredients.

Melt the tallow and wax over a hot fire until they are thoroughly well mixed. Add the dried soap a little at a time, so that it may become thoroughly incorporated with the wax and tallow. Bring the mixture to boiling-point, then remove it from the fire or stove and ignite the fumes which will then be rising freely. Continue the burning process for about fifteen minutes, then extinguish the flames by replacing the lid of the pan. The shellac and black may be added while the composition is cooling.

Stone-to-stone re-transfer ink.—The ingredients of this ink consist of:—

4 oz. Transfer ink.	4 oz. Medium varnish.
4 „, Litho black ink.	1 „, Canada balsam.

Melt the transfer ink over a slow fire and add the other ingredients separately.

Canada balsam will not only add to the effectiveness of this ink, but it will also improve its working qualities.

Copperplate transfer ink.—Ingredients consist of:—

1 oz. Tallow.	4 oz. Bitumen.
3 „, Bee's wax.	1 „, Canada balsam.
4 „, Shellac.	1 „, Carbon black.
2 „, Soap.	

The method in this case differs somewhat from the

preceding. First melt the bitumen and then add the wax and soap in small pieces as before. Burn this for fifteen minutes, and add the shellac, balsam, and black, boiling the whole gently for forty minutes. Mould into squares or sticks, and for convenience in handling cover these with tinfoil.

Should an extra powerful ink be required for shading or stippling films, the stone-to-stone re-transfer ink can be reduced to a working consistency with castor oil instead of varnish, and thus rendered suitable for this purpose.

CHAPTER III

LITHOGRAPHIC TRANSFER PAPERS

Essential Features — Varnish Transfer Paper — Damp-stone Transfer Paper — French Transparent Transfer Paper — Copperplate Transfer Paper — An Alternative Recipe — Granulated Papers — Photo-litho Transfer Paper.

TRANSFER papers are even more used than the transfer compositions already described, and in greater variety, in consequence of which there is a wide difference of opinion concerning their merits.

To a certain extent the specific value of any transfer paper must depend upon local conditions. That which might be of the utmost value to one printer would in all probability fail to meet the requirements of another. With these also, as with the transfer inks, the main point is to grasp the general principles involved. Adhering to these principles enables any intelligent workman to adapt the transfers to his own peculiar necessity. It is most important that lithographic transfer paper should be absolutely impervious to the transfer composition or ink, so that an impression of full strength can be conveyed to the stone, leaving its greasy properties unimpaired. The paper therefore must undergo special preparation, and here again the character of the work and the conditions under which it is carried out are the chief controlling elements. So much is this the case that many lithographic printers prefer to make their own transfer paper, and find such a procedure eminently satisfactory.

A good bank post double foolscap paper, about 26 lb., first thinly coated with a solution of concentrated size and afterwards varnished with a heavy coach body varnish, gives excellent results. When transferring large work in which a number of printings are involved, and where accuracy of register is a *sine quâ non*, the following mixture may, if desired, be substituted for the coach body varnish :—

Best oak varnish	.	.	.	1 quart.
Turpentine	.	.	.	$\frac{1}{2}$ pint.
Boiled linseed oil	.	.	.	$\frac{1}{2}$ „

Paper thus prepared rarely stretches or becomes distorted to any appreciable extent, and can be used with equally good results on either cold or warm stones.

Its keeping qualities are, however, limited; it is therefore advisable to utilise the transfer impressions with as little delay as possible.

This may be criticised as a somewhat primitive and old-fashioned transfer paper; but of the many transfer papers now in use, none can claim to be exactly new.

Another stone-to-stone transfer paper of the simplest possible character can be made by coating a good writing paper with the following composition. Soak 3 oz. of glue in 6 oz. of water for about 8 hours. Reduce 1 lb. of starch to a thick, creamy paste by rubbing it down in a little cold water and then adding boiling water until the required consistency is obtained. Mix the starch and glue together, and add a little gamboge or cochineal as colouring matter, so as to enable the printer to see at a glance which is the coated side of the paper. Spread this composition on the paper while it is still warm.

A transparent transfer paper with a soluble coating is frequently desirable, and for certain purposes may be strongly

recommended. A French transfer paper meets such a requirement, and at the same time possesses many other excellent qualities. It picks up a firm, clean impression, and transfers every particle of it to the stone. It is also transparent, and sufficiently adhesive to stick to a very slightly damped stone under a light pressure.

A transfer paper which may be used as a base upon which to write or draw a design for subsequent transference to stone, as well as for stone-to-stone transferring, should be coated with a composition of a gelatinous character, which will not be readily soluble in water. Writing transfer ink is of course dissolved in water, and its effect on a soft, soluble composition would be disastrous.

The following formula is suggestive as well as practical:—

Gelatine	4 oz.
Isinglass	6 „
Flake white	3 lb.
Gamboge	2 oz.

Make a strong size of the above by boiling the gelatine and isinglass with a little water. Mix the gamboge and flake white with a little warm water, and add the mixture to the gelatine solution. This composition must be applied to the paper while still quite warm, as it forms into a comparatively stiff jelly while cooling. This paper should be transferred to warm stones.

Copperplate transfer paper is to some extent a development of the variety just described; that is, if the conditions under which such transfers are made will bear comparison with operations of an essentially different character.

The composition used for coating copperplate transfer paper must possess a somewhat heavy body, and for this

reason plaster of paris enters into its composition, which is as follows:—

Plaster of paris	2 lb.
Flake white	1 „
Flour	2 „
Fish glue	$\frac{1}{4}$ „
Alum	1 oz.

Soak the alum and glue from 8 to 10 hours, and then boil them until they are dissolved. Make the flour into a smooth paste by the addition of a little water, and mix it with the flake white. Mix the plaster of paris with water, and stir continuously until it becomes incapable of setting. Add the other ingredients, already mixed, and see that they become thoroughly incorporated with the plaster of paris, after which coat the paper twice with the mixture.

The following may be substituted for the above:—

Plaster of paris	2 lb.
Flour	2 „
Gelatine	4 oz.

A transfer paper with its surface granulated to represent a mechanical stipple, or the texture of a grained stone, may be prepared in the following manner. Take of

Starch	9 oz.
Parchment chippings	12 „
Flake white	14 „

Prepare the starch as previously described, and dissolve the isinglass by boiling. Mix the flake white into a thin paste by the addition of water. Warm the three ingredients, and mix the whole thoroughly. Coat a fairly heavy printing paper twice with this composition, and when it is thoroughly dry give it the required granulation by means of grained stones or engraved plates. The grain thus imparted breaks up the drawing into a series of minute dots. Paper of this description is most suitable for pencil or crayon work. Its

usefulness is obvious. It enables the artist to use his chalks in the usual manner, without the inconvenience of handling large stones. No graining of the stone is necessary, and the grained effect can be confined to any portion of the design.

Photo-litho transfer paper is in every respect a specific article, the coating of which consists of a gelatinous emulsion, which can be readily sensitised, and upon which a photographic image can be developed. Special preparation and manipulation are therefore necessary in connection with its production, and these points will be fully dealt with in a subsequent chapter.

One more variety of transfer paper should be mentioned, namely, the diaphanic, which possesses excellent qualities for certain classes of work. It is very transparent, and extremely useful in the tracing of key formes, or for making facsimile drawings for immediate transference to stone.

CHAPTER IV

COPPERPLATE TRANSFER PRINTING

The Copperplate Press—The Operation—Charging the Engraved Plate—Cleaning-off and Polishing—Making the Impression—Useful Notions.

ALTHOUGH copperplate printing may not now be so extensively practised as in years gone by, it is not, so far as we can judge, very likely to be superseded in the near future. It is still regarded as a necessary adjunct to lithography, especially where the amount of commercial work produced is of any moment.

From a purely mechanical point of view the construction of the copperplate press (Fig. 3) is of an exceedingly simple character. Its primary purpose is to produce a heavy and uniform pressure on the plate during operation.




FIG. 3.

After being charged with a special pigment and cleaned as hereafter described, the plate is laid, face upwards, on the iron

bed or table of the press and in contact with the paper, and passed through between two iron cylinders. These cylinders are so adjusted as to produce an exceptionally heavy pressure. Such are the simple elements of a process which, however, requires much closer investigation.

In its application to lithography the following are the only requisites for copperplate transfer printing.

A stick of prepared transfer ink—whiting, free from grit—transfer paper, and a plentiful supply of soft rags. Likewise, an iron plate with a gas jet underneath (Fig. 4), a square of printer's blanket, and a damp book consisting of twenty or thirty sheets of blotting or other absorbent




FIG. 4.

paper slightly and uniformly damped.

A good copperplate transfer paper can be made according to the recipe given in Chap. III., but unless a fairly large quantity is used the commercial qualities will be found most economical.

Copperplate printing, in its application to lithography, is a simple operation, but it requires extraordinary care for its successful execution. The conditions under which lithographic transfers are made from a copperplate engraving are vastly different from those which control copperplate printing for ordinary purposes of reproduction.

The engraved plate is first well heated by means of the hot plate already mentioned. The transfer ink is then *forced* into the engraved parts until every line is fully charged, the ink having been previously enclosed in a double fold of soft rag.

During this part of the operation great care must be

taken that the transfer ink does not burn through overheating, as this would partially destroy its greasy nature and leave it hard and brittle. The transfer impression would suffer in consequence, and, though to all appearance perfect on the paper, it would be weak and ineffective when applied to the lithographic stone. Such an error of judgment is not at all unusual, and should therefore be the more carefully guarded against. It frequently occurs without the knowledge of the operator, owing, it may be, to his over-anxiety to complete his work in as short a time as possible.

The plate must now be cleaned, *i.e.* the surplus ink and scum must all be removed. This may be done before the plate is quite cool, and after a little experience it will be possible to accomplish the cleansing process without in any way disturbing the ink in the lines of the engraving. The rag used for cleaning must be tightly folded into the form of a pad and kept free from creases. After final cleansing and polishing with whiting the plate is ready for an impression. The transfer paper requires damping until it is quite limp, when it is brought into contact with the inked plate and subjected to a very heavy pressure. The backing is a woollen blanket, preferably of fine texture; this ensures perfect contact between the plate and the paper. The plate is now very slightly warmed to dry the transfer paper, which is allowed to peel off; this it does very readily if, after a little while, the corners and edges are but slightly eased.

Oil of tar will effectually remove any accretions of copperplate transfer ink which may have hardened in the lines of the engraving.

It may be useful also to know that it is possible to use a small lithographic press in place of a copperplate press, assuming, of course, that a sufficiently heavy and uniform pressure can be guaranteed. This is not altogether an innovation, yet it is not a familiar notion.

CHAPTER V

THE LITHOGRAPHIC PRESS

Mechanical Principles—Constructive Details—Scraper—Tympan—
Practical Suggestions—Elastic Bedding.

It is not a little surprising to find that the mechanical principle of the lithographic press in general use to-day is almost identical with that which the pioneers of the craft employed so successfully. This is an interesting fact which either reflects much credit upon the ingenuity of the early lithographic printers or points to an unreasonable conservatism on the part of the present-day craftsmen. A discussion of this phase of the question would be of doubtful interest, for the practical printer has long been accustomed to regard it simply as a convenient appliance for the production of a heavy and readily adjustable pressure.

A brief examination will prove to what extent these requirements are fulfilled by the modern lithographic press (Fig. 5).

The simplicity of its construction suggests a first point for favourable criticism. In fact, its general mechanical arrangements are so exceedingly simple that the merest tyro might readily understand their principles and purpose.

The adjustability of the pressure by means of the screw D (Fig. 8) is both effective and necessary, owing to the constantly varying thickness of the lithographic stones.

The pressure of the boxwood scraper B on the surface of

the stone is perfectly rigid, and yet, owing to the intervention of the tympan C, is sufficiently elastic to ensure the closest possible contact. Figs. 6 and 7 show one or two constructive details by which the hand lever A and the cam motion E bring up the cylinder F to the bottom of the carriage or bed of the press, Fig. 8.

It is in this position that the movement of the carriage





FIG. 5.

gives the necessary pressure required to pull an impression. The shaft H runs across the press and operates a similar cam to E on the opposite side. These two cams raise the brass block G and give the requisite support to the cylinder F when the pressure is applied.

These are the chief characteristics of the lithographic press, and as such they require not a little attention and intelligent manipulation. It is practically impossible to

secure a steady and uniform pressure unless the scraper and tympan are carefully adjusted.

The former must be perfectly true with its V-shaped edge nicely rounded, and the latter tightly stretched on the frame C so that it will not sag or bulge when pressure is applied and the scraper passes over it. To reduce the enormous friction caused by this pressure the back of the tympan is usually dressed with a mixture of tallow and plumbago, a dressing which requires frequent renewal. The plumbago possesses but little body, and its salutary effect soon passes away. To prevent this and to increase its adhesiveness it



Figs. 6 and 7.

is sometimes mixed with a little gum. A mineral black which is found in large quantities in the west of England is even more effective than plumbago for this purpose. It forms a strong and flexible dressing for the leather, is peculiarly adhesive and provides an efficient lubricant.

It is a decided advantage to have two tympan in use, one for small stones and another for the larger sizes. It is obviously

unwise to pull a number of impressions from small stones with a large tympan, for if this practice is persisted in the tympan leather not only loses its shape, but becomes perceptibly thinner on such parts as may have been most subjected to pressure.

For similar reasons it is advisable to have a number of boxwood scrapers of different sizes. The "dents" produced by a small stone on a large scraper can only be removed by planing.

In lithographic press work some form of elastic bedding

placed underneath the stone will not only materially assist the pressure, but will also minimise the risk of breakages. In fact, the pressure is frequently so keen and of such a direct character as to render this arrangement little short of a necessity. Extra thick linoleum will serve this purpose




FIG. 8.

admirably, and a zinc covering for this bedding will complete the equipment of the lithographic press.

The operations directly associated with lithographic press work are of sufficient importance to warrant a full description of each, and will form the nucleus of the following chapter.

CHAPTER VI

LITHOGRAPHIC PRESS WORK

Preparing the Design—Treatment of an Ink Drawing—Chalk Drawings—Alterations—Value of Impressions—Offsets—The Lithographic Hand-roller—Proving—Registration—General Features—Transferring—A Commercial Necessity—Arrangement—Choice of Paper—Transference to Stone—Preparing the Forme.

THE operations directly associated with lithographic press work are more or less of a preparatory character. The preparation of a design, in its progressive stages, from the lithographic draughtsman to the printing machine, is usually carried out in conjunction with the press. Only under exceptional conditions or for some particular class of work is the lithographic press actually employed for printing purposes. Its ready adaptability to the ever-varying thickness of lithographic stones, and the manner in which pressure can be applied at will, as well as the intense sharpness of such pressure, render it peculiarly suitable for the work now under discussion. Such operations will be better understood and probably more easily remembered if they are described in a sequence such as might be presented under average commercial conditions. Taking a design as it leaves the lithographic draughtsman, *i.e.* in the form of a greasy drawing on stone, the first object of the printer is to so prepare it as to preserve the conditions described in Chap. I. page 2. This he may accomplish in the following manner.

Cover the whole stone with fresh strong gum and allow it to dry. Then if it be an ink drawing, wash off the

gum with water, and remove the drawing ink from the surface of the design with a few drops of turpentine and a piece of clean rag. Proceed to roll up with a lithographic hand-roller charged with good black printing ink. The consistency of this printing ink can only be determined by the character of the work under treatment. It is therefore a matter of experience rather than rule. Heavy designs covering large areas can be worked up with moderately thin ink, while work of a finer description will most probably require a stronger ink for its successful treatment. Between these two extremes there is a variety of conditions and effects which will require a ready recognition and an intelligent adaptation or modification of any operation which may be described. It may even be advisable to *rub up* the work with a piece of soft rag and printing ink, but the clearness and crispness of the drawing can best be preserved by a complete removal of the greasy ink with which the drawing was originally made. More particularly is this desirable when heavy, solid work is in close contact with work of a finer description, for the excessively greasy character of the artist's drawing ink has a dangerous tendency to smear or spread and to thicken the design, unless a reasonable amount of care is exercised. After rolling up the work as well as possible, and having decided that it is firm and strong and is fully charged with ink, dry the stone perfectly and dust over the design with finely powdered resin or French chalk. With a piece of water of Ayr stone polish away any scum or dirt which may surround the work, and etch it quickly with a weak solution of nitric acid. Cover up with strong gum and dry it. The design is now ready either for proving or transferring.

The treatment of chalk drawings, grained stones, or transfers from grained paper needs a slight variation of the

operations already described. The preliminary etching is generally carried out by the draughtsman by flooding the stone with a mixture of gum and acid, after which the gum solution is allowed to dry. The chemical change which takes place during this etching is often described as one in which the soap present in lithographic chalks is changed to an insoluble compound. This chemical change is perhaps a somewhat contentious matter, but the effect and not the principle involved is to us the matter of primary importance, and this effect is such as to actually prevent any spreading of the design on the stone beyond the lines of the original drawing.

Returning once more to the operation, wash off the gum, and, having removed the excess of water in the usual way, roll up firmly with a strong black ink. Instead of washing out the drawing with turpentine immediately, work off the original chalk by rolling up with a good nap roller and taking frequent impressions. In this way the grain of the drawing will be gradually developed and rendered fit for further operations. The stone can then be passed to the prover or transferrer.

A French writer, in referring to the importance of really good *chalk* drawing and printing, as well as to its artistic and technical value, once said: "The printer requires a fair appreciation of that subtle suggestiveness which gradations of tone can impart to a chalk drawing before he can hope to successfully reproduce the artist's original conception. A good printer handles his roller over a chalk drawing with the same feeling as that with which a violin player handles his bow. By movements rapid or slow, and by greater or less pressure over certain parts, he charges the drawing to the proper tone."

If at any time the original work requires alterations, they may be executed in the following manner. Roll up

the design firmly in strong, black ink, and, after fanning the surface dry, dust it over with French chalk. Make the necessary erasures with water of Ayr stone and etch with fairly strong nitric acid. Polish slightly, and wash well with a plentiful supply of clean water. Pour over the stone a very weak solution of alum, and again wash thoroughly with hot water, so that its rapid evaporation may leave the work ready for immediate manipulation. Alterations may be made by transferring or drawing. In either case it is advisable to gum up the work with strong gum and allow it to stand until dry. The subsequent treatment of any alteration will, of course, depend upon their character and extent. As new work, they should be carefully handled.

It is most important that a very *weak* solution of alum should be used. Being an alkali, a strong solution would have a tendency to dissolve the greasy particles of the drawing and cause them to spread and thicken.

It is always advisable to take an impression from each design, whether it be in ink or crayon, before it is laid aside for subsequent manipulation. These impressions will not only reveal any inaccuracies or weaknesses which might otherwise pass unnoticed, but also serve as a useful record and for comparison with other transfers or impressions which may be required.

There are other phases of preparatory work which come within the scope of the lithographic pressman, and as they frequently constitute an intermediary stage between the first drawing of the draughtsman on stone and the making of transfer impressions to facilitate reproduction, a description at this point will be appropriate.

It may be that a key forme only has been prepared, or perhaps an outline forme with sufficient detail. In either case a number of offsets equivalent to the number of colours

necessary for the completion of the design will be required. These are made by taking good, solid impressions in stiff black ink from the key or outline forme. Dust these over with a mixture of three parts Venetian red and one part lamp-black. Lay them in convenient positions on a well-polished dry stone, and run them through the lithographic press with a light yet firm pressure. The result will be faint yet sufficiently clear offsets of an outline which will enable the lithographic draughtsman to prepare any number of formes, and these will register or fit each other and the original drawing with perfect accuracy. Such outlines will in no way affect the work of the draughtsman, and will disappear at the first application of the gum sponge or moisture in any form.

A lithographic *nap*-roller (Fig. 9) facilitates the work of



FIG. 9.

the pressman in the preparation and development of original drawings on stone, and becomes an ab-

absolute necessity when crayon drawings on grained stones are operated upon. The preparation and preservation of a roller of this description requires a more than average amount of care and attention. The best rollers are covered with French calf-skin with a soft, velvet-like nap, and may be prepared as follows. Run the roller in crude castor oil for a short time until the leather becomes soft and pliable, then work out the superfluous oil by repeated rolling in medium varnish, occasionally scraping off the varnish with a broad blunt knife. Continue this for a day or two, then gradually work into the skin some good non-drying black printing ink. The roller thus prepared may be somewhat harsh, but a few days' use will bring it into condition. An occasional application of tallow or lard, say about once a week, will keep the roller skin soft and pliable, and counteract the

hardening effect of constant contact with the damp surface of the lithographic stone and the oxidisation of the printing ink.

• Proving the work of the lithographic artist, though not always an absolute necessity, is a helpful and most important function. In its progressive stage it enables both designer and lithographer to observe the realisation of their colour schemes, and to amplify or minimise if necessary the effects they desire to produce. Errors of judgment or of detail can be rectified before the work reaches a more advanced stage. Again, a finished proof offers something of a tangible character for an expression of approval or disapproval, and serves as a useful and helpful guide to the printer throughout the subsequent operations.

This will show clearly the importance of the prover's work, and though it is not by any means an unusual proceeding to *prove up* even the most elaborate designs in the lithographic printing machines, it is, for obvious reasons, more convenient to confine such work to the press. It may therefore be regarded as an intermediate operation, distinctly apart from the preparation of the original drawing which precedes it, and the arrangement for machine printing which follows. The distinctive and pre-eminently the most important feature of proving is the manner in which one colour is registered with another; and although the methods usually adopted are of the simplest possible character, the most scrupulous care is requisite for their successful application. It appears to be an almost ridiculous plan, so simple is it, to cut away the angles formed by the register lines after the first printing (Fig. 10A), and then to place them to corresponding lines on each colour forme, or to pierce the register lines as in Fig. 10B, passing a fine needle through each puncture into corresponding holes drilled in the stones and allowing the sheets to fall into position,—yet these operations demand constant care and attention.

The mixing of colours for proving, and the general principle of their application, are matters which are almost entirely under the control of the printer. Their selection and the manner in which they are employed are both determined by the individual character of the work. It is impossible to indicate any "rule of thumb" guide for their application or manipulation. The individual fancy of the artist, or the wish of a customer, are the only probable complications which may have to be considered. Then again, many phases of the work are more or less experimental,



FIG. 10A.




FIG. 10B.

when the resourcefulness of the printer may be tested, and the mechanical features of his work be relieved by the exercise of intelligent application, if not of artistic perception. Very rarely is it possible to print from the litho-draughtsman's original drawing, and even when it may be convenient to do so, it is, in the majority of cases, inadvisable on account of the element of risk

involved. There is an ever-present danger of the stone breaking,—a catastrophe which would necessitate an entire reproduction of the design, and even under the most favourable conditions the constant attrition produced by the rollers, etc., would have an appreciable effect on the work, and in course of time destroy its value for graphic reproduction.

Many other equally cogent reasons why duplicates of the original should be made for printing purposes present themselves. The chief of these is an essentially commercial one. To reproduce half a million impressions from a single small drawing would obviously depreciate the commercial value of

lithographic printing very considerably, and although there is no record of the circumstances under which the duplicating of original work by means of transfers was first evolved, it is only reasonable to suppose that it was the direct outcome of a necessity which was as peremptory in its demands as it has been far-reaching in its effects. The method is one by which any number of impressions can be made on a suitably prepared paper, and with a sufficiently greasy pigment. These can be re-transferred to a lithographic stone, and in this way facsimiles of the original may be secured and arranged in the manner most convenient for machine printing. Great care is necessary in making these transfer impressions. They must be perfectly solid, yet not overcharged with ink, *i.e.* they must be clean and sharp, and as nearly an exact replica of the original work as it is possible to make them.

That the further description of these operations may be as lucid and practical as possible, we will apply it to ordinary work-a-day conditions, and suppose that a design in three workings has been lithographed and prepared for transferring as already described. The size of the work is $7\frac{1}{4}$ in. by $4\frac{1}{2}$ in., then the paper on which it is to be printed ought to be double crown, 20 in. by 30 in. This will allow $1\frac{1}{2}$ in. for the gripper and $\frac{1}{2}$ in. margin at the back and sides. Sixteen transfers can be pulled from each colour forme on a thin, transparent transfer paper. Mark out a sheet of stout paper as in Fig. 11, and arrange the transfers in the position indicated by the dotted lines. The gripper margins A A are determined by the construction of the machines, and may be varied accordingly.

Varnished transfer papers may be laid down on a slightly warmed dry stone, and if French transfer paper be used the stone must be slightly damped. If the sheet of transfers is laid down to a board—Fig. 12—uniformity of gripper margin

will be assured throughout the series, and the work of the machine printer facilitated.

Pull it through the lithographic press with a gradually increasing pressure in the usual way. The varnish transfer




FIG. 11.

paper will be sufficiently tacky to adhere slightly to the surface of the stone, so that the pressure may be repeated again and again with perfect safety. It may not be possible to remove the base upon which they were arranged, as it is



FIG. 12.

usual to secure them in position with paste. At this point the manipulation of the two varieties of paper differs slightly. The thin, transparent variety is usually fastened down to its paper base with syrup, glucose, or some sticky composition of a similar character. This paper backing can be removed immediately after sufficient pressure has been applied to fix the transfers to the stone. As this transfer paper is adhesive it is necessary to damp the surface of the litho-stone before it is laid down, when, of course, it will readily adhere, even under a moderately light pressure.

The further preparation of work, after being transferred in this manner, is in many respects similar to the treatment of new work, but with this important difference. A new transfer should almost invariably be worked up with a soft rag and black ink, the latter being thinned down with turpentine and varnish. Gum up the work, and allow the gum to dry. Roll a piece of soft rag into a pad, and charge it with printing ink which has been thinned down. Wipe off the gum on the surface of the stone, leaving only a thin film over the work. Rub up the transfers with the rag already prepared, and when fully charged with ink cover them with fresh gum. If possible they should stand for one or two hours, when the rolling up and etching may be proceeded with.

Accuracy of register can be ensured by the second and third sets of transfers being patched up to the first forme in the following manner.

Make two fairly strong black impressions of this forme on a stout unstretchable paper. Fix these up on a glass frame in such a position as to allow the light to pass through them, and carefully place each transfer in its exact position. They can then be laid down on separate stones in the same way as the first set. These are the simple outlines of the transferring process. In detail they may, of course, be modified to meet the exigencies of peculiar conditions, which in lithography are frequently the controlling powers, and at all times are matters of vital importance.

CHAPTER VII

MACHINE PRINTING

The Printing Machine—The Halligan—Some Mechanical Phases—Speed
—Pressure—Levelling the Stones—Cylinder Brake—Inking Rollers
—Damping.

CONCERNING the structural qualities of the various types of lithographic printing machines now in use, much might be written and divers opinions expressed. In this respect, however, it would be invidious to suggest that one maker's machines were better than another's, and such would be the natural trend of a discussion on these lines. The machines all have, it is true, many points in common where comparisons would be legitimate and easy. Yet, on the other hand, they each possess distinct advantages which will no doubt appeal to the printer individually, in proportion to their suitability or otherwise for his particular work. Conviction will follow experience in these matters, and any decision arrived at after this fashion may be regarded as a useful and valuable acquisition.

The illustration on page 35 (Fig. 13) gives a fair general idea of the modern lithographic machine.

Fig. 14 illustrates a somewhat novel type of lithographic printing machine, in which the gripper is entirely dispensed with, the sheet being held to gauges by the operator until caught between the small cylinder and the stone, when pressure is immediately applied. The stone is simply blocked up in the bed of the machine and the position of the print

on the paper assured by moving the gauges. This useful little jobbing machine is a decided innovation, and the simplicity of its construction is only equalled by the precision of its movements.

Lithographic machine printing presents many peculiar features, each one of which requires careful and constant attention for their successful operation. Some of its purely mechanical aspects—the care of the machine and its accessories,




FIG. 13.

together with their various functions and applications—offer a wide scope for resourcefulness and ability of a high order. The primary purpose of the machine itself was undoubtedly to accelerate the reproductive power of lithography from a commercial point of view; and throughout the entire course of its development the aim of the engineer has been to produce a printing machine with an ever-increasing capacity

for reproduction. It does not follow, however, that the printer's responsibility has been proportionately increased. Mechanical appliances have now so far superseded hand labour that, apart from a thorough knowledge of the principles of lithography, which is in itself essential, successful lithographic machine printing is largely due to resourcefulness, alert perception, and a skilful blending of mechanical and technical knowledge.

Passing over the vast amount of detail which is usually and almost invariably associated with machine printing, but




FIG. 14.

which offers little that is new to the practical worker, it might be advantageous to discuss a few points which are too often overlooked.

Speed, as has already been pointed out, is a very important factor in lithographic machine printing. It has become quite a necessity, and everything which conduces to it should receive the most careful consideration. Economy of power is too seldom regarded as a standard of efficiency in the printer. At any rate, as far as this is concerned it is doubtful if he

fully realises the effect of what may appear to him as insignificant matters. A little pressure more or less on the stone may be in itself a mere trifle, so also would be a careless arrangement of the inking rollers or indiscriminate damping of the stones, yet, when taken together, what a considerable waste of power they might cause;—a waste which is altogether unnecessary and could easily be obviated by care and forethought. Excessive pressure is frequently resorted to in order to “bring up” an impression which is defective owing to some error of judgment in its preparation. It undoubtedly secures the desired effect, but at what a cost! There is a proportionately heavier drag on the machine and a greater strain on its most vital parts. The following view of this matter may be regarded as somewhat exaggerated, but it is by no means an uncommon state of affairs, and will at least serve to emphasise the importance of this point. It is a popular fallacy to suppose that in adjusting the litho-stone to the bed of the printing machine it should be made *perfectly level*. As a matter of fact a much easier and more satisfactory impression can be made from a stone which is worked just a little higher at the front or gripper edge than at the back, and for this reason. The drag on the cylinder as it makes the impression is appreciably greater at the back than at the front, and when the pressure is heavy it has a tendency to leave the back edge with a very decided jerk. The remedy is obvious and simple. As already suggested, the stone should be set in the machine with the least possible inclination towards the front. This adjustment is easily effected by a judicious arrangement of a few layers of brown paper. Just think for a moment of the effect likely to be produced by such a jerk or jar, which would under ordinary working conditions occur from twelve to fourteen times per minute whilst the machine was in motion! Abnormal pressure would of course intensify the strain, and sooner or later produce results of a

decidedly disastrous character. Under the most favourable conditions this continual springing would tend to move the stone out of position, and thus affect the register of one forme with another.

Another certain result of this condition of things is, that the sharp pressure on the back edge of the stone would almost certainly cause an appreciable indentation in the cylinder covering. This would eventually cut through, or at least interfere with the working of a larger sheet at some future time.

The mechanism for raising or lowering the lithographic stone in the machine for the adjustment of pressure is comparatively simple (Fig. 15).

There are two screws similar to A which pass right through the feet of the stone carriage B B. A movement of the screws will therefore cause a corresponding movement of the stone carriage on the blocks or inclines C C. The lock-nut D holds the screw securely once the pressure is adjusted.




FIG. 15.

So few printers really understand the proper adjustment of a cylinder brake that some information concerning it will no doubt prove acceptable. In the first place, a continuous action brake which can be released at certain intervals is most suitable. It holds the cylinders perfectly rigid whilst the machine is running free, and applies a sufficient check at the points required. The intermittent movement referred to is obviated in various ways. Fig. 13 shows an example of one which is both simple and effective. It might be well also to explain the principle and purpose of the cylinder brake. It is almost impossible to cut mechanical gearing which will run easily and yet be entirely free from *slogger*. Consequently the revolution of a printing machine cylinder

would be more or less jerky unless steadied in some way. This is especially the case when it reaches the stone, and, owing to the pressure applied, lifts a little in the gearing. A recognition of this simple matter will enable an intelligent workman to arrange the brake action with judgment and effect.




FIG. 16A.

A comparison of the old arrangement of inking rollers (Fig. 16A) with the new (Fig. 16B) is in itself an object lesson in this question of power and its economical application. It is but reasonable to suppose that the power required to move a set of rollers arranged in the old-fashioned manner (Fig. 16A) will be infinitely greater than that




FIG. 16B.

which would be needed for such an arrangement as shown in Fig. 16B.

Pursuing this matter still further, the question of indiscriminate damping presents itself. Granted that the influence here is an indirect one, yet it is a cause which

frequently leads to an undesirable finish. Every printer knows something of the effect produced by excess of water upon printing inks. It hardens and stiffens them by accelerating oxidisation. In course of time their free working on the rollers is interfered with, and loss of power is by no means the worst result. Weak and impoverished impressions, abnormal wear and tear of the printing forme, and excessive saturation of the paper may follow.

In lithography generally, and in lithographic machine printing particularly, the damping of the stone is a matter which requires constant and careful attention; any arrangements for this purpose should therefore be as effective as




FIG. 17.

possible. The damping rollers should be thoroughly cleaned each day, in order to remove any scum or grease which may have been collected from the printing forme.

The arrangement of damping rollers shown in Fig. 17 is a decidedly practical one. The upper roller consists of metal, usually brass or zinc. It collects any accumulation of ink or scum from the actual dampers, and can be cleaned at any time without serious interference with the progress of the work. Its adoption, however, has not been very general, although it would be difficult to ascribe any good reasons for such a fact.

CHAPTER VIII

MACHINE PRINTING—*continued*

Register—Atmospheric Conditions—The Key—The Gripper—Starting the Machine—Fixing the Stone—Strength of Colour—Grit—Making Ready—Regulation of Speed.

It is almost impossible to overestimate the importance of register in lithographic machine printing, and any suggestions which are likely to be of assistance to the printer in this matter will no doubt be welcomed.

Variable atmospheric conditions, insufficiently matured paper, or constitutional defects in the machine, are frequent sources of inaccurate register. These may be to some extent unavoidable and therefore beyond the printer's control, but there are numerous other points which have an important bearing upon the accurate fitting of one colour or forme with another, and therefore require care and attention. The following method of procedure is well worth consideration, as it has decided advantages over many others.

The *key*, or outline forme, to which the colour formes have been set up, is put into the machine at the beginning of the printing operations. The exact position of the design on the sheet is arranged, and twenty or thirty impressions taken on a reliable paper. With these impressions as a guide it is a comparatively easy matter to register each colour accurately. This effects a saving both in time and material, and rarely fails to produce satisfactory results. During the early stages of the printing, when it is difficult to detect any

slight movement of the stone in the machine, a sheet bearing an impression of the key may be printed in the usual way, when any variation in register will be revealed at a glance. The relative positions of the side lay and gripper seldom receive the consideration they ought to have. The gripper and side lay should be exactly at right angles to each other, and any divergence whatever from this rule simply courts disaster. If they form an acute angle there is a danger of the sheet moving *forward* a little as the gripper closes. If, on the other hand, they are fixed at an obtuse angle, there is a proportionate risk of the sheet




FIG. 18.

falling back as the gripper closes. If any degree of uniformity could be guaranteed in these movements, then all would still be well, but unfortunately no such guarantee can be given, owing to a possible variation in the cutting of different batches of paper.

Another matter of a similar character and quite as important in its issues is more directly connected with the gripper.

The type of gripper shown in Fig. 18 is probably the best for general use. It enables the printer to use two or more pins upon which to rest his sheet, according to the particular requirements of his work. Two pins are usually

sufficient and answer best, for the following reasons. It is by no means unusual to find that the paper, trimmed though it may be, has slightly convex or concave edges, owing either to insufficient damping or an inaccurate setting of the knife in the guillotine cutting machine. This can, of course, be avoided, but the point at present under consideration is one of *possible* effects. This contingency and its effect are considerably exaggerated in Figs. 19A and 19B, but for purposes of illustration the suggestiveness of the two sketches is not at all too emphatic.

Start the machine with a light pressure, for once the stone is locked up a certain amount of danger will always exist if at any time it is necessary to reduce the pressure. The stone may still be held by the blocks, even after the bed of the machine has been lowered, only to come down with a snap when pressure is applied. Such a danger




FIG. 19.

might, of course, be averted by slackening the screws and blocks; but then the stone would almost certainly move out of position and the registration of the forme be altered.

Narrow slips of paper folded two or three times, and inserted between the block and the stone, will often check any tendency the latter may have to lift when the screws are tightened.

Of the many annoyances associated with the lithographic machine printer's work, *grit* is probably the most troublesome, inasmuch as its presence is almost imperceptible, while its effect is extensive and often disastrous. Its sharp grains become embedded in the inking-roller skins, and plough tiny

furrows across the printing forme, doing much damage before the printer realises the presence of any foreign matter on the




FIG. 20A.—Patent conical counter shafting.

inking-rollers. Prevention is a simple matter enough, but a cure is rarely, if ever, accomplished. Dust the rollers and examine them carefully before commencing operations, and in




FIG. 20B.—Patent conical counter shafting.

this way ensure perfect cleanliness. It may seem a trifle, but it is none the less an important one, and perhaps the

reader has already realised that "trifles make perfection, and perfection is no trifle."




FIG. 21.

In *making ready* on a lithographic printing machine, as in almost every phase of industrial life, method is the great secret of success. Method conquers the most stubborn diffi-

culties, and, though it is not at all times profoundly interesting in its application, yet it more than repays any monotony it may involve. In the matter of lithographic printing, at any rate, a few methods of an essentially simple character might be cultivated with advantage. This chapter is not intended as a complete record of such methods, but a number of items are discussed therein which, though simple, are intensely practical, and likely to suggest more to the reader than is found described in the text.

The question of speed may sometimes seriously handicap progress. It is a self-evident fact that the solid impression of a heavy poster cannot be made at the same speed as a light tint in chromo work. Speed cones are usually fixed to a counter-shaft to regulate the speed of the machine as required. Figs. 20A and 20B show an improved arrangement of this character, in which tapering drums A A are substituted for cones, the belt being moved and held in any position by the screw and forks B and C. D is the driving pulley which transmits the power to the machine.

Electricity as a motive power for printing machinery is quietly yet irresistibly winning its way into general favour, and for very cogent reasons. It is the most convenient form of motive power, and can be transmitted for long distances without any appreciable loss. It takes up little space, and almost entirely dispenses with belts and shafting. It is also essentially economical, because it can be applied to the smallest press just as easily as to a 60' by 40' poster machine (Fig. 21).

CHAPTER IX

LITHOGRAPHIC COLOUR PRINTING

A Commercial Value—Peculiar Features—Colour Sequence—Controlling Elements—A Question of Register—Suitable Paper.

As a commercial phase of lithographic printing, colour printing offers a vast and ever-widening field of usefulness. Nor is it altogether deficient in these artistic qualities which are pre-eminently suggestive, as well as attractive and artistic. Colour printing, in its application to lithography, is in many respects peculiar. It is not what might be described as a self-contained process; for its successful realisation depends as much upon the harmonious and skilful combination of colours in the design as upon the manipulation of the printing inks, the sequence of the colour formes, and their accurate fit or register during the actual printing. The most excellent printing would produce barely passable results unless the design was effectively arranged, and prepared with some consideration for the conditions under which it might be printed. Nor is it at all unlikely that a design, however smart and artistic it might appear in its original form, would be irretrievably spoiled by clumsy handling or careless printing. The subject for immediate consideration is the practical employment of printing inks for the reproduction of coloured designs, their qualities, peculiarities, and relative values, as well as the means employed to make them amenable to commercial conditions. An intelligent appreciation of these points will not only extend the possibilities of printing inks,

but will also enable the machineman to accentuate their attractive and suggestive power.

“Colour is to design what salt is to food,” and successful colour printing has been very aptly described as the adaptation of printing ink to the ever-varying character of work and conditions of employment. This very practical definition will form the keynote of a chapter which, by the very nature of things, must be to some extent authoritative and comprehensive. The colour sequence, *i.e.* the order in which the colours must be employed to secure the best and most economical results, is of primary importance in colour printing. On broad lines, the principle usually followed is one in which the opaque colours are printed first, and upon these all secondary effects are built up. This building up of colours plays also a most important part. Its relation to colour sequence is a necessary and influential one. For example, it might not be absolutely essential that even a yellow should be printed first, if it did not form the base for the building up of a green by the superposition of blues, of an orange effect in conjunction with red, or as a secondary flesh tone under the buff.

The difference between printing a blue over a red or *vice versa* is also very striking. One produces a purplish-black brown, and the other a rich chocolate-brown. Other complications of a similar character are common, but these will indicate with sufficient clearness the possible modifications of colour sequence.

Another feature upon which colour sequence in printing largely depends is the point at which the outline forme can be most effectively introduced. It is advisable to print the outline forme at as early a stage as possible for obvious reasons. Perfect registration is far from easy to secure. Red in the lips, blues in the eyes, and isolated touches of colour in various parts of the design must fit the browns, and

therefore fit each other, and yet they may have no direct relation to each other in the printing. A remedy has been already suggested, but once an outline forme is printed the cause of bad registration is to some extent removed, and a remedy quite unnecessary. When worked on reasonable lines it is frequently an advantage to make the outline one of the earlier printings, so that any harshness of contour, etc., may be toned down by the succeeding greys. It is often a matter of personal opinion, or perhaps of circumstance, which decides the final printings. The pink may be reserved to impart brilliancy and warmth to the prints, or it may be equally suitable to hold back a grey, and, by regulating its tone and strength, soften down any tendency to hardness, pick out the darker prints, and emphasise the shadows. Even these suggestions, although usually regarded as standard ideas, must be subjected to modifications under certain conditions.

Here is a practical instance. Unless paper is unusually well seasoned and of first-rate quality, the temperature of the workroom equable, and the printing machine in good order—a combination of excellences which is unfortunately rarely met with—the colour sequence must be of a fairly elastic nature. To print a gold first is quite usual, because the bronze powder will persistently adhere to any preceding printings. From that standpoint alone such a procedure would be eminently practical and convenient, but suppose for a moment that the gold must fit a later printing with absolute accuracy, *e.g.* an outline forme, or as forming the base for some ornamental scheme, then the difficulties which arise are somewhat trying, and for this reason. The paper being new, the most serious distortion of any kind is likely to occur during the first printings, and so long as yellows, fleshes, or other colours of a similar character are printed first, no serious difficulty is likely to arise; but with the gold printing it may be

altogether different. It is quite possible to make both yellow and flesh dry dead, *i.e.* without even sufficient tack to catch the almost impalpable bronze powder. At the same time, care must be exercised that the colouring matter is not left dry on the surface of the paper owing to its separation from the reducing medium. This plan has been adopted under actual commercial conditions and with conspicuous success, and it is therefore offered as a preventive measure which is free from many drawbacks which are the frequent accompaniment of novel ideas and operations. Here then is a simple practical summary of the idea. The yellow and flesh, or equivalent colours, are printed first, so that they will dry free from gloss or *tack*. The fit required between such colours and subsequent printings is generally a matter of minor importance, and at this stage distortion of the paper, whether it be by stretching or contracting, will not seriously depreciate the value of the print when completed. Register between the gold and an outline is frequently of an entirely different character, and in many cases the slightest variation will be readily discernible, and have a decidedly bad effect on the finished work. Apart from this, the questions which decide or control the colour sequence have been clearly indicated previously.

This matter may be one of convenience also, for unless otherwise predetermined it would be unwise and far from economical to print a blue before a yellow, or a black before a red, etc. The amount of cleaning up thereby involved would become a serious and distinctly disagreeable item, and purity of tone in the lighter colours would be conspicuous by its absence.

The matter of well seasoned printing paper has been already referred to. For effective colour printing the paper must also possess several other essential qualities. It should be firm in substance, sufficiently absorbent to carry the

successive layers of printing ink, as far as possible unstretchable, and should present a smooth surface though not a glazed one. The chalky, dull, enamelled papers offer many recognised features of value to the colour printer. They assist in the absorption of the ink as well as afford a suitable surface for their impression. Friction-glazed and other prepared papers are also excellent for colour printing by lithographic methods.



CHAPTER X

LITHOGRAPHIC COLOUR PRINTING—*continued*

Printing Inks—Varnish—Reducing Medium—Relative Values—Some useful Hints—Bronze Blue—Vermilion—Ink Mixing—Ceramic Transfers—Colour Transparencies.

FOR the successful manipulation of printing inks of any description it will be necessary to know something of their composition, or at any rate of such features as render them peculiarly suitable for printing purposes. From a printer's point of view the most important of these features is what may be described as the reducing medium, *i.e.* the medium which holds together the various colours so as to produce pigments of suitable working consistency. The most useful and the commonest form of reducing medium is a linseed oil product, known in its prepared state as a lithographic varnish, with a supplementary title indicating its specific character. Its value to the lithographic printer lies mainly in the fact that when it is fully matured it possesses a good full body along with fair drying properties and freedom from any excess of greasy matter. This varnish is used in three or four consistencies between which any degree of strength may be arranged by mixing. A brief outline of the manner in which they are prepared may still further emphasise their usefulness in lithographic printing.

Raw linseed oil is matured and oxidised until its consistency is considerably reduced. It is still further reduced by being boiled at a high temperature, and is known com-

mercially as "boiled linseed oil." As this boiling is continued the fumes which quickly rise can be ignited, and the liquid soon assumes a syrupy or stringy character, according to the length of time during which it is subjected to the action of fire. By extending or discontinuing the burning the varnish is produced in three grades—thin, medium, or strong.

Lithographic varnish is a good servant but a bad master, and it is a generally recognised fact that, beyond a certain point, lithographic varnishes as a reducing medium will depreciate the value of colour.

The chief requisite in colour printing is the production of a solid flat impression, and for this purpose almost all printing inks must be reduced to a suitable working consistency. To accomplish this, and at the same time retain the full colour strength of printing ink, a soft, free-working composition will be useful and desirable.

There are several commercial varieties of solid oil from which the excess of grease has been extracted. These form excellent reducing mediums. They break down the *tack* of stiff pigments and enable them to work freely during the printing operations. The drying of inks thus prepared is not seriously retarded; they *lift* readily and usually produce brilliant impressions. There is a reasonable and logical explanation of these peculiarities which is both interesting and suggestive. Whatever the character of a reducing medium may be, its effect on the strength of colour will of course be in proportion to the quantity used. In all probability 1 oz. of a solid oil composition, otherwise known as lithographic reducing medium, would soften down a quantity of printing ink for which at least three times its bulk of varnish would be required. Consequently, the depth of colour and covering power of an ink reduced with "litho medium" would be proportionately greater than that reduced

with varnish. Vaseline in some of its commercial forms is frequently used by American printers, and even in this country its use is being tardily, though none the less surely, recognised.

A few remarks anent the *intelligent* application of a softening medium may not be inopportune. Considerable care and judgment must always be exercised or there will be a loss of cohesion in the colour pigments which cannot fail to prove disastrous. The tendency of lithographic varnish is to bind the colour pigments together, and this should not be entirely counteracted by the addition of fatty compositions, lest the printing inks run "scummy" during printing operations, and in drying leave the colouring matter, from which they have been detached, on the surface of the paper in the form of a dry powder.

Such lack of cohesion may, however, be an inherent feature of the ink itself, and not be produced in the manner just indicated. Bronze blue affords a striking example of a printing ink of this character. It is, in fact, a "constitutional weakness" which cannot apparently be prevented, but which is fortunately not incurable. The addition of a little Canada balsam to bronze-blue ink will add considerably to its working qualities. The loose particles of the pigment appear to be held together without becoming harsh or stringy, as might easily happen if varnish of sufficient strength was added to produce the same effect.

Other colours, again, such as vermilion and yellow, owing to their weight and texture, will always require a fair percentage of varnish in their composition. At the same time, a little reducing medium might also prove beneficial. Referring once more to the fact that vermilion, as distinguished from its imitation, is unusually heavy, etc., it may be useful to know that for "blocking out" work it has no equal in all the range of printing inks. It possesses unrivalled opacity,

and as a "blocking-out" agent frequently plays an important part in colour printing.

Of the other printing inks, few possess characteristics of a sufficiently striking character to require special mention. Their working qualities present no exceptional difficulties, and their employment either under primary or secondary conditions is almost invariably determined either by the character of the work or some such conditions as have been already indicated.

When the strength of a colour is problematical, or its effect more or less a question of experiment, it is a safe plan to mix it a little lighter than will be required. For obvious reasons it is much easier to alter the line or tone of a light colour than that of a darker one.

The arrangements for extensive and economical ink mixing need not be of a very elaborate character. Standard colours might with advantage be mixed in large quantities and kept as stock shades. Fleshes, pink, blues, greys, etc., are all useful colours which are in constant use. A warm or cold tone could be imparted to a *stock* grey as required, and a similar method adopted with regard to the other colours. Other peculiar conditions could be met in a similar manner, and many economies thereby effected.

Although the foregoing remarks refer mainly to lithographic colour printing generally, they may with equal effect be applied to many of its more specific branches.

Colour printing for tin-plate decoration will be fully discussed in a subsequent chapter.

Transfer printing for ceramic decoration presents many features in common with transfer printing for metal decoration. Printing colour transparencies is a commercial phase of colour work which is productive of many curious and attractive effects. Unlike the ordinary colour prints, the transparency is intended for exhibition both by reflected and transmitted

light. The paper is of a thin, tough quality, and the first printing is usually a white of good covering power and exceptional opacity. It is not necessary to print a solid white groundwork for the coloured design. If an intense brilliant colour is required by transmitted light the omission of part of the white printing will add considerably to the effective character of the design. A brilliancy secured in such a manner may be still further intensified by printing the colour or colours in register *on both sides of the paper*. This can be easily accomplished by first allowing the cylinder covering to take an impression from the stone, and then, with the sheet laid in the gripper, make a second impression in the usual way immediately after.

The first print, which might be termed the transfer, will then be made in accurate register on the back of the sheet.

Semi-transparent, or even transparent, effects can be obtained with any of the colours by an omission of the white printing from the parts affected. Complete opacity may be secured by its introduction.

This print is afterwards rendered more or less transparent by coating it with a suitable varnish.

CHAPTER XI

SUBSTITUTES FOR LITHOGRAPHIC STONES

Metal Plates — Preparation — Manipulation — Descriptive Details —
Machine Printing—The Printing Bed—Rotary Printing Machine.

METAL plate, as a substitute for stone, is now such an important factor in lithography that the printer who wishes to consider himself thoroughly efficient must possess a fairly comprehensive and practical knowledge of its manipulation and possibilities.

The prejudice which has hitherto checked the progress of this branch of lithography was not altogether of an unreasonable character. The plates themselves were far from reliable, and the difficulties resulting therefrom were a fruitful source of trouble and expense.

Metal, as a printing surface, is even yet a comparatively new factor in lithography, and the majority of printers have been working with lithographic stones from their apprenticeship till the present time. It is not surprising, therefore, that in relation to the use of stones almost every possible contingency has been provided for, but with metal plates a little fresh knowledge must necessarily be acquired before the workman can claim the same familiarity of manipulation which he may feel towards the parent process. This is, in fact, the point upon which the whole question usually turns. Good work can be produced from zinc and aluminium plates,—of that there is not the slightest doubt,—and it is equally certain that the advantages offered by their use are of a sub-

stantially practical character. They can be handled with ease and with absolutely no fear of breaking. They are much less costly than stone, and require less storage room.

A grain of a finer and sharper texture can be imparted to metal than is the case with stone, and what is even of greater importance, the character of such a grain remains unaffected for a considerable time. Surface inequalities are rarely met with in metal printing surfaces, and consequently uniform pressure is to a certain extent guaranteed. In photo-lithography it is possible to make a print from a negative direct on to the plate (Chap. XVII. page 100). This ensures an original of exceptional clearness and strength, especially in half-tone subjects.

Although an ordinary zinc plate, which has been carefully polished to free it from every trace of grease, can be used for lithographic printing, the best results are obtained from plates which have been specially prepared. A slight de-polishing with pumice sand and a piece of felt may impart the requisite "tooth" to the face of the plate, or the following method may be adopted:—Clean the plate with pumice sand and felt, and immediately immerse it in a hot bath containing—

18 oz. Water.
¼ oz. Alum.
1 dram Nitric acid.

Keep this liquid in constant motion over the face of the plate until it assumes an even, silvery-grey appearance, and then wash it thoroughly with a plentiful supply of clean water. Dry at once, and quickly.

These plates can also be sand-grained by specially constructed machinery, or a variety of grains and stipple can be imparted to their surface by etching or sand blast.

A novel yet practical idea, which has met with considerable success, is to electrolytically prepare the surface of the plates. The value of this preparation has been amply demon-

strated by its extensive adoption and successful use. Another distinctly progressive feature is a deposit of alumina on the zinc, which for printing purposes gives it all the advantages of an aluminium plate.

Transfers can be made on metal plates in much the same manner as on lithographic stones. For press work




Plate-graining machine, showing oscillating motion.

mount the plate on a piece of cardboard its own size, then, having gummed a sheet of brown paper on the face of the litho-stone, place the mounted plate near the centre and fasten it with paste or gum. This will prevent it moving about, and also raise it sufficiently from the stone to enable the printer to use his damping-cloth and roller freely.

Before mounting, the back of the plate should be carefully dusted to free it from grit and dirt.

After the drawing or transfer has been made cover the surface of the plate with strong gum, and while this is still wet add to it a solution of bichromate of potash. Leave a slight film only of the gum bichromate, and then dry it quickly and thoroughly. Wash out the work with turpen-




Plate-graining machine, showing interior of trough.

tine, *not with water*. The gum, being insoluble in turpentine, remains unaffected.

Roll the plate up *solid* in black ink, sponge it over with water, damp it with a cloth, and then roll it up in the usual way. When the work becomes fully charged with ink, dust it over with a mixture of resin and French chalk, and etch it with the acid etching solution.

Every maker of zinc and aluminium plates supplies this special etching solution, prepared for a certain quality and character of metal. It is advisable, therefore, to use the preparation recommended, and thus avoid the many pitfalls which beset the path of the experimentalist.

“The plate is now well washed over with clean water, and *thinly* gummed up. When the gum is dry wash out the work on the top of the gum with dry flannel or felt till all the work is removed, sprinkle a few drops of water on the plate, and with a rubbing-up rag and a little ink and turps rub up the work till it is gently charged with ink, then roll up till work or transfer looks strong and sharp, when the plate is ready for printing.”

For etching and rolling up chalk drawings on grained plates: “Pour in a saucer some of the etching solution, and add about the same quantity of fresh, strong gum. This solution is evenly distributed all over the plate with a camel-hair brush, and left to dry. Then the etching is removed with water, and the plate very thinly gummed up and left to dry. Now the work is washed out with turps and a piece of dry, soft felt or flannel, *without water*, till all the work disappears, and the plate rolled up solid black. Then sponge over with water-sponge, damp over and roll up till work appears nice and sharp. Now dust over with resin and French chalk, and etch again with the etching solution, full strength. After the etching has dried remove the same with water, and gum up again.

“When drawings are to be washed out for proofing or printing, the plate should first be thinly gummed up. This gum layer is left *to dry thoroughly*, and is not removed when the work is washed out (without water) with turps and a dry piece of flannel or felt. Next wipe away all the black ink and turps, still using no water for this operation. Should any black work be left, use some more turps on

the *clean dry rag* till all the work has been removed, then sprinkle a few drops of water on the plate, and use a clean rag to remove the gum layer and loose black ink left on the plate, then damp over as usual and roll up.

“Plates treated in this way retain the grease contained in the drawing, and the work rolls up easier and quicker, and none of the finer work gets weakened or lost; also, the plate keeps cleaner and free from scum.

“When alterations are necessary the work should be rolled up with a strong black ink, and dusted over with French chalk (powdered talc). Remove the part which requires altering with a mixture of equal parts etching




FIG. 22.

solution and turpentine on a small piece of felt or flannel, and rinse well with water. Pour some special re-preparing solution in a saucer, and apply this solution with a camel-hair brush to the parts where the work has been removed; after the solution has remained for a few seconds rinse well with water. This operation is to be repeated several times till the surface looks clean, no work being visible; and after the plate is dried with clean white blotting paper it is ready to receive the additional work. When the alteration has been made, the rolling up should be done with the bichromate solution, as per general directions.

“Where the alterations involve additional work only without erasures roll up the design first with a good,




FIG. 23.

strong ink, and dust over with French chalk. The special re-preparing solution is used in the same manner as acetic or citric acid is employed on a litho-stone. For this purpose we recommend that the special solution should be diluted with an equal quantity of clean water, and the solution applied with a camel-hair brush. It should remain on for a few seconds, and then be quickly rinsed with clean water. This operation may with advantage be repeated two or three times for securing a clean surface for the additional work. When the plate has been thoroughly dried with clean blotting paper it is ready to receive the additional work. The rolling up should be done with the bichromate solution, as per general directions."

Machine printing from zinc or aluminium plates requires but a slight modification of well-known methods; and although it may in some respects present entirely new features, the making ready of work in which several printings are employed is simplified, and consequently much time is saved. In the ordinary type of litho-printing machine the printing bed (Fig. 22) is levelled in the machine for the first printing, and, if this is carefully arranged, no alteration will be required throughout the whole series; for, in changing from one colour to another, the printing plate can be slipped from the bed and another substituted in a very few minutes. The most scrupulous care should be exercised at all times to prevent dirt or grit of any kind insinuating itself between the surface of the printing bed and the back of the plate.

It is not in connection with the flat-bed printing machine, however, that the most decided progress is likely to be made in surface printing from metal plates. "The change which is already foreshadowed in the printing mechanism of to-day is shown by the growing demand for the rotary in place of the slow and tedious movements of the flat-bed press."

The mechanical principle of the rotary machine (Fig. 23) at once suggests an absolute precision of movement which it is scarcely possible to guarantee in the flat-bed press. There is no appreciable lift in the gearing of the cylinders when the impression is made, and practically no risk whatever of *slogger*, such as that described in Chap. VII. page 38. The uniform velocity of the cylinders, which is to a great extent




FIG. 24.

due to the points already indicated, considerably reduces friction, produces perfect registration, and enables the machine to be worked at a high rate of speed. The machine shown on page 63 presents many novel and essentially practical features. The side elevation (Fig. 24) gives a fairly accurate idea of its general mechanical principles.

CHAPTER XII

TIN-PLATE PRINTING

Its Evolution—Transfer and Direct Transfer Printing—The Coated Paper—Reversed Designs—Sequence of Printing—Printing Inks—Purity of Tone—Drying.

TIN-PLATE printing or decoration is probably the most remarkable development of modern lithography. From a most unpretentious and unpromising beginning its evolution has been an unbroken record of phenomenal progress. Owing to its intrinsic merits and peculiarly assertive character it has created an enormous demand for its own productions.

Difficulties innumerable were encountered and surmounted, whilst a whole host of trade prejudices had to be removed before anything approaching a commercial success could be claimed. The original idea was to transfer a printed design from a suitably prepared paper to the metal plates in much the same manner as the children of to-day use transfer prints for decorative and other purposes. Though this method is now to some extent superseded, it is by no means obsolete. It is extensively used for certain classes of work, and so long as the present type of direct tin-printing machine is used this transfer method of metal decoration will more or less be retained.

It is difficult, and in some cases impossible, to print unusually large or exceptionally thick metal plates by the direct process. Hence the value of Transfer Printing as a useful auxiliary process which can be resorted to without

the expense of special machinery. The ordinary lithographic paper-printing machine, without any modification whatever, will fulfil every requirement.

Almost any paper which has been coated with a starchy composition will be suitable for Transfer Printing. Though not absolutely essential, it is decidedly an advantage to use a paper which is somewhat porous, not too hard. A brief description of the principles involved will probably lead to a clearer understanding of the points already indicated.

The print is made on the starchy composition with which the paper is coated, and never actually penetrates to the paper itself. This composition, being readily soluble in water, can be transferred from its paper base to any other surface, and will carry with it any print or impression previously made thereupon. In theory, then, this process is exceedingly simple, nor is it likely to present any insuperable difficulties in practice.

One of the most important features of Transfer Printing, which affects not only the colour sequence but the draughtsmanship, is the inversion of the design when printed. To the printer who is accustomed to chromo work on paper, this matter will probably offer many awkward situations. The control over colour effects is somewhat restricted, and consequently not only care and skill, but a certain amount of special training and actual experience, will be necessary for the production of really successful work. In theory the outline forme should be printed first, but in practice it is frequently advantageous to introduce some of the transparent tints as first printings. In the first place, such prints rarely affect the design to any great extent as far as register or fit is concerned. Consequently, any distortion of the paper from atmospheric or other causes has no very serious consequences, and such distortion, *i.e.* expansion or contraction, would be most likely to occur during the initial

printings. There is yet another and equally important reason for this suggested modification of the colour sequence. The light, tacky tints considerably improve the printing surface offered by the mucilaginous coating of the paper, and the stronger inks can be printed on it with a full body of colour yet without any tendency to smash and smear. The lighter tints, then, are printed first, and these are followed by the opaque colours, reds and yellows being last. The peculiar feature of such an arrangement is that, after the first few printings, the design becomes partly obscured, and the relative value of different colours, together with the effect of their super-position, are frequently questions of skilful calculation rather than visual appreciation. Thus successful manipulation is therefore more or less the result of careful observation and wide experience. In certain classes of work it may, of course, be absolutely essential to ascertain the effects of colours as they are printed. This can be done by transferring a progressive print to a sheet of dull enamel surface paper, using gum water as a transferring medium. In all work where specific colour effects are required it will be advisable to make such test transfers again and again at different stages of the work.

Concerning the printing inks themselves but little need be said. They must be of good quality, varnishable, and of intense colouring power. Purity of tone is requisite, not only under ordinary circumstances, but under what may be regarded as exceptional conditions. The print, when subsequently transferred to the metal plate, will be placed in a stove having a temperature of 140° Fahr. Few colours remain quite unaffected by this stoving, but with carefully selected printing inks the effect is scarcely perceptible. It can, moreover, usually be anticipated, and to some extent minimised, either by judicious super-position or skilful preparation of the colours themselves before printing. The following

example will suggest a number of expedients for the preservation of tone of colour in tin-plate decoration.

Pale blues will frequently become of a decidedly greenish *hue* when varnished or stoved, and this may be modified by an exaggerated intensity of colour, even to hardness, when printing. At same time, it must be remembered that "blues" are seldom, if ever, affected in *tone*. Pinks of the lighter shades, on the other hand, may suffer both in *hue* and *tone*. "Reds" may be mixed with a more liberal amount of "lake" than they apparently need, and then backed up with solid masses of "yellow" and "flesh." These will restore the bright vermilion hue, and likewise give a greater amount of density or covering power to the colour. Black, in the same manner, may be intensified by an underlay of blue. As far as purity and density are concerned, the "white" printing is by far the most important. The primary function of this printing in tin-plate decoration is the formation of an opaque ground on the metal plate—equivalent to the white paper. Without it the colours of a design would lose their brilliancy and effect, for their purity and density would be affected by the lustrous sheen of the bright metal plate.

It is a printing, then, of some importance, and the most scrupulous care should be exercised during its manipulation. In consequence of the exceptional density required it is usual to repeat the "white" printing either two or three times. The first printing especially should be made with a smooth, well-mixed ink, which should be worked with the intention of securing a perfectly flat and solid impression rather than a heavy body of colour. The requisite amount of density can be obtained by the second or third impressions.

A slight tinge of "Oriental blue" given to the "white" will improve its appearance and counteract the discoloration produced by the varnishing and stoving.

Another point with which the average printer is not

familiar is the unusually rapid drying of each colour. The printing inks must dry on the surface, and not even in the slightest degree be allowed to permeate the paper. This is, in fact, the *cruz* of the whole matter; and, assuming that the coating of the paper is suitable and perfect, the drying cannot be otherwise than on the surface. Dryers, preferably liquid, must be mixed with the printing inks in liberal quantities. Here, again, experience alone can be relied upon for guidance. Printing inks have their peculiar characteristics, and atmospheric conditions are ever varying. It would therefore be unwise to indicate any hard-and-fast lines upon which to work. There is at least one danger accompanying the use of dryers in any form which must not be overlooked. Colours may dry too hard and present for the succeeding printings a surface similar to a varnished sheet, which will offer no *grip* to the printing ink, and upon which it will probably run, and, consequently, produce a defective impression. This is by no means an infrequent occurrence. Experience alone can prevent it, but the remedy is as simple as it is effective. Briskly rub each printed sheet with a pad of soft rag and a little magnesia or French chalk. Magnesia is best. It is an almost impalpable powder, and has no ill effect even upon the most delicate tints. This rubbing will produce a slightly matt surface on the hard glossy ink, and on this a good solid impression may be made without further trouble.

The printed sheets should be exposed to the air for a few hours to accelerate drying. This may be done in any convenient manner, either by laying them out in frames or hanging them up. A "set off" in Transfer Printing should be sedulously avoided; not that the soiling of the back of a sheet is of any moment, but because the matter set off on the back of one sheet must be pulled off the face of another, and that very often in liberal proportions.

CHAPTER XIII

TIN-PLATE PRINTING—*continued*

Direct Tin Printing — The Machine — Peculiarities of Impression — Cylinder Covering — Colour Sequence — Printing Inks — Drying Racks — Air Drying and Stoving.

“DIRECT tin printing” is not, as the term might suggest, a *direct* impression of the printing forme on the metal plate. It is in reality a transfer printing process in which the transferring medium is a cylinder with an elastic covering. This additional cylinder is one of the chief characteristics of a direct tin-printing machine, and, apart from a few accessory movements, it is in this respect alone that it differs from an ordinary lithographic printing machine. Fig. 25 gives a sufficiently clear idea of this distinguishing feature. A detailed description of its mechanical principles is unnecessary, but the following points will prove helpful.

The impression is made from the printing forme upon the lower cylinder during the first half of its revolution, and transferred to the metal plate, which is carried by the upper cylinder as the revolution is completed. The reciprocal movement of these two cylinders is therefore a matter which demands the keenest possible attention. Their pitch must be absolutely accurate, the pressure of one against the other nicely adjusted, and the brake arrangement on both such as to ensure a perfectly steady revolution.

The lower cylinder is covered with a three-ply rubber blanket, which provides a sufficiently elastic impression surface.




FIG. 25.—Rapid tin-plate printing press.



This rubber covering is a most important feature, and requires both careful adjustment and intelligent use. Careful adjustment is requisite to ensure the tension being perfectly uniform over the whole surface, when the material is drawn taut by means of a tooth-and-ratchet arrangement. Were it not so, the printing surface presented would naturally vary in thickness and resilience, in consequence of which the pressure would be variable and the impression distorted.

A most remarkable peculiarity of this rubber covering is that it has a very decided influence upon the size of the impression. If, for example, its pressure upon the printing forme is increased, the impression will be slightly less than the work on the stone, whilst a lighter pressure will of course produce the opposite effect. It is advisable, therefore, when making a first impression, to measure it from back to front and compare it with the printing forme. This method will ensure a print of the exact size, and avoid any risk of complications in the subsequent printings. Such distortion—for a distortion it really is—may frequently be turned to good account, and under certain conditions it may prove to be a help rather than a hindrance. Some slight inaccuracy in the fitting of any part of the design may occasionally be corrected by inserting patches of thin paper under the cylinder covering, so as to almost imperceptibly increase the pressure over the required area. This idea in its application to “making ready” at a tin-printing machine will suggest many possibilities to the resourceful printer, and if intelligently treated will rarely prove troublesome. In a lesser degree the same system of packing may be applied to the upper cylinder, and the size of the impression to some extent controlled during its transference to the metal plate. The speed of the machine also affects the impression, and in a somewhat peculiar manner. Several theories have been set forth to prove why an increase in speed should produce a slight

enlargement of the impression, and *vice versa*; but it is doubtful if any of them are altogether satisfactory. Most probably it is due to a momentary change in the resilience of the rubber. The character of the pressure, which is certainly influenced by increasing or diminishing the speed, would of course effect such a change. The effect, as just indicated, is, however, only perceptible when a very pronounced variation in the speed takes place. A rubber blanket is also affected in a somewhat similar manner by atmospheric changes, though not appreciably by moisture.

One other point in connection with the cylinder covering is worth noting. Whenever it is necessary to remove the impression from the blanket,—and the necessity may arise many times during the course of a day's run,—let it be done with turpentine or benzole, and as rapidly as possible. After the superfluous turpentine or other cleanser has been wiped off, dust over the blanket with French chalk. This will completely absorb any of the cleanser which may have permeated the rubber, and thus minimise any injurious effect.

Unlike the Transfer Process in Direct Printing, the colour sequence is practically the same as for paper printing. There are, of course, essential points of difference, and these may fitly mark the next stage of progress in the discussion of this subject. In the first place, a bright metal plate does not present an altogether suitable printing surface, and for several reasons. The sheen of such a plate will show through many of the printed colours with a dull metallic lustre. The surface, again, is hard and excessively smooth, or, as it is sometimes expressively described, without *tooth*. As can easily be seen, this is far from an ideal printing surface.

White also plays a prominent and effective part in many designs, and is frequently indispensable. Its presence, when necessary in Direct Tin Printing, must therefore be arranged for in some form or other. One white printing is

seldom sufficient to produce a perfectly clean and solid ground. Two printings, or even three, may be necessary. Purity of tone is a most important point, and therefore a pigment should be chosen which will, not only remain unchanged by its contact with the metal, but which will be unaffected by the heat applied during stoving. The appearance of this white may be improved by the addition of blue, as in Transfer Printing (p. 70), and here also the smallest possible quantity will be sufficient.

Gold Lacquer Printing is peculiar to Tin-plate Decoration, and its advent indicated a vast progress in artistic display and effect.

Printing lacquer is a transparent pigment of about the same consistency and character as printing ink. It is usually prepared in three shades of colour—red, citron or orange, and pale gold. A combination of these in suitable proportions will produce almost any strength or shade of gold which may be required. Except as regards their unusually brilliant transparency, these lacquers much resemble yellow lakes, and in paper printing might even be used as economical substitutes for the more expensive pigments. This, however, is only a suggestion, and has little if any practical bearing upon their application to Tin-plate Printing, where they completely transform the bright sheen of the highly polished metal plate into a brilliant and most effective gold. Gold lacquer is an exceptional pigment in many respects. It works exceedingly well, and gives a sharp, flat impression where most other pigments would fail. It also has the power of conveying many of its own good qualities to any printing ink with which it may be incorporated.

In Transfer Printing the question of rapid drying is very important, and in Direct Tin Printing it is even more so. Arrangements of a somewhat extensive character must be made for the reception of metal plates immediately after

printing, so that the air may freely circulate about them, and thus assist in the drying. The room in which the printing




FIG. 26.

sheaves A A are adjustable so as to carry plates of different sizes. The printed sheets are set up on end in the grooves B B, and by arranging them back to back in pairs a large number can be accommodated without hindering the drying. Other types of drying racks are shown in the sectional drawings (Figs. 27A and 27B).

The question of air-drying *versus* stoving has ever been a contentious one, and admits of considerable diversity of opinion. Air-drying is preferable where convenient. It is

much more economical than stoving, of course; but, on the

sheets are thus stored must be free from dust, for it will readily adhere to the tacky printing ink, and afterwards prove a source of endless trouble.

Drying racks of various descriptions are used for the storage of printed metal plates. One of the best is constructed on the lines shown in Fig. 26. The




FIG. 27A.

other hand, it might be a better plan to stove a printing than to wait, perhaps for some hours, until it dried naturally. With some printing inks and under certain climatic conditions both may be necessary, so it is almost impossible to lay down any hard-and-fast rules as to the adoption of either plan.

Some knowledge of their respective disadvantages should be acquired, however, in order to avoid, or at least minimise, them.

Take, for instance, a course of eight printings, each one absolutely necessary to the design, and each one to be dried by stoving. It is only reasonable to suppose that the first and second printings

will be seriously affected by the subsequent stovings. They will undoubtedly harden to such an extent as to render the super-position of other colours a difficult matter, and their purity of tone will most probably be affected. According to the same line of reasoning, some sheets would be more affected by the heat than others, owing to their position in the racks, the heat of stoves being greatest near the top.




FIG. 28.—Convenient method of stacking decorated metal plates to distribute their weights and prevent injury.

Naturally, it requires a much longer time, but it is equally effective, much less troublesome, and generally more satisfactory.




FIG. 27B.

Air-drying can only be accomplished by adding to the printing ink a proportion of some suitable drier. (See Transfer Printing, p. 71.)

CHAPTER XIV

TIN-PLATE DECORATION

Suitable Designs — A Variety of Effects — Gold Lacquer — Superposition of Colours — Embossed Effects — Embossing Plates — Lacquers.

It is usually and rightly supposed that the most effective results in Tin-plate Decoration are produced from designs which are lithographed for that specific purpose.

Designs which are specially arranged for Paper Printing can be used so long as the effect produced by the transposition from right to left does not affect its application, or render the same impossible. This, of course, applies more particularly to designs in which lettering appears, but at the same time it may affect designs of an essentially pictorial character in an equally important manner; for it must be remembered that a drawing for Tin-plate Printing must appear on the lithographic stone exactly as it is impressed on the metal, and not, as in Paper Printing, reversed from right to left. This naturally simplifies the drawing on stone, and to some extent enables the draughtsman to dispense with the reversing mirror when copying.

The primary object of this short chapter will be to point out some of the characteristic features of Tin-plate Decoration, so that such methods as are usually adopted by the artist and the printer may be modified or amplified to meet any peculiar requirements of work in hand.

A greater variety of effects can be attained on the

polished metal plate than it is at all possible to produce on paper.

A gold effect, the result of lacquer printing, is especially striking. In a similar manner an excellent translucent lustre can be imparted to almost any colour by taking away the white opaque ground, and thereby producing a peculiar semi-transparency which is both pleasing and effective. Lacquer printed over *white* produces a *buff* colour, which can be used as a second yellow or to form the base of a flesh. The colour of the lacquer is softer and less obtrusive when printed under instead of above the white. The super-position of colour generally, as described in Chap. XII. page 70, is peculiar to tin-plate printing, and suggests the advisability, if not the necessity, of a special design. The advantages of such super-position are obvious and substantial. Under ordinary commercial conditions it is almost impossible in tin printing to obtain the same intensity of tones in the printed colours as in paper printing. Some such strengthener as the super-position of suitable colours is therefore necessary. The work of the lithographic draughtsman is in this respect of a somewhat unusual character; but a little intelligent consideration will render its execution on these lines comparatively easy and satisfactory.

As already stated, yellows can be accentuated by a super-position of lacquer, and in the same manner blues and greys add intensity to black. Red can be strengthened by a foundation of lacquer, also flesh and yellow, either singly or in combination. The drawing of lacquer and white formes should receive the most careful attention. They should fit each other accurately, even to the most minute details; for the slightest overlapping will be revealed by the presence of a very assertive buff colour, while any deficiency in combination will leave a not less striking margin of bright tin exposed.

In some instances it might be an advantage to transfer one forme from *black* to *white* to produce the opposite colour, and thus ensure perfect register.

In decorative designs particularly, tin-plate printing suggests almost unlimited possibilities for brilliant effects, and in this respect it offers fair latitude for individual originality and manipulative skill. In the production of show tablets especially, considerable attention has been given to embossing, in order to suggest and represent relief. Though not actually produced by the artist, this is in effect part of the scheme or plan of his design, and will consequently influence his work to some extent. For simple ornamentation only, metal embossing presents little that is new or novel; but for the production of relief effects in the pictorial elements of a design its application becomes a more important and influential matter. By its aid a flat and otherwise uninteresting subject can be made attractive and vigorous, and for general purposes of effective display its value will be considerably enhanced and its assertive character emphasised.

Without entering too minutely into matters which affect the lithographic printer in an indirect fashion only, it will yet be useful to him to know how an embossing die is produced which registers accurately with the design to be operated on. A black impression of the outline forme of the design is made on transfer paper similar to that described in Chap. XII. page 68, and re-transferred, by pressure only, to another sheet of the same paper. The re-transfer is to be the impression required, and this in its turn is re-transferred again to a prepared brass plate. The only preparation necessary is the levelling and planing of the plate, and, if desired, it can be coated with a thin layer of white paint or enamel. This white ground makes the work easier, by rendering the impression more distinct. With such a guide as this the cutting or engraving is a comparatively simple matter.

The engraved plate is placed in a casting box, and a stereo-metal casting is made from it. A little trimming may be necessary for the completion of these two tools, and they will require to be suitably mounted, so that they may be accurately adjusted in the embossing press.

Metal embossing has certain limitations which must be recognised as an essential condition of its effective application.

The plates vary considerably in texture and temper, and the depth and character of relief will, to some extent at least, be controlled by the quality of the metal. Sharp lines and abrupt terminations impose a strain under which many plates split, therefore such features ought to be avoided. Easy, rounded lines, rather than those of the straight furrow description, produce the best results and give least trouble during operations. Where abrupt terminations are quite unavoidable the design should, if possible, be so arranged as to evade the super-position of colour over these parts.

Lacquer, if properly mixed and applied, is probably the toughest pigment used by the tin printer, and is generally suitable for embossed work. It prints an exceedingly thin layer or film on the face of the metal, which under average conditions rarely interferes with the working of the embossing tool.

CHAPTER XV

PHOTO-LITHOGRAPHY

Early Experiments—An Analysis—The Direct Process—Transfer Process—Line and Half-tone—Some Difficulties—A Natural Grain—Ink Photo-screen Effects—Essential Features.

ONE of the most promising features of lithography is its co-partnership with photography as a rapid and accurate method of reproduction. The resources offered by this combination are very extensive. For facsimile copying and proportionate enlargement or reduction photography stands unrivalled, and, although in certain phases it may be somewhat mechanical in its effects, its relation to lithography as a reproductive art is nevertheless of an intensely practical nature, and far from inartistic in character.

The first idea of inking up a photographic print so that it might be transferred to the lithographic stone was suggested in the simplest possible manner. A brief account of its inception will be instructive as well as interesting, inasmuch as it will lead to a clearer conception of the elementary principles involved.

During the early experiments in carbon printing it was discovered that a gelatinous film sensitised with certain bichromates could be charged with a coloured pigment, and a picture developed thereon. At first it was not realised that images produced by the action of the light on such a surface could be inked up with a greasy composition and afterwards transferred to the lithographic stone, but it was not long

before this important point became apparent. It was found that after exposure under the negative the transfer ink would only adhere to such portions of the gelatinous surface as had been acted upon by the light.

Photo-lithography will best be considered under two sections, namely—

1. The *direct* process, in which the actual printing surface is prepared and exposed under the negative.

2. The *transfer* process, in which a gelatine-coated paper is sensitised in a solution of bichromate of potassium and the photographic print made upon it.

The *direct* process in its application to the lithographic stone is uncertain in its results. It is impossible to secure sufficiently close contact between the negative and the stone, particularly when large surfaces are under operation, and consequently the print is rarely if ever an unqualified success. The erasure of defective work is also a serious matter, and can only be effected by polishing and preparing the stone again.

In the *transfer* process absolutely close contact can be assured by the use of the transfer paper; and should the print from any cause whatever prove defective, another can be made immediately without any serious loss of time or material.

The successful application of the *direct* process to zinc and aluminium plates is, however, an accomplished fact. The metal plate is sufficiently elastic to adapt itself to any inequalities on the surface of the negative. Under such conditions as these this process offers at least one very important advantage. There is not the slightest possibility of distortion such as might occur in the development of a transfer. The metal plate also lends itself to easy manipulation.

Photo-lithography in line is simply the reproduction of line drawings or prints in which the design is represented in black and white with only such gradations as may be suggested by lines or dots.

Half-tone photo-lithography is the reproduction of a design or copy which has in its composition gradations of tone in the form of flat tints.

It is sometimes described as the translation of the graduated light and shade of the original copy into a surface which can be printed from by mechanical means, for which purpose the ink-bearing surface is broken up into the most minute sections, and thus forming an almost imperceptible grain. The first attempts to reproduce the half-tones of a copy, in the form of a grain consisting of minute dots of varying size and contiguity according to the gradation of tone required, were made with a screen of open textile fabric. This screen was placed between the lens and the sensitive plate, but the results were crude and unsatisfactory.

The invention of cross-lined screens, in which the lines were cut on glass and filled with black or other suitable colouring matter, was a decided advancement in the half-tone photo processes.

The "screeny" effect produced by the "unvarying uniformity of grain" in half-tone work is undoubtedly the chief drawback to its more extensive adoption for photo-lithography. Fine etching cannot be resorted to as in photo-engraving, neither is it possible to emphasise effects by skilful overlay and underlay; consequently half-tone impressions from a lithographic stone are frequently disappointing. There are no insurmountable obstacles to hinder the production of excellent transfers, nor is it a difficult matter to transfer them to stone. The trouble is, as already pointed out, the unvarying uniformity of the grain.

This effect, or rather this lack of effect, has been to some extent overcome by the use of a "four-line" screen in lieu of the usual "crossed" screen, but even this is merely a *remedy* and not a *cure*.

It has been confidently asserted that the highest degree

of excellence in photo-process work will be attained by the adoption of what may be termed a natural grain. Several processes have been introduced which are undoubtedly based upon collotype methods in which a reticulated grain is produced more or less suitable for lithographic printing. Unlike the mechanical screen grain the texture of these processes reproduces the original copy with but little, if any, loss of expressive power. This is indeed a feature of considerable importance, and suggests many possibilities in the way of artistic reproduction.

To reproduce an old chalk drawing so that it might be successfully transferred to stone and printed in the usual way, would be practically impossible by any other process. In copying through a ruled screen many of the delicate contrasts of light and shade would be so reduced as to become almost valueless, consequently the print loses both in artistic and expressive power. In contradistinction to this a natural grain exhibits no harshness or indistinctness in the gradations of tone, and retains its clearness and sharpness throughout the printing operation.

Reverting again to the half-tone ruled screens, it may be well to state that small prints, being usually subjected to a closer inspection than large ones, must be reproduced with great attention to the finer details to ensure a certain amount of fidelity, and for this reason a screen with fine rulings must be employed. Naturally, stronger and more vigorous reproduction can be secured with the coarser rulings, but the *screen* effect will be too pronounced for close scrutiny.

There is still much to achieve in photo-lithography, and it is probably owing to a full recognition of this fact that the progressive character of the process is maintained. Its commercial value is undoubted, and its successful application is chiefly a question of *how* and *where* it can be most effectively introduced.

The essential features of photo-lithography are :—

1. A copy or original in which the modelling is well defined, and the light and shade well emphasised, even to a point of slight exaggeration.

2. A *negative* in which the whites of the original appear opaque, with clear glass to represent the lines and solids.

3. A *print* which can be developed or inked up with a pigment sufficiently greasy in nature to transfer to the lithographic stone.

CHAPTER XVI

PHOTO-LITHOGRAPHY—*continued*

The Copy—Gradations of Tone—Scraper Boards—Description and Effect—Shading Mediums—Crayon Drawings—Half-tone Copy.

It has already been pointed out that well-defined modelling is most desirable in the original copy. To secure this a considerable degree of artistic perception and discretion, as well as manipulative skill, is requisite. In photo-process work it is almost impossible to produce artistic effects from an indifferent or unsuitable copy.

Pen-and-ink sketches and wash drawings are entirely under the control of the artist, and characteristic effects are chiefly due to bold and vigorous conception and skilful drawing. Few photographs are suitable for photo-mechanical reproduction without some previous preparation. Accentuation or modulation of the high lights and shadows will in all probability be necessary to secure a sufficient contrast of light and shade. The middle tints may require but little attention, unless it be to work down any tendency to abruptness in the gradations of tone. A bold and well-defined silver print usually copies well when clamped between two pieces of glass to take out the grain, and photographed by artificial light.

Scraper boards offer most remarkable possibilities for black and white and half-tone sketches. A careful examination of Fig. 29 will serve to demonstrate their peculiar fitness for process drawing. A light wood pulp board forms a con-

venient base upon which a thick coating of white composition is laid. Black ruled lines are printed on this surface, and lines of a similar texture are embossed at right angles to them. Some of the characteristic effects which can be produced on this board by the use of the crayon and scraper are suggested by Nos. 6 and 7, Fig. 30. No. 8 gives a stipple which is both printed and embossed. No. 9 is a plain board upon which pen-and-scraper effects alone are produced. Drawings in pen and ink, on Nos. 10 and 11 patterns, may be effectively handled by a free and skilful use of the scraper. Embossed lines only are the peculiar features of these boards, but variety of texture can be obtained by scraping these lines into dots.

Scraper board sketches almost invariably represent a maximum of effect with a minimum of work, and for this reason alone such an adaptable and simple medium should soon win its way into general favour.

Their merit, however, is not confined to this one point. They provide almost unrivalled copy for photo reproduction, and can therefore be applied to a variety of purposes. Even a cursory glance at the scraper board sketch on page 91 will reveal many points of interest and value which a more careful scrutiny can scarcely fail to emphasise.

Small patches of scraper boards can be introduced into process drawings of any description, and brilliant results be secured thereby. In such a manner clouds, waves, foliage, and a variety of other effects can be introduced.

Shading mediums are already well known to lithographers, yet it is doubtful if their usefulness for the amplification of sketches or process drawings is fully appreciated. They offer almost endless combinations of texture and tint, and are therefore most useful and valuable accessories in the hands of a resourceful artist.

Many artists favour crayon work on a grained paper, adopt-




FIG. 29.—Reproduction of a drawing made on Gilby & Hermann's scraper boards.











FIG. 30.—Some scraper board textures.



ing a broad sketchy treatment in liberal proportions, so that in the subsequent reduction the freedom of the original will be toned down just sufficiently to enhance the picturesque and artistic value. Drawings made on scraper boards, grained papers, or by the aid of shading mediums, are photographed and reproduced by the ordinary line method. In making sketches for "half-tone" photo-mechanical reproduction it must be remembered that, as far as photo-lithography is concerned, it is impossible to accentuate effects by what is known as "fine etching" when applied to photo-engraving. A negative for photo-process work of any description should be absolutely perfect in every respect. The whites of the copy in the negative should be of an absolutely opaque black, showing clean, sharp edges, with clear glass representing the lines, dots, etc. These are all-important factors, and their influence upon the reproduction of the original can scarcely be over-estimated.

CHAPTER XVII

PHOTO-LITHOGRAPHY—*continued*

A Copying Table—Exposure—Illumination—Photo-litho Transfers—
The Paper—Printing—Developing—A Direct Process.

To discuss the respective merits of the “wet” collodion, collodion emulsion, and dry-plate processes lies beyond the province of this work, as does also a detailed description of the operations involved.

The processes are purely photographic, and have already been presented to the craft in various forms. It is, moreover, almost impossible to bring within the limits of a single chapter anything approaching to a comprehensive record of the multitudinous details upon which process photography is based. All that can be attempted is to take one or two outstanding features which suggest a few useful hints.

The original or copy for reproduction must be on the same optical plane as the sensitive plate in the camera, *i.e.* they must be absolutely parallel with each other. There are several ways of ensuring this. The most convenient method is to use a copying table and board similar to Fig. 31. With such an arrangement as this direct copying can be attained through the lens, or the camera can be turned half-way round, and the image reversed by means of a mirror or prism attachment. The chief advantage of such an arrangement is, that the position of the camera can be altered at will without affecting the relative positions of the plate and copy.




FIG. 31.

REESE LIBRARY
OF THE
UNIVERSITY

Correct exposure and sufficient illumination of the copy are important factors in photographic reproductions of any kind, but they are of infinitely greater importance when applied to photo-process reproduction. One is, to a certain extent, dependent upon the other. The former must of necessity be controlled by the latter; yet no amount of exposure will compensate for defective illumination. Where artificial light is employed the advantage of using two lights is obviously great. Apart from the greater brilliancy and intensity of the light, the illumination of the copy is more evenly distributed. In scraper-board copies no shadows are thrown from the embossed dots or lines, and the granular texture of grained papers is almost entirely eliminated.

A bichromated, gelatine paper can be obtained by coating a hard writing paper of medium thickness with a gelatinous solution consisting of 1 oz. of gelatine and 1 oz. of water, and afterwards sensitising it with bichromate of potassium. It is advisable, however, to use the commercial varieties of coated paper, and to sensitise it as it is required.

The sensitising solution can be prepared by dissolving 1 oz. of bichromate of potassium in 20 fluid oz. of water. Add to this sufficient ammonia to give it a bright orange tinge. Keep this solution at a temperature of 60° Fahr., and float the paper on it for about one minute. Pin or clip the paper to a board or squeeze it to glass, and dry in a dark room.

Print this paper under the negative in a diffused light until the design appears in a rich golden-brown colour, when the exposure may be regarded as sufficient. The time allowed for such an exposure will, of course, vary according to the quality of the negative and the intensity of the light.

A development of the print may now be proceeded with in the following manner.

Thin down a little transfer ink with turpentine and

distribute it evenly on a composition roller. Roll up the print until it is completely covered with an exceedingly fine film of ink, after which allow the turpentine to evaporate. Immerse the transfer in tepid water for about 10 minutes, and then rub it gently with a piece of cotton lint previously soaked in water, until the superfluous ink is removed and the design stands out clean and sharp.

The transference of the print to stone can be accomplished in the usual lithographic manner. The chief points to be observed are, to allow sufficient time for printing, and to ink up the transfer with the thinnest possible film of ink.

A photo print can be made direct on the zinc or aluminium plate, and by a slight modification of the photo-engraving process it can be developed according to lithographic methods.

It is impossible to introduce an intermediate process without, in some manner at least, depreciating the quality of the work. In a direct photo print on zinc, or, in fact, on any suitable printing surface, the finer qualities of the work are much more likely to be retained than when a transfer print is made under the negative and afterwards transferred in the usual manner.

Coat a finely grained zinc plate with sensitised asphalt solution and expose it under a negative for about $4\frac{1}{2}$ minutes in direct sunlight, and from 12 to 15 minutes in a diffused light. The action of light on the asphalt solution is to render it insoluble in turpentine, so that if a sufficiently exposed plate is immersed in pure turpentine the lines, etc., of the design, being of course represented by clear lines in the negative, will remain intact, while the surrounding portions will be dissolved and washed away. After development wash the plate freely in water, and dry it by fanning or with a pair of bellows. Let it stand for about 10 minutes and then slightly etch it with a very weak solution of nitric

acid. Cover the work with strong, fresh gum, and dry it thoroughly and quickly. Remove the gum and "rub up" the design with black ink in the usual way. Wash, dry, and dust over with French chalk. The plate can then be prepared in the manner described in Chap. XI. page 61.



THE END

INDEX

	PAGE		PAGE
ADJUSTING pressure in machine	38	Colours, standard	55
Adjusting stones in machine	37	Copperplate press	17
Air drying—tin printing	78, 79	Printing	17-19
Alum	27	Stove	18
Aluminium plates	57	Copy, photo-litho	87
Aluminium plates—		Copying table	96
Alterations	62	Crayon or chalk drawing	8
Direct photo	58, 85, 99	Crayon work	88, 90
Etching	61	Cylinder press	21
Machining	65		
Printing bed	65	Damping rollers	40
Rolling up	60	Design	24
Sensitising	97	Design, inverted	68
Transferring	59	Design, suitable	80
Aluminium rotary machine	65, 66	Development, photo print	99
American printers	53	Direct impression, A	72
Asphalt solution	99	Discoloration	70
		Distortion	49, 68, 75
Bavarian limestone	12	Dryers	71
Blocking out	54, 55	Drying colours	50, 71
Blue tinge	70, 77	Drying metal plates	77, 78
Boxwood scraper	20	Drying racks	78, 79
Brake cylinder	38	Duplication of design	30, 31
Bronze printing	49		
		Effect of pinks and greys	49
Cam motion	21	Effects in tin-plate printing	81
Canada balsam	54	Elastic bedding	22, 23
Castor oil	28	Electricity	46
Cause and effect	2	Elements of lithography	2
Ceramic decoration	55	Embossed lines	88
Chalk drawings	25, 26	Plates	82
Chemical affinity	2	Embossing discs	82, 83
Clean stones	3	Enamelled paper	51
Cohesion in printing ink	54	Etching	25, 26
Colour and design	48	Evolution of tin-plate printing	67
Changes	70	Exposure	98
Mixing	31		
Printing	47	Fine etching	95
Registration	48	French chalk	71, 76
Sequence	48, 50, 76	Skins	28
Super-position	48, 81	Friction glazed paper	51
Transparencies	55		

	PAGE		PAGE
Glass muller	6	Original stones	30
Gold lacquer	77, 82, 83	Outline forme	48
Gold printing	49	Packing cylinder	22
Grain, natural	87	Paper, enamelled	61
Graining stones	5, 6	Well seasoned	49-51
Grinding stones	4-6	Pen and ink sketches	89
Gripper	42	Pen and scraper effects	90
Gripper margins	31	Photo litho—	
Grit	43	Copy	89
Half-tone, photo-litho	84	Development	98, 100
Halligan machine	34-36	Direct	85
Hand labour and machine	3	Half-tone	86
Lever	21	Inception of	84
Roller	28	Line	85
High lights	89	Printing	99
Homogeneity of stones	2	Transfer	85
Transfer paper		Transfer paper	98
Illumination of copy	98	Plumbago	22
Impression	27	Porosity of stones	2
Impression, size of	75	Preparation of stones	2-7
Impression, solid	46	Preparing designs	24, 25
Inking rollers	39	Pressure alterations	43
Inks, printing	52-56	Excessive	37
Tin-plate printing	69-71	Litho press	20
Transfer	8-11	Peculiarities	75, 76
Inverted design	68	Printing inks	52
Key formes	27, 41	Cohesion of	53
Lacquer, peculiar feature of	83	Printing medium	1
Lacquer, tin-plate	77	Proving	29, 30
Lamp-black	28	Recipes, transfer inks	9-11
Leather dressing	22	Transfer papers	13-15
Level surfaces	3	Reciprocal movement	72
Levelling stones	37	Reducing medium	53, 54
Line, photo-litho	85	Register lines	29, 30
Linoleum	23	Registration	29, 41
Linseed oil	52, 53	Registration of colour	48
Litho press for copperplate	19	Remedy, A	71
Litho press, mechanical principles	20, 21	Re-transferring	31
Litho press, pressure	20	Rotary machine, printing	65, 66
Litho varnish	52, 53	Rubber blanket	72-75
Magnesia	71	Resilience of	76
Mechanical affinity	2	Scraper	20-22
Metal plates	57	Scraper boards	89, 90
Method	45	Scratches	3
Modification of colour sequence	48	Screen effect	86
Motor driving	46	Screen photo	86
Nap roller	28	Senefelder	2
Natural grain	87	Sensitising solution	99
Negative	88	Sequence of colour	48
Offsets	27, 28	Set off	71
Oriental blue tinge	70, 77	Shading mediums	90
		Shadow	89
		Sheen of metal plate	70
		Side lay	42
		Silver print	89

	PAGE		PAGE
Slogger	38	Transfer paper (<i>contd.</i>)--	
Sludge	5	Stone to stone	13
Solid oil	53	Transparent	13, 14
Speed	36, 37, 46	Varnished	13
Speed cones	46	Transfer printing	55
Standard colours	55	Transferring	32, 33, 99
Stone-planing machine	3, 4	Transparencies	55
Stone-polishing machine	4, 5	Trimming paper	43
Stoving tin-plates	78	Tympan	21, 22
Transferred prints	69		
Substitutes for stone	57	V-shaped edge	22
Suggestion, A	49	Varnish, litho	52, 53
Super-position of colours	48	Vaseline	54
		Venetian red	28
Tooth of grained stones	7		
Of metal plates	58	Water of Ayr stone	25
Transfer inks—		White printing	70, 76, 77
Active principle of	8, 9		
Copperplate	10, 11	Zinc plates	57
Extra powerful	4	Zinc plates—	
Plate	9	Alterations	62
Stone to stone	10	Depolishing	58
Writing	9, 10	Etching	61
Transfer paper—		Graining	58
Autographic	14	Machining	65
Copperplate	14, 15	Photo, direct	58, 83, 97
Diaphanic	16	Printing bed	65
Grained	15, 16	Rolling up	60
Photo-litho	16, 99	Sensitising	99
Specific value of	12	Transferring to	59

JANUARY, 1905.

Catalogue

OF

Special Technical Works

FOR

MANUFACTURERS, STUDENTS, AND TECHNICAL SCHOOLS

BY EXPERT WRITERS

INDEX TO SUBJECTS.

	PAGE		PAGE
Agricultural Chemistry ...	10	Dyers' Materials ...	21
Air, Industrial Use of ...	11	Dye-stuffs ...	22
Alum and its Sulphates ...	9	Enamelling Metal ...	18
Ammonia ...	9	Enamels ...	18
Aniline Colours ...	3	Engraving ...	31
Animal Fats ...	6	Essential Oils ...	7
Anti-corrosive Paints ...	4	Evaporating Apparatus ...	26
Architecture, Terms in ...	30	External Plumbing... ..	27
Architectural Pottery ...	16	Fats ...	5, 6
Artificial Perfumes... ..	7	Faults in Woollen Goods... ..	20
Balsams ...	10	Gas Firing ...	26
Bibliography ...	32	Glass-making Recipes ...	17
Bleaching ...	23	Glass Painting ...	17
Bone Products ...	8	Glue Making and Testing... ..	8
Bookbinding ...	31	Greases ...	5
Brick-making ...	15, 16	History of Staffs Potteries	16
Burnishing Brass ...	28	Hops ...	28
Carpet Yarn Printing ...	21	Hot-water Supply ...	28
Ceramic Books ...	14, 15	How to make a Woollen Mill	
Charcoal ...	8	Pay ...	21
Chemical Essays ...	9	India-rubber ...	13
Chemistry of Pottery ...	17	Inks ...	3, 11
Chemistry of Dye-stuffs ...	23	Iron-corrosion ...	4
Clay Analysis ...	16	Iron, Science of ...	26
Coal-dust Firing ...	26	Japanning ...	28
Colour Matching ...	21	Lacquering ...	28
Colliery Recovery Work ...	25	Lake Pigments ...	2
Colour-mixing for Dyers ...	21	Lead and its Compounds ...	11
Colour Theory ...	22	Leather Industry ...	13
Combing Machines... ..	24	Leather-working Materials	14
Compounding Oils ...	6	Lithography ...	31
Condensing Apparatus ...	26	Lubricants ...	5, 6
Cosmetics ...	8	Manures ...	8, 10
Cotton Dyeing ...	23	Mineral Pigments ...	3
Cotton Spinning ...	24	Mine Ventilation ...	25
Damask Weaving ...	20	Mine Haulage ...	25
Dampness in Buildings ...	30	Oil and Colour Recipes ...	3
Decorators' Books ...	28	Oil Boiling ...	4
Decorative Textiles ...	20	Oil Merchants' Manual ...	7
Dental Metallurgy ...	25	Oils ...	12
Dictionary of Paint Materials	2	Ozone, Industrial Use of ...	5
Drying Oils ...	5	Paint Manufacture... ..	2
Drying with Air ...	12	Paint Materials ...	3
Dyeing Marble ...	31	Paint-material Testing ...	4
Dyeing Woollen Fabrics ...	23	Paper-pulp Dyeing... ..	18
		Petroleum ...	6
		Pigments, Chemistry of ...	2
		Plumbers' Work ...	27
		Porcelain Painting... ..	18
		Pottery Clays ...	16
		Pottery Manufacture ...	14
		Power-loom Weaving ...	19
		Preserved Foods ...	30
		Printers' Ready Reckoner	31
		Printing Inks ...	3
		Recipes for Oilmen, etc. ...	3
		Resins... ..	10
		Risks of Occupations ...	11
		Rivetting China, etc. ...	16
		Sanitary Plumbing ...	28
		Scheele's Essays ...	9
		Sealing Waxes ...	11
		Silk Dyeing ...	22
		Silk Throwing ...	19
		Smoke Prevention... ..	26
		Soaps ...	7
		Spinning ...	20
		Staining Marble, and Bone	31
		Steam Drying ...	11
		Sugar Refining ...	32
		Steel Hardening ...	26
		Sweetmeats ...	30
		Terra-cotta ...	16
		Testing Paint Materials ...	4
		Testing Yarns ...	20
		Textile Fabrics ...	20
		Textile Materials ...	19, 20
		Timber ...	29
		Varnishes ...	4
		Vegetable Fats ...	7
		Waste Utilisation ...	10
		Water, Industrial Use ...	12
		Waterproofing Fabrics ...	21
		Weaving Calculations ...	20
		Wood Waste Utilisation ...	29
		Wood Dyeing ...	31
		Wool Dyeing ...	22, 23
		Writing Inks ...	11
		X-Ray Work ...	13
		Yarn Testing ...	20

PUBLISHED BY

SCOTT, GREENWOOD & CO.,

19 LUDGATE HILL, LONDON, E.C.

Tel. Address: "PRINTERIES, LONDON".

Tel. No. 5403, Bank.

Paints, Colours and Printing Inks.

THE CHEMISTRY OF PIGMENTS. By ERNEST J. PARRY, B.Sc. (Lond.), F.I.C., F.C.S., and J. H. COSTE, F.I.C., F.C.S. Demy 8vo. Five Illustrations. 285 pp. 1902. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Introductory. Light—White Light—The Spectrum—The Invisible Spectrum—Normal Spectrum—Simple Nature of Pure Spectral Colour—The Reconstitution of White Light—Primary and Complementary Colours—Coloured Bodies—Absorption Spectra—**The Application of Pigments.** Uses of Pigments: Artistic, Decorative, Protective—Methods of Application of Pigments: Pastels and Crayons, Water Colour, Tempera Painting, Fresco, Encaustic Painting, Oil-colour Painting, Ceramic Art, Enamel, Stained and Painted Glass, Mosaic—**Inorganic Pigments.** White Lead—Zinc White—Enamel White—Whitening—Red Lead—Litharge—Vermilion—Royal Scarlet—The Chromium Greens—Chromates of Lead, Zinc, Silver and Mercury—Brunswick Green—The Ochres—Indian Red—Venetian Red—Siennas and Umbers—Light Red—Cappagh Brown—Red Oxides—Mars Colours—Terre Verte—Prussian Brown—Cobalt Colours—Cœruleum—Smalt—Copper Pigments—Malachite—Bremen Green—Scheele's Green—Emerald Green—Verdigris—Brunswick Green—Non-arsenical Greens—Copper Blues—Ultramarine—Carbon Pigments—Ivory Black—Lamp Black—Bistre—Naples Yellow—Arsenic Sulphides: Orpiment, Realgar—Cadmium Yellow—Vandyck Brown—**Organic Pigments.** Prussian Blue—Natural Lakes—Cochineal—Carmine—Crimson—Lac Dye—Scarlet—Madder—Alizarin—Campeachy—Quercitron—Rhamnus—Brazil Wood—Alkanet—Santal Wood—Archil—Coal-tar Lakes—Red Lakes—Alizarin Compounds—Orange and Yellow Lakes—Green and Blue Lakes—Indigo—Dragon's Blood—Gamboge—Sepia—Indian Yellow, Puree—Bitumen. Asphaltum, Mummy—**Index.**

THE MANUFACTURE OF PAINT. A Practical Handbook for Paint Manufacturers, Merchants and Painters. By J. CRUICKSHANK SMITH, B.Sc. Demy 8vo. 1901. 200 pp. Sixty Illustrations and One Large Diagram. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Preparation of Raw Material—Storing of Raw Material—Testing and Valuation of Raw Material—Paint Plant and Machinery—The Grinding of White Lead—Grinding of White Zinc—Grinding of other White Pigments—Grinding of Oxide Paints—Grinding of Staining Colours—Grinding of Black Paints—Grinding of Chemical Colours—Yellows—Grinding of Chemical Colours—Blues—Grinding Greens—Grinding Reds—Grinding Lakes—Grinding Colours in Water—Grinding Colours in Turpentine—The Uses of Paint—Testing and Matching Paints—Economic Considerations—**Index.**

DICTIONARY OF CHEMICALS AND RAW PRODUCTS USED IN THE MANUFACTURE OF PAINTS, COLOURS, VARNISHES AND ALLIED PREPARATIONS. By GEORGE H. HURST, F.C.S. Demy 8vo. 380 pp. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

THE MANUFACTURE OF LAKE PIGMENTS FROM ARTIFICIAL COLOURS. By FRANCIS H. JENNISON, F.I.C., F.C.S. Sixteen Coloured Plates, showing Specimens of Eighty-nine Colours, specially prepared from the Recipes given in the Book. 136 pp. Demy 8vo. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

The Groups of the Artificial Colouring Matters—The Nature and Manipulation of Artificial Colours—Lake-forming Bodies for Acid Colours—Lake-forming Bodies' Basic Colours—Lake Bases—The Principles of Lake Formation—Red Lakes—Orange, Yellow, Green, Blue, Violet and Black Lakes—The Production of Insoluble Azo Colours in the Form of Pigments—The General Properties of Lakes Produced from Artificial Colours—Washing, Filtering and Finishing—Matching and Testing Lake Pigments—**Index.**

THE MANUFACTURE OF MINERAL AND LAKE PIGMENTS.

Containing Directions for the Manufacture of all Artificial, Artists and Painters' Colours, Enamel, Soot and Metallic Pigments. A Text-book for Manufacturers, Merchants, Artists and Painters. By Dr. JOSEF BERSCH. Translated by A. C. WRIGHT, M.A. (Oxon.), B.Sc. (Lond.). Forty-three Illustrations. 476 pp., demy 8vo. 1901. Price 12s. 6d.; India and Colonies 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Introduction—Physico-chemical Behaviour of Pigments—Raw Materials Employed in the Manufacture of Pigments—Assistant Materials—Metallic Compounds—The Manufacture of Mineral Pigments—The Manufacture of White Lead—Enamel White—Washing Apparatus—Zinc White—Yellow Mineral Pigments—Chrome Yellow—Lead Oxide Pigments—Other Yellow Pigments—Mosaic Gold—Red Mineral Pigments—The Manufacture of Vermilion—Antimony Vermilion—Ferric Oxide Pigments—Other Red Mineral Pigments—Purple of Cassius—Blue Mineral Pigments—Ultramarine—Manufacture of Ultramarine—Blue Copper Pigments—Blue Cobalt Pigments—Smalts—Green Mineral Pigments—Emerald Green—Verdigris—Chromium Oxide—Other Green Chromium Pigments—Green Cobalt Pigments—Green Manganese Pigments—Compounded Green Pigments—Violet Mineral Pigments—Brown Mineral Pigments—Brown Decomposition Products—Black Pigments—Manufacture of Soot Pigments—Manufacture of Lamp Black—The Manufacture of Soot Black without Chambers—Indian Ink—Enamel Colours—Metallic Pigments—Bronze Pigments—Vegetable Bronze Pigments.

PIGMENTS OF ORGANIC ORIGIN—Lakes—Yellow Lakes—Red Lakes—Manufacture of Carmine—The Colouring Matter of Lac—Safflower or Carthamine Red—Madder and its Colouring Matters—Madder Lakes—Manjit (Indian Madder)—Lichen Colouring Matters—Red Wood Lakes—The Colouring Matters of Sandal Wood and Other Dye Woods—Blue Lakes—Indigo Carmine—The Colouring Matter of Log Wood—Green Lakes—Brown Organic Pigments—Sap Colours—Water Colours—Crayons—Confectionery Colours—The Preparation of Pigments for Painting—The Examination of Pigments—Examination of Lakes—The Testing of Dye-Woods—The Design of a Colour Works—Commercial Names of Pigments—Appendix: Conversion of Metric to English Weights and Measures—Centigrade and Fahrenheit Thermometer Scales—Index.

RECIPES FOR THE COLOUR, PAINT, VARNISH, OIL, SOAP AND DRY-SALTERY TRADES.

Compiled by AN ANALYTICAL CHEMIST. 350 pp. 1902. Demy 8vo. Price 7s. 6d.; India and British Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Pigments or Colours for Paints, Lithographic and Letterpress Printing Inks, etc.—Mixed Paints and Preparations for Paint-making, Painting, Lime-washing, Paperhanging, etc.—Varnishes for Coach-builders, Cabinetmakers, Wood-workers, Metal-workers, Photographers, etc.—Soaps for Toilet, Cleansing, Polishing, etc.—Perfumes—Lubricating Greases, Oils, etc.—Cements, Pastes, Glues and Other Adhesive Preparations—Writing, Marking, Endorsing and Other Inks—Sealing-wax and Office Requisites—Preparations for the Laundry, Kitchen, Stable and General Household Uses—Disinfectant Preparations—Miscellaneous Preparations—Index.

OIL COLOURS AND PRINTING INKS.

By LOUIS EDGAR ANDÉS. Translated from the German. 215 pp. Crown 8vo. 56 Illustrations. 1903. Price 5s.; India and British Colonies, 5s. 6d.; Other Countries, 6s.; strictly Net.

Contents.

Linseed Oil—Poppy Oil—Mechanical Purification of Linseed Oil—Chemical Purification of Linseed Oil—Bleaching Linseed Oil—Oxidizing Agents for Boiling Linseed Oil—Theory of Oil Boiling—Manufacture of Boiled Oil—Adulterations of Boiled Oil—Chinese Drying Oil and Other Specialities—Pigments for House and Artistic Painting and Inks—Pigment for Printers' Black Inks—Substitutes for Lampblack—Machinery for Colour Grinding and Rubbing—Machines for mixing Pigments with the Vehicle—Paint Mills—Manufacture of House Oil Paints—Ship Paints—Luminous Paint—Artists' Colours—Printers' Inks—VEHICLES—Printers' Inks—PIGMENTS and MANUFACTURE—Index.

(See also *Writing Inks*, p. 11.)

SIMPLE METHODS FOR TESTING PAINTERS' MATERIALS. By A. C. WRIGHT, M.A. (Oxon.), B.Sc. (Lond.). Crown 8vo. 160 pp. 1903. Price 5s.; India and British Colonies, 5s. 6d.; Other Countries, 6s.; strictly Net.

Contents.

Necessity for Testing—Standards—Arrangement—The Apparatus—The Reagents—Practical Tests—Dry Colours—Stiff Paints—Liquid and Enamel Paints—Oil Varnishes—Spirit Varnishes—Driers—Putty—Linseed Oil—Turpentine—Water Stains—The Chemical Examination—Dry Colours and Paints—White Pigments and Paints—Yellow Pigments and Paints—Blue Pigments and Paints—Green Pigments and Paints—Red Pigments and Paints—Brown Pigments and Paints—Black Pigments and Paints—Oil Varnishes—Linseed Oil—Turpentine.

IRON - CORROSION, ANTI - FOULING AND ANTI-CORROSIVE PAINTS. Translated from the German of LOUIS EDGAR ANDÉS. Sixty-two Illustrations. 275 pp. Demy 8vo. 1900. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Iron-rust and its Formation—Protection from Rusting by Paint—Grounding the Iron with Linseed Oil, etc.—Testing Paints—Use of Tar for Painting on Iron—Anti-corrosive Paints—Linseed Varnish—Chinese Wood Oil—Lead Pigments—Iron Pigments—Artificial Iron Oxides—Carbon—Preparation of Anti-corrosive Paints—Results of Examination of Several Anti-corrosive Paints—Paints for Ship's Bottoms—Anti-fouling Compositions—Various Anti-corrosive and Ship's Paints—Official Standard Specifications for Ironwork Paints—Index.

THE TESTING AND VALUATION OF RAW MATERIALS USED IN PAINT AND COLOUR MANUFACTURE. By M. W. JONES, F.C.S. A Book for the Laboratories of Colour Works. 88 pp. Crown 8vo. 1900. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Aluminium Compounds—China Clay—Iron Compounds—Potassium Compounds—Sodium Compounds—Ammonium Hydrate—Acids—Chromium Compounds—Tin Compounds—Copper Compounds—Lead Compounds—Zinc Compounds—Manganese Compounds—Arsenic Compounds—Antimony Compounds—Calcium Compounds—Barium Compounds—Cadmium Compounds—Mercury Compounds—Ultramarine—Cobalt and Carbon Compounds—Oils—Index.

STUDENTS' MANUAL OF PAINTS, COLOURS, OILS AND VARNISHES. By JOHN FURNELL. Crown 8vo. 12 Illustrations. 96 pp. 1903. Price 2s. 6d.; Abroad, 3s.; strictly net.

Contents.

Plant—Chromes—Blues—Greens—Earth Colours—Blacks—Reds—Lakes—Whites—Painters' Oils—Turpentine—Oil Varnishes—Spirit Varnishes—Liquid Paints—Enamel Paints.

Varnishes and Drying Oils.

THE MANUFACTURE OF VARNISHES, OIL REFINING AND BOILING, AND KINDRED INDUSTRIES. Translated from the French of ACH. LIVACHE, Ingénieur Civil des Mines. Greatly Extended and Adapted to English Practice, with numerous Original Recipes by JOHN GEDDES MCINTOSH. 27 Illustrations. 400 pp. Demy 8vo. 1899. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Resins—Solvents: Natural, Artificial, Manufacture, Storage, Special Use—Colouring: Principles, Vegetable, Coal Tar, Coloured Resinates, Coloured Oleates and Linoleates—Gum Running: Melting Pots, Mixing Pans—Spirit Varnish Manufacture: Cold Solution Plant, Mechanical Agitators, Storage Plant—Manufacture, Characteristics and Uses of the Spirit Varnishes—Manufacture of Varnish Stains—Manufacture of Lacquers—Manufacture of Spirit Enamels—Analysis of Spirit Varnishes—Physical and Chemical Constants of Resins—Table of Solubility of Resins in different Menstrua—Systematic qualitative Analysis of Resins, Hirschop's tables—Drying Oils—Oil Refining: Processes—Oil Boiling—Driers—Liquid Driers—Solidified Boiled Oil—Manufacture of Linoleum—Manufacture of India Rubber Substitutes—Printing Ink Manufacture—Lithographic Ink Manufacture—Manufacture of Oil Varnishes—Running and Special Treatment of Amber, Copal, Kauri, Manilla—Addition of Oil to Resin—Addition of Resin to Oil—Mixed Processes—Solution in Cold of previously Fused Resin—Dissolving Resins in Oil, etc., under pressure—Filtration—Clarification—Storage—Ageing—Coachmakers' Varnishes and Japans—Oak Varnishes—Japanners' Stoving Varnishes—Japanners' Gold Size—Brunswick Black—Various Oil Varnishes—Oil-Varnish Stains—Varnishes for "Enamels"—India Rubber Varnishes—Varnishes Analysis: Processes, Matching—Faults in Varnishes: Cause, Prevention—Experiments and Exercises.

DRYING OILS, BOILED OIL AND SOLID AND LIQUID DRIERS. By L. E. ANDÉS. Expressly Written for this Series of Special Technical Books, and the Publishers hold the Copyright for English and Foreign Editions. Forty-two Illustrations. 342 pp. 1901. Demy 8vo. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Properties of the Drying Oils; Cause of the Drying Property; Absorption of Oxygen; Behaviour towards Metallic Oxides, etc.—The Properties of and Methods for obtaining the Drying Oils—Production of the Drying Oils by Expression and Extraction; Refining and Bleaching; Oil Cakes and Meal; The Refining and Bleaching of the Drying Oils; The Bleaching of Linseed Oil—The Manufacture of Boiled Oil; The Preparation of Drying Oils for Use in the Grinding of Paints and Artists' Colours and in the Manufacture of Varnishes by Heating over a Fire or by Steam, by the Cold Process, by the Action of Air, and by Means of the Electric Current; The Driers used in Boiling Linseed Oil; The Manufacture of Boiled Oil and the Apparatus therefor; Livache's Process for Preparing a Good Drying Oil and its Practical Application—The Preparation of Varnishes for Letterpress, Lithographic and Copperplate Printing, for Oilcloth and Waterproof Fabrics; The Manufacture of Thickened Linseed Oil, Burnt Oil, Stand Oil by Fire Heat, Superheated Steam, and by a Current of Air—Behaviour of the Drying Oils and Boiled Oils towards Atmospheric Influences, Water, Acids and Alkalies—Boiled Oil Substitutes—The Manufacture of Solid and Liquid Driers from Linseed Oil and Rosin; Linolic Acid Compounds of the Driers—The Adulteration and Examination of the Drying Oils and Boiled Oil.

Oils, Fats, Soaps and Perfumes.

LUBRICATING OILS, FATS AND GREASES: Their Origin, Preparation, Properties, Uses and Analyses. A Handbook for Oil Manufacturers, Refiners and Merchants, and the Oil and Fat Industry in General. By GEORGE H. HURST, F.C.S. Second Revised and Enlarged Edition. Sixty-five Illustrations. 317 pp. Demy 8vo. 1902. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s. strictly net.

Contents.

Introductory—Hydrocarbon Oils—Scotch Shale Oils—Petroleum—Vegetable and Animal Oils—Testing and Adulteration of Oils—Lubricating Greases—Lubrication—Appendices—Index.

TECHNOLOGY OF PETROLEUM: Oil Fields of the World—Their History, Geography and Geology—Annual Production and Development—Oil-well Drilling—Transport. By HENRY NEUBERGER and HENRY NOALHAT. Translated from the French by J. G. McINTOSH. 550 pp. 153 Illustrations. 26 Plates. Super Royal 8vo. 1901. Price 21s.; India and Colonies, 22s.; Other Countries, 23s. 6d.; strictly net.

Contents.

Study of the Petroliferous Strata—Petroleum—Definition—The Genesis or Origin of Petroleum—The Oil Fields of Galicia, their History—Physical Geography and Geology of the Galician Oil Fields—Practical Notes on Galician Land Law—Economic Hints on Working, etc.—Roumania—History, Geography, Geology—Petroleum in Russia—History—Russian Petroleum (*continued*)—Geography and Geology of the Caucasian Oil Fields—Russian Petroleum (*continued*)—The Secondary Oil Fields of Europe, Northern Germany, Alsace, Italy, etc.—Petroleum in France—Petroleum in Asia—Transcaspian and Turkestan Territory—Turkestan—Persia—British India and Burmah—British Burmah or Lower Burmah—China—Chinese Thibet—Japan, Formosa and Saghalien—Petroleum in Oceania—Sumatra, Java, Borneo—Isle of Timor—Philippine Isles—New Zealand—The United States of America—History—Physical Geology and Geography of the United States Oil Fields—Canadian and other North American Oil Fields—Economic Data of Work in North America—Petroleum in the West Indies and South America—Petroleum in the French Colonies.

Excavations—Hand Excavation or Hand Digging of Oil Wells.

Methods of Boring.

Accidents—Boring Accidents—Methods of preventing them—Methods of remedying them—Explosives and the use of the "Torpedo" Levigation—Storing and Transport of Petroleum—General Advice—Prospecting, Management and carrying on of Petroleum Boring Operations.

General Data—Customary Formulæ—Memento. Practical Part. General Data bearing on Petroleum—Glossary of Technical Terms used in the Petroleum Industry—Copious Index.

THE PRACTICAL COMPOUNDING OF OILS, TALLOW AND GREASE FOR LUBRICATION, ETC.

By AN EXPERT OIL REFINER. 100 pp. 1898. Demy 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Introductory Remarks on the General Nomenclature of Oils, Tallow and Greases suitable for Lubrication—**Hydrocarbon Oils**—Animal and Fish Oils—**Compound Oils**—Vegetable Oils—Lamp Oils—Engine Tallow, Solidified Oils and Petroleum Jelly—**Machinery Greases:** Loco and Anti-friction—Clarifying and Utilisation of Waste Fats, Oils, Tank Bottoms, Drainings of Barrels and Drums, Pickings Up, Dregs, etc.—The Fixing and Cleaning of Oil Tanks, etc.—Appendix and General Information.

ANIMAL FATS AND OILS: Their Practical Production,

Purification and Uses for a great Variety of Purposes. Their Properties, Falsification and Examination. Translated from the German of LOUIS EDGAR ANDÉS. Sixty-two Illustrations. 240 pp. 1898. Demy 8vo. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Introduction—Occurrence, Origin, Properties and Chemical Constitution of Animal Fats—Preparation of Animal Fats and Oils—Machinery—Tallow-melting Plant—Extraction Plant—Presses—Filtering Apparatus—Butter: Raw Material and Preparation, Properties, Adulterations, Beef Lard or Remelted Butter, Testing—Candle-fish Oil—Mutton-Tallow—Hare Fat—Goose Fat—Neatsfoot Oil—Bone Fat: Bone Boiling, Steaming Bones, Extraction, Refining—Bone Oil—Artificial Butter: Oleomargarine, Margarine Manufacture in France, Grasso's Process, "Kaiser's Butter," Jahr & Münzberg's Method, Filbert's Process, Winter's Method—Human Fat—Horse Fat—Beef Marrow—Turtle Oil—Hog's Lard: Raw Material—Preparation, Properties, Adulterations, Examination—Lard Oil—Fish Oils—Liver Oils—Artificial Train Oil—Wool Fat: Properties, Purified Wool Fat—Spermaceti: Examination of Fats and Oils in General.

THE OIL MERCHANTS' MANUAL AND OIL TRADE READY RECKONER. Compiled by FRANK F. SHERRIFF. Second Edition Revised and Enlarged. Demy 8vo. 214 pp. 1904. With Two Sheets of Tables. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Trade Terms and Customs—Tables to Ascertain Value of Oil sold per cwt. or ton—Specific Gravity Tables—Percentage Tare Tables—Petroleum Tables—Paraffine and Benzoline Calculations—Customary Drafts—Tables for Calculating Allowance for Dirt, Water, etc.—Capacity of Circular Tanks Tables, etc., etc.

THE CHEMISTRY OF ESSENTIAL OILS AND ARTIFICIAL PERFUMES. By ERNEST J. PARRY, B.Sc. (Lond.), F.I.C., F.C.S. 411 pp. 20 Illustrations. 1899. Demy 8vo. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

The General Properties of Essential Oils—Compounds occurring in Essential Oils—The Preparation of Essential Oils—The Analysis of Essential Oils—Systematic Study of the Essential Oils—Terpeneless Oils—The Chemistry of Artificial Perfumes—Appendix: Table of Constants—Index.

VEGETABLE FATS AND OILS: Their Practical Preparation, Purification and Employment for Various Purposes, their Properties, Adulteration and Examination. Translated from the German of LOUIS EDGAR ANDÉS. Ninety-four Illustrations. 340 pp. Second Edition. 1902. Demy 8vo. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

General Properties—Estimation of the Amount of Oil in Seeds—The Preparation of Vegetable Fats and Oils—Apparatus for Grinding Oil Seeds and Fruits—Installation of Oil and Fat Works—Extraction Method of Obtaining Oils and Fats—Oil Extraction Installations—Press Moulds—Non-drying Vegetable Oils—Vegetable drying Oils—Solid Vegetable Fats—Fruits Yielding Oils and Fats—Wool-softening Oils—Soluble Oils—Treatment of the Oil after Leaving the Press—Improved Methods of Refining—Bleaching Fats and Oils—Practical Experiments on the Treatment of Oils with regard to Refining and Bleaching—Testing Oils and Fats.

SOAPS. A Practical Manual of the Manufacture of Domestic, Toilet and other Soaps. By GEORGE H. HURST, F.C.S. 390 pp. 66 Illustrations. 1898. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Introductory—Soap-maker's Alkalies—Soap Fats and Oils—Perfumes—Water as a Soap Material—Soap Machinery—Technology of Soap-making—Glycerine in Soap Lyes—Laying out a Soap Factory—Soap Analysis—Appendices.

Textile Soaps.

TEXTILE SOAPS AND OILS. Handbook on the Preparation, Properties and Analysis of the Soaps and Oils used in Textile Manufacturing, Dyeing and Printing. By GEORGE H. HURST, F.C.S. Crown 8vo. 195 pp. 1904. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Methods of Making Soaps—Hard Soap—Soft Soap. Special Textile Soaps—Wool Soaps—Calico Printers' Soaps—Dyers' Soaps. Relation of Soap to Water for Industrial Purposes—Treating Waste Soap Liquors—Boiled Off Liquor—Calico Printers' and Dyers' Soap Liquors—Soap Analysis—Fat in Soap.

ANIMAL AND VEGETABLE OILS AND FATS—Tallow—Lard—Bone Grease—Tallow Oil. Vegetable Soap, Oils and Fats—Palm Oil—Coco-nut Oil—Olive Oil—Cotton-seed Oil—Linseed Oil—Castor Oil—Corn Oil—Whale Oil or Train Oil—Repe Oil.

GLYCERINE.

TEXTILE OILS—Oleic Acid—Blended Wool Oils—Oils for Cotton Dyeing, Printing and Finishing—Turkey Red Oil—Alizarine Oil—Oleine—Oxy Turkey Red Oils—Soluble Oil—Analysis of Turkey Red Oil—Finisher's Soluble Oil—Finisher's Soap Softening—Testing and Adulteration of Oils—Index.

Cosmetical Preparations.

COSMETICS: MANUFACTURE, EMPLOYMENT AND TESTING OF ALL COSMETIC MATERIALS AND COSMETIC SPECIALITIES.

Translated from the German of Dr. THEODOR KOLLER. Crown 8vo. 262 pp. 1902. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s. net.

Contents.

Purposes and Uses of, and Ingredients used in the Preparation of Cosmetics—Preparation of Perfumes by Pressure, Distillation, Maceration, Absorption or Enflourage, and Extraction Methods—Chemical and Animal Products used in the Preparation of Cosmetics—Oils and Fats used in the Preparation of Cosmetics—General Cosmetic Preparations—Mouth Washes and Tooth Pastes—Hair Dyes, Hair Restorers and Depilatories—Cosmetic Adjuncts and Specialities—Colouring Cosmetic Preparations—Antiseptic Washes and Soaps—Toilet and Hygienic Soaps—Secret Preparations for Skin, Complexion, Teeth, Mouth, etc.—Testing and Examining the Materials Employed in the Manufacture of Cosmetics—Index.

Glue, Bone Products and Manures.

GLUE AND GLUE TESTING. By SAMUEL RIDEAL, D.Sc.

(Lond.), F.I.C. Fourteen Engravings. 144 pp. Demy 8vo. 1900. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Constitution and Properties: Definitions and Sources, Gelatine, Chondrin and Allied Bodies, Physical and Chemical Properties, Classification, Grades and Commercial Varieties—**Raw Materials and Manufacture:** Glue Stock, Lining, Extraction, Washing and Clarifying, Filter Presses, Water Supply, Use of Alkalies, Action of Bacteria and of Antiseptics, Various Processes, Cleansing, Forming, Drying, Crushing, etc., Secondary Products—**Uses of Glue:** Selection and Preparation for Use, Carpentry, Veneering, Paper-Making, Book-binding, Printing Rollers, Hectographs, Match Manufacture, Sandpaper, etc., Substitutes for other Materials, Artificial Leather and Caoutchouc—**Gelatine:** General Characters, Liquid Gelatine, Photographic Uses, Size, Tanno, Chrome and Formo-Gelatine, Artificial Silk, Cements, Pneumatic Tyres, Culinary, Meat Extracts, Isinglass, Medicinal and other Uses, Bacteriology—**Glue Testing:** Review of Processes, Chemical Examination, Adulteration, Physical Tests, Valuation of Raw Materials—**Commercial Aspects.**

BONE PRODUCTS AND MANURES: An Account of the

most recent Improvements in the Manufacture of Fat, Glue, Animal Charcoal, Size, Gelatine and Manures. By THOMAS LAMBERT, Technical and Consulting Chemist. Illustrated by Twenty-one Plans and Diagrams. 162 pp. Demy 8vo. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Chemical Composition of Bones—Arrangement of Factory—Properties of Glue—Glutin and Chondrin—Skin Glue—Liming of Skins—Washing—Boiling of Skins—Clarification of Glue Liquors—Glue-Boiling and Clarifying-House—Specification of a Glue—Size—Uses and Preparation and Composition of Size—Concentrated Size—Properties of Gelatine—Preparation of Skin Gelatine—Drying—Bone Gelatine—Selecting Bones—Crushing—Dissolving—Bleaching—Boiling—Properties of Glutin and Chondrin—Testing of Glues and Gelatines—The Uses of Glue, Gelatine and Size in Various Trades—Soluble and Liquid Glues—Steam and Waterproof Glues—**Manures**—Importation of Food Stuffs—Soils—Germination—Plant Life—**Natural Manures**—Water and Nitrogen in Farmyard Manure—Full Analysis of Farmyard Manure—Action on Crops—Water-Closet System—Sewage Manure—Green Manures—**Artificial Manures**—**Mineral Manures**—Nitrogenous Matters—Shoddy—Hoofs and Horns—Leather Waste—Dried Meat—Dried Blood—Superphosphates—Composition—Manufacture—Common Raw Bones—Degreased Bones—Crude Fat—Refined Fat—Degelatinised Bones—Animal Charcoal—Bone Superphosphates—Guanos—Dried Animal Products—Potash Compounds—Sulphate of Ammonia—Extraction in Vacuo—French and British Gelatines compared—Index.

Chemicals, Waste Products and Agricultural Chemistry.

REISSUE OF CHEMICAL ESSAYS OF C. W. SCHEELÉ. First Published in English in 1786. Translated from the Academy of Sciences at Stockholm, with Additions. 300 pp. Demy 8vo. 1901. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Memoir: C. W. Scheele and his work (written for this edition by J. G. McIntosh)—On Fluor Mineral and its Acid—On Fluor Mineral—Chemical Investigation of Fluor Acid, with a View to the Earth which it Yields, by Mr. Wiegler—Additional Information Concerning Fluor Minerals—On Manganese, Magnesium, or Magnesia Vitriariorum—On Arsenic and its Acid—Remarks upon Salts of Benzoin—On Silex, Clay and Alum—Analysis of the Calculus Vesical—Method of Preparing Mercurius Dulcis Via Humida—Cheaper and more Convenient Method of Preparing Pulvis Algarothi—Experiments upon Molybdæna—Experiments on Plumbago—Method of Preparing a New Green Colour—Of the Decomposition of Neutral Salts by Unslaked Lime and Iron—On the Quantity of Pure Air which is Daily Present in our Atmosphere—On Milk and its Acid—On the Acid of Saccharum Lactis—On the Constituent Parts of Lapis Ponderosus or Tungsten—Experiments and Observations on Ether—Index.

THE MANUFACTURE OF ALUM AND THE SULPHATES AND OTHER SALTS OF ALUMINA AND IRON. Their Uses and Applications as Mordants in Dyeing and Calico Printing, and their other Applications in the Arts, Manufactures, Sanitary Engineering, Agriculture and Horticulture. Translated from the French of LUCIEN GESCHWIND. 195 Illustrations. 400 pp. Royal 8vo. 1901. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Theoretical Study of Aluminium, Iron, and Compounds of these Metals—Aluminium and its Compounds—Iron and Iron Compounds.
Manufacture of Aluminium Sulphates and Sulphates of Iron—Manufacture of Aluminium Sulphate and the Alums—Manufacture of Sulphates of Iron.
Uses of the Sulphates of Aluminium and Iron—Uses of Aluminium Sulphate and Alums—Application to Wool and Silk—Preparing and using Aluminium Acetates—Employment of Aluminium Sulphate in Carbonising Wool—The Manufacture of Lake Pigments—Manufacture of Prussian Blue—Hide and Leather Industry—Paper Making—Hardening Plaster—Lime Washes—Preparation of Non-inflammable Wood, etc.—Purification of Waste Waters—**Uses and Applications of Ferrous Sulphate and Ferric Sulphates—**Dyeing—Manufacture of Pigments—Writing Inks—Purification of Lighting Gas—Agriculture—Cotton Dyeing—Disinfectant—Purifying Waste Liquors—Manufacture of Nordhausen Sulphuric Acid—Fertilising.
Chemical Characteristics of Iron and Aluminium—Analysis of Various Aluminous or Ferruginous Products—Aluminium—Analysing Aluminium Products—Alunite Alumina—Sodium Aluminate—Aluminium Sulphate—**Iron—**Analytical Characteristics of Iron Salts—Analysis of Pyritic Lignite—Ferrous and Ferric Sulphates—Rouil Mordant—Index.

AMMONIA AND ITS COMPOUNDS: Their Manufacture and Uses. By CAMILLE VINCENT, Professor at the Central School of Arts and Manufactures, Paris. Translated from the French by M. J. SALTER. Royal 8vo. 114 pp. 1901. Thirty-two Illustrations. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

General Considerations: Various Sources of Ammoniacal Products; Human Urine as a Source of Ammonia—**Extraction of Ammoniacal Products from Sewage—**Extraction of Ammonia from Gas Liquor—Manufacture of Ammoniacal Compounds from Bones, Nitrogenous Waste, Beetroot Wash and Peat—Manufacture of Caustic Ammonia, and Ammonium Chloride, Phosphate and Carbonate—Recovery of Ammonia from the Ammonia-Soda Mother Liquors—Index.

ANALYSIS OF RESINS AND BALSAMS. Translated from the German of Dr. KARL DIETERICH. Demy 8vo. 340 pp. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Definition of Resins in General—Definition of Balsams, and especially the Gum Resins—External and Superficial Characteristics of Resinous Bodies—Distinction between Resinous Bodies and Fats and Oils—Origin, Occurrence and Collection of Resinous Substances—Classification—Chemical Constituents of Resinous Substances—Resinols—Resinot Annols—Behaviour of Resin Constituents towards the Cholesterine Reactions—Uses and Identification of Resins—Melting-point—Solvents—Acid Value—Saponification Value—Resin Value—Ester and Ether Values—Acetyl and Corbonyl Value—Methyl Value—Resin Acid—Systematic Résumé of the Performance of the Acid and Saponification Value Tests.

Balsams—Introduction—Definitions—Canada Balsam—Copaiba Balsam—Angostura Copaiba Balsam—Babia Copaiba Balsam—Carthagea Copaiba Balsam—Maracaibo Copaiba Balsam—Maturin Copaiba Balsam—Gurjum Copaiba Balsam—Para Copaiba Balsam—Surinam Copaiba Balsam—West African Copaiba Balsam—Mecca Balsam—Peruvian Balsam—Tolu Balsam—Acaroid Resin—Amine—Amber—African and West Indian Kino—Bengal Kino—Labdanum—Mastic—Pine Resin—Sandarach—Scammonium—Shellac—Storax—Adulteration of Styrax Liquidus Crudus—Purified Storax—Styrax Crudus Colatus—Tacamahac—Thapsia Resin—Turpentine—Chios Turpentine—Strassburg Turpentine—Turpeth Turpentine. **Gum Resins**—Ammoniacum—Bdellium—Euphorbium—Galbanum—Gamboge—Lactucarium—Myrrh—Opananax—Sagapenum—Olibanum or Incense—Acaroid Resin—Amber—Thapsia Resin—Index.

MANUAL OF AGRICULTURAL CHEMISTRY. By HERBERT INGLE, F.I.C., Lecturer on Agricultural Chemistry, the Yorkshire College; Lecturer in the Victoria University. 388 pp. 11 Illustrations. 1902. Demy 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d. net.

Contents.

Introduction—The Atmosphere—The Soil—The Reactions occurring in Soils—The Analysis of Soils—Manures, Natural—Manures (continued)—The Analysis of Manures—The Constituents of Plants—The Plant—Crops—The Animal—Foods and Feeding—Milk and Milk Products—The Analysis of Milk and Milk Products—Miscellaneous Products used in Agriculture—Appendix—Index.

THE UTILISATION OF WASTE PRODUCTS. A Treatise on the Rational Utilisation, Recovery and Treatment of Waste Products of all kinds. By Dr. THEODOR KOLLER. Translated from the Second Revised German Edition. Twenty-two Illustrations. Demy 8vo. 280 pp. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

The Waste of Towns—**Ammonia and Sal-Ammoniac**—Rational Processes for Obtaining these Substances by Treating Residues and Waste—Residues in the Manufacture of Aniline Dyes—Amber Waste—Brewers' Waste—Blood and Slaughter-House Refuse—Manufactured Fuels—Waste Paper and Bookbinders' Waste—Iron Slags—Excrement—Colouring Matters from Waste—Dyers' Waste Waters—Fat from Waste—Fish Waste—Calamine Sludge—Tannery Waste—Gold and Silver Waste—India-rubber and Caoutchouc Waste—Residues in the Manufacture of Rosin Oil—Wood Waste—Horn Waste—Infusorial Earth—Iridium from Goldsmiths' Sweepings—Jute Waste—Cork Waste—Leather Waste—Glue Makers' Waste—Illuminating Gas from Waste and the By-Products of the Manufacture of Coal Gas—Meerschum—Molasses—Metal Waste—By-Products in the Manufacture of Mineral Waters—Fruit—The By-Products of Paper and Paper Pulp Works—By-Products in the Treatment of Coal Tar Oils—Fur Waste—The Waste Matter in the Manufacture of Parchment Paper—Mother of Pearl Waste—Petroleum Residues—Platinum Residues—Broken Porcelain. Earthenware and Glass—Salt Waste—Slate Waste—Sulphur—Burnt Pyrites—Silk Waste—Soap Makers' Waste—Alkali Waste and the Recovery of Soda—Waste Produced in Grinding Mirrors—Waste Products in the Manufacture of Starch—Stearic Acid—Vegetable Ivory Waste—Turf—Waste Waters of Cloth Factories—Wine Residues—Tinplate Waste—Wool Waste—Wool Sweat—The Waste Liquids from Sugar Works—Index.

Writing Inks and Sealing Waxes.

INK MANUFACTURE : Including Writing, Copying, Lithographic, Marking, Stamping, and Laundry Inks. By SIGMUND LEHNER. Three Illustrations. Crown 8vo. 162 pp. 1902. Translated from the German of the Fifth Edition. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; net.

Contents.

Varieties of Ink—Writing Inks—Raw Materials of Tannin Inks—The Chemical Constitution of the Tannin Inks—Recipes for Tannin Inks—Logwood Tannin Inks—Ferric Inks—Alizarine Inks—Extract Inks—Logwood Inks—Copying Inks—Hektographs—Hektograph Inks—Safety Inks—Ink Extracts and Powders—Preserving Inks—Changes in Ink and the Restoration of Faded Writing—Coloured Inks—Red Inks—Blue Inks—Violet Inks—Yellow Inks—Green Inks—Metallic Inks—Indian Ink—Lithographic Inks and Pencils—Ink Pencils—Marking Inks—Ink Specialities—Sympathetic Inks—Stamping Inks—Laundry or Washing Blue—Index

SEALING-WAXES, WAFERS AND OTHER ADHESIVES FOR THE HOUSEHOLD, OFFICE, WORKSHOP AND FACTORY. By H. C. STANDAGE. Crown 8vo. 96 pp. 1902. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Materials Used for Making Sealing-Waxes—The Manufacture of Sealing-Waxes—Wafers—Notes on the Nature of the Materials Used in Making Adhesive Compounds—Cements for Use in the Household—Office Gums, Pastes and Mucilages—Adhesive Compounds for Factory and Workshop Use.

Lead Ores and Compounds.

LEAD AND ITS COMPOUNDS. By THOS. LAMBERT, Technical and Consulting Chemist. Demy 8vo. 226 pp. Forty Illustrations. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; net. Plans and Diagrams.

Contents.

History—Ores of Lead—Geographical Distribution of the Lead Industry—Chemical and Physical Properties of Lead—Alloys of Lead—Compounds of Lead—Dressing of Lead Ores—Smelting of Lead Ores—Smelting in the Scotch or American Ore-hearth—Smelting in the Shaft or Blast Furnace—Condensation of Lead Fume—Desilverisation, or the Separation of Silver from Argentiferous Lead—Cupellation—The Manufacture of Lead Pipes and Sheets—Protoxide of Lead—Litharge and Massicot—Red Lead or Minium—Lead Poisoning—Lead Substitutes—Zinc and its Compounds—Pumice Stone—Drying Oils and Siccatives—Oil of Turpentine Resin—Classification of Mineral Pigments—Analysis of Raw and Finished Products—Tables—Index.

NOTES ON LEAD ORES : Their Distribution and Properties. By JAS. FAIRIE, F.G.S. Crown 8vo. 1901. 64 pages. Price 2s. 6d.; Abroad, 3s.; strictly net.

Industrial Hygiene.

THE RISKS AND DANGERS TO HEALTH OF VARIOUS OCCUPATIONS AND THEIR PREVENTION. By LEONARD A. PARRY, M.D., B.S. (Lond.). 196 pp. Demy 8vo. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Occupations which are Accompanied by the Generation and Scattering of Abnormal Quantities of Dust—Trades in which there is Danger of Metallic Poisoning—Certain Chemical Trades—Some Miscellaneous Occupations—Trades in which Various Poisonous Vapours are Inhaled—General Hygienic Considerations—Index.

Industrial Uses of Air, Steam and Water.

DRYING BY MEANS OF AIR AND STEAM. Explanations, Formulæ, and Tables for Use in Practice. Translated from the German of E. HAUSBRAND. Two folding Diagrams and Thirteen Tables. Crown 8vo. 1901. 72 pp. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

British and Metric Systems Compared—Centigrade and Fahr. Thermometers—Estimation of the Maximum Weight of Saturated Aqueous Vapour which can be contained in 1 kilo. of Air at Different Pressure and Temperatures—Calculation of the Necessary Weight and Volume of Air, and of the Least Expenditure of Heat, per Drying Apparatus with Heated Air, at the Atmospheric Pressure: *A*, With the Assumption that the Air is *Completely Saturated* with Vapour both before Entry and after Exit from the Apparatus—*B*, When the Atmospheric Air is Completely Saturated *before entry*, but at its *exit* is only $\frac{2}{3}$, $\frac{1}{2}$ or $\frac{1}{3}$ Saturated—*C*, When the Atmospheric Air is *not* Saturated with Moisture before Entering the Drying Apparatus—Drying Apparatus, in which, in the Drying Chamber, a Pressure is Artificially Created, Higher or Lower than that of the Atmosphere—Drying by Means of Superheated Steam, without Air—Heating Surface, Velocity of the Air Current, Dimensions of the Drying Room, Surface of the Drying Material, Losses of Heat—Index.

(See also "Evaporating, Condensing and Cooling Apparatus," p. 27.)

PURE AIR, OZONE AND WATER. A Practical Treatise of their Utilisation and Value in Oil, Grease, Soap, Paint, Glue and other Industries. By W. B. COWELL. Twelve Illustrations. Crown 8vo. 85 pp. 1900. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Atmospheric Air; Lifting of Liquids; Suction Process; Preparing Blown Oils; Preparing Siccative Drying Oils—Compressed Air; Whitewash—Liquid Air; Retrocession—Purification of Water; Water Hardness—Fleshings and Bones—Ozonised Air in the Bleaching and Deodorising of Fats, Glues, etc.; Bleaching Textile Fibres—Appendix: Air and Gases; Pressure of Air at Various Temperatures; Fuel; Table of Combustibles; Saving of Fuel by Heating Feed Water; Table of Solubilities of Scale Making Minerals; British Thermal Units Tables; Volume of the Flow of Steam into the Atmosphere; Temperature of Steam—Index.

THE INDUSTRIAL USES OF WATER. COMPOSITION—EFFECTS—TROUBLES—REMEDIES—RESIDUARY WATERS—PURIFICATION—ANALYSIS.

By H. DE LA COUX. Royal 8vo. Translated from the French and Revised by ARTHUR MORRIS. 364 pp. 135 Illustrations. 1903. Price 10s. 6d.; Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Chemical Action of Water in Nature and in Industrial Use—Composition of Waters—Solubility of Certain Salts in Water Considered from the Industrial Point of View—Effects on the Boiling of Water—Effects of Water in the Industries—Difficulties with Water—Feed Water for Boilers—Water in Dyeworks, Print Works, and Bleach Works—Water in the Textile Industries and in Conditioning—Water in Soap Works—Water in Laundries and Washhouses—Water in Tanning—Water in Preparing Tannin and Dyewood Extracts—Water in Papermaking—Water in Photography—Water in Sugar Refining—Water in Making Ices and Beverages—Water in Cider Making—Water in Brewing—Water in Distilling—Preliminary Treatment and Apparatus—Substances Used for Preliminary Chemical Purification—Commercial Specialities and their Employment—Precipitation of Matters in Suspension in Water—Apparatus for the Preliminary Chemical Purification of Water—Industrial Filters—Industrial Sterilisation of Water—Residuary Waters and their Purification—Soil Filtration—Purification by Chemical Processes—Analyses—Index.

(See Books on Smoke Prevention, Engineering and Metallurgy, p. 26, etc.)

X Rays.

PRACTICAL X RAY WORK. By FRANK T. ADDYMAN, B.Sc. (Lond.), F.I.C., Member of the Roentgen Society of London; Radiographer to St. George's Hospital; Demonstrator of Physics and Chemistry, and Teacher of Radiography in St. George's Hospital Medical School. Demy 8vo. Twelve Plates from Photographs of X Ray Work. Fifty-two Illustrations. 200 pp. 1901. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Historical—Work leading up to the Discovery of the X Rays—The Discovery—**Apparatus and its Management**—Electrical Terms—Sources of Electricity—Induction Coils—Electrostatic Machines—Tubes—Air Pumps—Tube Holders and Stereoscopic Apparatus—Fluorescent Screens—**Practical X Ray Work**—Installations—Radioscopy—Radiography—X Rays in Dentistry—X Rays in Chemistry—X Rays in War—Index.

List of Plates.

Frontispiece—Congenital Dislocation of Hip-Joint.—I., Needle in Finger.—II., Needle in Foot.—III., Revolver Bullet in Calf and Leg.—IV., A Method of Localisation.—V., Stellate Fracture of Patella showing shadow of "Strapping".—VI., Sarcoma.—VII., Six-weeks-old Injury to Elbow showing new Growth of Bone.—VIII., Old Fracture of Tibia and Fibula badly set.—IX., Heart Shadow.—X., Fractured Femur showing Grain of Splint.—XI., Barrell's Method of Localisation.

India-Rubber and Gutta Percha.

INDIA-RUBBER AND GUTTA PERCHA. Translated from the French of T. SEELIGMANN, G. LAMY TORVILHON and H. FALCONNET by JOHN GEDDES MCINTOSH. Royal 8vo. Eighty-six Illustrations. Three Plates. 412 pages. 1903. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

India-Rubber—Botanical Origin—Climatology—Soil—Rational Culture and Acclimation of the Different Species of India-Rubber Plants—Methods of Obtaining the Latex—Methods of Preparing Raw or Crude India-Rubber—Classification of the Commercial Species of Raw Rubber—Physical and Chemical Properties of the Latex and of India-Rubber—Mechanical Transformation of Natural Caoutchouc into Washed or Normal Caoutchouc (Purification) and Normal Rubber into Masticated Rubber—Softening, Cutting, Washing, Drying—Preliminary Observations—Vulcanisation of Normal Rubber—Chemical and Physical Properties of Vulcanised Rubber—General Considerations—Hardened Rubber or Ebonite—Considerations on Mineralisation and other Mixtures—Coloration and Dyeing—Analysis of Natural or Normal Rubber and Vulcanised Rubber—Rubber Substitutes—Imitation Rubber.

Gutta Percha—Botanical Origin—Climatology—Soil—Rational Culture—Methods of Collection—Classification of the Different Species of Commercial Gutta Percha—Physical and Chemical Properties—Mechanical Transformation—Methods of Analysing—Gutta Percha Substitutes—Index.

Leather Trades.

PRACTICAL TREATISE ON THE LEATHER INDUSTRY. By A. M. VILLON. Translated by FRANK T. ADDYMAN, B.Sc. (Lond.), F.I.C., F.C.S.; and Corrected by an Eminent Member of the Trade. 500 pp., royal 8vo. 1901. 123 Illustrations. Price 21s.; India and Colonies, 22s.; Other Countries, 23s. 6d.; strictly net.

Contents.

Preface—Translator's Preface—List of Illustrations.

Part I., Materials used in Tanning—Skins: Skin and its Structure; Skins used in Tanning; Various Skins and their Uses—Tannin and Tanning Substances: Tannin; Barks (Oak); Barks other than Oak; Tanning Woods; Tannin-bearing Leaves; Excrescences; Tan-bearing Fruits; Tan-bearing Roots and Bulbs; Tanning Juices; Tanning Substances used in Various Countries; Tannin Extracts; Estimation of Tannin and Tannin Principles.

Part II., Tanning—The Installation of a Tannery: Tan Furnaces; Chimneys, Boilers, etc.; Steam Engines—Grinding and Trituration of Tanning Substances: Cutting up Bark; Grinding Bark; The Grinding of Tan Woods; Powdering Fruit, Galls and Grains; Notes on

the Grinding of Bark—Manufacture of Sole Leather: Soaking; Sweating and Unhairing; Plumping and Colouring; Handling; Tanning; Tanning Elephants' Hides; Drying; Striking or Pinning—Manufacture of Dressing Leather: Soaking; Depilation; New Processes for the Depilation of Skins; Tanning; Cow Hides; Horse Hides; Goat Skins; Manufacture of Split Hides—On Various Methods of Tanning: Mechanical Methods; Physical Methods; Chemical Methods; Tanning with Extracts—Quantity and Quality; Quantity; Net Cost; Quality of Leather—Various Manipulations of Tanned Leather: Second Tanning; Grease Stains; Bleaching Leather; Waterproofing Leather; Weighting Tanned Leather; Preservation of Leather—Tanning Various Skins.

Part III., **Currying**—Waxed Calf: Preparation; Shaving; Stretching or Slicking; Oiling the Grain; Oiling the Flesh Side; Whitening and Graining; Waxing; Finishing; Dry Finishing; Finishing in Colour; Cost—White Calf: Finishing in White—Cow Hide for Upper Leathers: Black Cow Hide; White Cow Hide; Coloured Cow Hide—Smooth Cow Hide—Black Leather—Miscellaneous Hides: Horse; Goat; Waxed Goat Skin; Matt Goat Skin—Russia Leather: Russia Leather; Artificial Russia Leather.

Part IV., **Enamelled, Hungary and Chamoy Leather, Morocco, Parchment, Furs and Artificial Leather**—Enamelled Leather: Varnish Manufacture; Application of the Enamel; Enamelling in Colour—Hungary Leather: Preliminary; Wet Work or Preparation; Aluming; Dressing or Loft Work; Tallowing; Hungary Leather from Various Hides—Tawing: Preparatory Operations; Dressing; Dyeing Tawed Skins; Rugs—Chamoy Leather—Morocco: Preliminary Operations, Morocco Tanning: Mordants used in Morocco Manufacture; Natural Colours used in Morocco Dyeing; Artificial Colours; Different Methods of Dyeing; Dyeing with Natural Colours; Dyeing with Aniline Colours; Dyeing with Metallic Salts; Leather Printing; Finishing Morocco; Shagreen; Bronzed Leather—Gilding and Silvering: Gilding; Silvering; Nickel and Cobalt—Parchment—Furs and Furriery: Preliminary Remarks; Indigenous Furs; Foreign Furs from Hot Countries; Foreign Furs from Cold Countries; Furs from Birds' Skins; Preparation of Furs; Dressing; Colouring; Preparation of Birds' Skins; Preservation of Furs—Artificial Leather: Leather made from Scraps; Compressed Leather; American Cloth; Papier Mâché; Linoleum; Artificial Leather.

Part V., **Leather Testing and the Theory of Tanning**—Testing and Analysis of Leather: Physical Testing of Tanned Leather; Chemical Analysis—The Theory of Tanning and the other Operations of the Leather and Skin Industry: Theory of Soaking; Theory of Unhairing; Theory of Swelling; Theory of Handling; Theory of Tanning; Theory of the Action of Tannin on the Skin; Theory of Hungary Leather Making; Theory of Tawing; Theory of Chamoy Leather Making; Theory of Mineral Tanning.

Part VI., **Uses of Leather**—Machine Belts: Manufacture of Belting; Leather Chain Belts; Various Belts, Use of Belts—Boot and Shoe-making; Boots and Shoes; Laces—Saddlery: Composition of a Saddle; Construction of a Saddle—Harness: The Pack Saddle; Harness—Military Equipment—Glove Making—Carriage Building—Mechanical Uses.

Appendix, **The World's Commerce in Leather**—Europe; America; Asia; Africa; Australasia—Index.

THE LEATHER WORKER'S MANUAL. Being a Compendium of Practical Recipes and Working Formulæ for Curriers, Bootmakers, Leather Dressers, Blacking Manufacturers, Saddlers, Fancy Leather Workers. By H. C. STANDAGE. 165 pp. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Blackings, Polishes, Glosses, Dressings, Renovators, etc., for Boot and Shoe Leather—Harness Blackings, Dressings, Greases, Compositions, Soaps, and Boot-top Powders and Liquids, etc., etc.—Leather Grinders' Sundries—Currier's Seasonings, Blacking Compounds, Dressings, Finishes, Glosses, etc.—Dyes and Stains for Leather—Miscellaneous Information—Chrome Tannage—Index.

Books on Pottery, Bricks, Tiles, Glass, etc.

THE MANUAL OF PRACTICAL POTTING. Compiled by Experts, and Edited by CHAS. F. BINNS. Revised Third Edition and Enlarged. 200 pp. 1901. Price 17s. 6d.; India and Colonies, 18s. 6d.; Other Countries, 20s.; strictly net.

Contents.

Introduction. The Rise and Progress of the Potter's Art—**Bodies.** China and Porcelain Bodies, Parian Bodies, Semi-porcelain and Vitreous Bodies, Mortar Bodies, Earthenwares Granite and C.C. Bodies, Miscellaneous Bodies, Sagger and Crucible Clays, Coloured Bodies, Jasper Bodies, Coloured Bodies for Mosaic Painting, Encaustic Tile Bodies, Body Stains, Coloured Dips—**Glazes.** China Glazes, Ironstone Glazes, Earthenware Glazes, Glazes without Lead, Miscellaneous Glazes, Coloured Glazes, Majolica Colours—**Gold and Gold Colours.** Gold, Purple of Cassius, Marone and Ruby, Enamel Coloured Bases, Enamel Colour Fluxes, Enamel Colours, Mixed Enamel Colours, Antique and Vellum Enamel Colours, Underglaze Colours, Underglaze Colour Fluxes, Mixed Underglaze Colours, Flow Powders, Oils and Varnishes—**Means and Methods.** Reclamation of Waste Gold, The Use of Cobalt, Notes on Enamel Colours, Liquid or Bright Gold—**Classification and Analysis.** Classification of Clay Ware, Lord Playfair's Analysis of Clays, The Markets of the World, Time and Scale of Firing, Weights of Potter's Material, Decorated Goods Count—Comparative Loss of Weight of Clays—Ground Felspar Calculations—The Conversion of Slop Body Recipes into Dry Weight—The Cost of Prepared Earthenware Clay—**Forms and Tables.** Articles of Apprenticeship, Manufacturer's Guide to Stocktaking, Table of Relative Values of Potter's Materials, Hourly Wages Table, Workman's Settling Table, Comparative Guide for Earthenware and China Manufacturers in the use of Slop Flint and Slop Stone, Foreign Terms applied to Earthenware and China Goods, Table for the Conversion of Metrical Weights and Measures on the Continent and South America—**Index.**

CERAMIC TECHNOLOGY: Being some Aspects of Technical Science as Applied to Pottery Manufacture. Edited by CHARLES F. BINNS. 100 pp. Demy 8vo. 1897. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

Preface—The Chemistry of Pottery—Analysis and Synthesis—Clays and their Components—The Biscuit Oven—Pyrometry—Glazes and their Composition—Colours and Colour-making—Index.

A TREATISE ON THE CERAMIC INDUSTRIES. A

Complete Manual for Pottery, Tile and Brick Works. By EMILE BOURRY. Translated from the French by WILTON P. RIX, Examiner in Pottery and Porcelain to the City and Guilds of London Technical Institute, Pottery Instructor to the Hanley School Board. Royal 8vo. 1901. 760 pp. 323 Illustrations. Price 21s.; India and Colonies, 22s.; Other Countries, 23s. 6d.; strictly net.

Contents.

Part I., **General Pottery Methods.** Definition and History. Definitions and Classification of Ceramic Products—Historic Summary of the Ceramic Art—Raw Materials of Bodies. Clays: Pure Clay and Natural Clays—Various Raw Materials: Analogous to Clay—Agglomerative and Agglutinative—Opening—Fusible—Refractory—Trials of Raw Materials—Plastic Bodies. Properties and Composition—Preparation of Raw Materials: Disaggregation—Purification—Preparation of Bodies: By Plastic Method—By Dry Method—By Liquid Method—Formation. Processes of Formation: Throwing—Expression—Moulding by Hand, on the Jolley, by Compression, by Slip Casting—Slapping—Slipping—Drying. Drying of Bodies—Processes of Drying: By Evaporation—By Aeration—By Heating—By Ventilation—By Absorption—Glazes. Composition and Properties—Raw Materials—Manufacture and Application—Firing. Properties of the Bodies and Glazes during Firing—Description of the Kilns—Working of the Kilns—Decoration. Colouring Materials—Processes of Decoration.

Part II., **Special Pottery Methods.** Terra Cottas. Classification: Plain Ordinary, Hollow, Ornamental, Vitrified, and Light Bricks—Ordinary and Black Tiles—Paving Tiles—Pipes—Architectural Terra Cottas—Vases, Statues and Decorative Objects—Common Pottery—Pottery for Water and Filters—Tobacco Pipes—Lustre Ware—Properties and Tests for Terra Cottas—Fireclay Goods. Classification: Argillaceous, Aluminous, Carboniferous, Silicious and Basic Fireclay Goods—Fireclay Mortar (Pug)—Tests for Fireclay Goods—Faïences. Varnished Faïences—Enamelled Faïences—Silicious Faïences—Pipeclay Faïences—Pebble Work—Feldspathic Faïences—Composition, Processes of Manufacture and General Arrangements of Faïence Potteries—Stoneware. Stoneware Properly So-called: Paving Tiles—Pipes—Sanitary Ware—Stoneware for Food Purposes and Chemical Productions—Architectural Stoneware—Vases, Statues and other Decorative Objects—Fine Stoneware—Porcelain. Hard Porcelain for Table Ware and Decoration, for the Fire, for Electrical Conduits, for Mechanical Purposes: Architectural Porcelain, and Dull or Biscuit Porcelain—Soft Phosphated or English Porcelain—Soft Vitreous Porcelain, French and New Sèvres—Argillaceous Soft or Seger's Porcelain—Dull Soft or Parian Porcelain—Dull Feldspathic Soft Porcelain—**Index.**

ARCHITECTURAL POTTERY. Bricks, Tiles, Pipes, Enamelled Terra-cottas, Ordinary and Incrusted Quarries, Stoneware Mosaics, Faïences and Architectural Stoneware. By LEON LEFÈVRE. With Five Plates. 950 Illustrations in the Text, and numerous estimates. 500 pp., royal 8vo. 1900. Translated from the French by K. H. BIRD, M.A., and W. MOORE BINNS. Price 15s.; India and Colonies, 16s.; Other Countries, 17s. 6d.; strictly net.

Contents.

Part I. Plain Undecorated Pottery.—Clays, Bricks, Tiles, Pipes, Chimney Flues, Terra-cotta.

Part II. Made-up or Decorated Pottery.

THE ART OF RIVETING GLASS, CHINA AND EARTHENWARE. By J. HOWARTH. Second Edition. 1900. Paper Cover. Price 1s. net; by post, home or abroad, 1s. 1d.

HOW TO ANALYSE CLAY. Practical Methods for Practical Men. By HOLDEN M. ASHBY, Professor of Organic Chemistry, Harvey Medical College, U.S.A. 74 pp. Twenty Illus. 1901. Price 2s. 6d.; Abroad, 3s.; strictly net.

NOTES ON POTTERY CLAYS. Their Distribution, Properties, Uses and Analyses of Ball Clays, China Clays and China Stone. By JAS. FAIRIE, F.G.S. 1901. 132 pp. Crown 8vo. Price 3s. 6d.; India and Colonies, 4s.; Other Countries, 4s. 6d.; strictly net.

A Reissue of

THE HISTORY OF THE STAFFORDSHIRE POTTERIES; AND THE RISE AND PROGRESS OF THE MANUFACTURE OF POTTERY AND PORCELAIN.

With References to Genuine Specimens, and Notices of Eminent Pottery. By SIMON SHAW. (Originally Published in 1829.) 265 pp. 1900. Demy 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Introductory Chapter showing the position of the Pottery Trade at the present time (1899)—**Preliminary Remarks—The Potteries**, comprising Tunstall, Brownhills, Greenfield and New Field, Golden Hill, Latebrook, Green Lane, Burslem, Longport and Dale Hall, Hot Lane and Cobridge, Hanley and Shelton, Etruria, Stoke, Penkhull, Fenton, Lane Delph, Foley, Lane End—**On the Origin of the Art**, and its Practice among the early Nations—**Manufacture of Pottery**, prior to 1700—**The Introduction of Red Porcelain** by Messrs Elers, of Bradwell, 1690—**Progress of the Manufacture** from 1700 to Mr. Wedgwood's commencement in 1760—**Introduction of Fluid Glaze**—Extension of the Manufacture of Cream Colour—Mr. Wedgwood's Queen's Ware—Jasper, and Appointment of Potter to Her Majesty—**Black Printing—Introduction of Porcelain.** Mr. W. Littler's Porcelain—Mr Cookworthy's Discovery of Kaolin and Petuntse, and Patent—Sold to Mr. Champion—resold to the New Hall Com.—**Extension of Term—Blue Printed Pottery.** Mr. Turner, Mr Spode (1), Mr. Baddeley, Mr. Spode (2), Messrs. Turner, Mr. Wood, Mr. Wilson, Mr. Minton—**Great Change in Patterns of Blue Printed—Introduction of Lustre Pottery.** Improvements in Pottery and Porcelain subsequent to 1800.

A Reissue of

THE CHEMISTRY OF THE SEVERAL NATURAL AND ARTIFICIAL HETEROGENEOUS COMPOUNDS USED IN MANUFACTURING PORCELAIN, GLASS AND POTTERY. By SIMEON SHAW. (Originally published in 1837.) 750 pp. 1900. Royal 8vo. Price 14s.; India and Colonies, 15s.; Other Countries, 16s. 6d.; strictly net.

Contents.

PART I., ANALYSIS AND MATERIALS.—Introduction: Laboratory and Apparatus Elements—Temperature—Acids and Alkalies—The Earths—Metals.

PART II., SYNTHESIS AND COMPOUNDS.—Science of Mixing—Bodies: Porcelain—Hard, Porcelain—Fritted Bodies, Porcelain—Raw Bodies, Porcelain—Soft, Fritted Bodies, Raw Bodies, Stone Bodies, Ironstone, Dry Bodies, Chemical Utensils, Fritted Jasper, Fritted Pearl, Fritted Drab, Raw Chemical Utensils, Raw Stone, Raw Jasper, Raw Pearl, Raw Mortar, Raw Drab, Raw Brown, Raw Fawn, Raw Cane, Raw Red Porous, Raw Egyptian, Earthenware, Queen's Ware, Cream Colour, Blue and Fancy Printed, Dipped and Mocha, Chalky, Rings, Stilts, etc.—**Glazes:** Porcelain—Hard Fritted Porcelain—Soft Fritted Porcelain—Soft Raw, Cream Colour Porcelain, Blue Printed Porcelain, Fritted Glazes, Analysis of Fritt, Analysis of Glaze, Coloured Glazes, Dips, Smears and Washes; **Glasses:** Flint Glass, Coloured Glasses, Artificial Garnet, Artificial Emerald, Artificial Amethyst, Artificial Sapphire, Artificial Opal, Plate Glass, Crown Glass, Broad Glass, Bottle Glass, Phosphoric Glass, British Steel Glass, Glass-Staining and Painting, Engraving on Glass, Dr. Faraday's Experiments—**Colours:** Colour Making, Fluxes or Solvents, Components of the Colours; **Reds, etc., from Gold,** Carmine or Rose Colour, Purple, Reds, etc., from Iron, Blues, Yellows, Greens, Blacks, White, Silver for Burnishing, Gold for Burnishing, Printer's Oil, Lustres.

TABLES OF THE CHARACTERISTICS OF CHEMICAL SUBSTANCES.

Glassware, Glass Staining and Painting.

RECIPES FOR FLINT GLASS MAKING. By a British Glass Master and Mixer. Sixty Recipes. Being Leaves from the Mixing Book of several experts in the Flint Glass Trade, containing up-to-date recipes and valuable information as to Crystal, Demi-crystal and Coloured Glass in its many varieties. It contains the recipes for cheap metal suited to pressing, blowing, etc., as well as the most costly crystal and ruby. Crown 8vo. 1900. Price for United Kingdom, 10s. 6d.; Abroad, 15s.; United States, \$4; strictly net.

Contents.

Ruby—Ruby from Copper—Flint for using with the Ruby for Coating—A German Metal—Cornelian, or Alabaster—Sapphire Blue—Crysophis—Opal—Turquoise Blue—Gold Colour—Dark Green—Green (common)—Green for Malachite—Blue for Malachite—Black for Melachite—Black—Common Canary Batch—Canary—White Opaque Glass—Sealing-wax Red—Flint—Flint Glass (Crystal and Demi)—Achromatic Glass—Paste Glass—White Enamel—Firestone—Dead White (for moons)—White Agate—Canary—Canary Enamel—Index.

A TREATISE ON THE ART OF GLASS PAINTING.

Prefaced with a Review of Ancient Glass. By ERNEST R. SUFFLING. With One Coloured Plate and Thirty-seven Illustrations. Demy 8vo. 140 pp. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d. net.

Contents.

A Short History of Stained Glass—Designing Scale Drawings—Cartoons and the Cut Line—Various Kinds of Glass Cutting for Windows—The Colours and Brushes used in Glass Painting—Painting on Glass, Dispersed Patterns—Diapered Patterns—Aciding—Firing—Fret Lead Glazing—Index.

PAINTING ON GLASS AND PORCELAIN AND ENAMEL PAINTING.

A Complete Introduction to the Preparation of all the Colours and Fluxes used for Painting on Porcelain, Enamel, Faience and Stoneware, the Coloured Pastes and Coloured Glasses, together with a Minute Description of the Firing of Colours and Enamels. By FELIX HERMANN, Technical Chemist. With Eighteen Illustrations. 300 pp. Translated from the German second and enlarged Edition. 1897. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

History of Glass Painting—The Articles to be Painted: Glass, Porcelain, Enamel, Stoneware, Faience—Pigments: Metallic Pigments: Antimony Oxide, Naples Yellow, Barium Chromate, Lead Chromate, Silver Chloride, Chromic Oxide—Fluxes: Fluxes, Felspar, Quartz, Purifying Quartz, Sedimentation, Quenching, Borax, Boracic Acid, Potassium and Sodium Carbonates, Rocaille Flux—Preparation of the Colours for Glass Painting—The Colour Pastes—The Coloured Glasses—Composition of the Porcelain Colours—The Enamel Colours: Enamels for Artistic Work—Metallic Ornamentation: Porcelain Gilding, Glass-Gilding—Firing the Colours: Remarks on Firing: Firing Colours on Glass, Firing Colours on Porcelain; The Muffle—Accidents occasionally Supervening during the Process of Firing—Remarks on the Different Methods of Painting on Glass, Porcelain, etc.—Appendix: Cleaning Old Glass Paintings.

Paper Staining.

THE DYEING OF PAPER PULP. A Practical Treatise for the use of Papermakers, Paperstainers, Students and others. By JULIUS ERFURT, Manager of a Paper Mill. Translated into English and Edited with Additions by JULIUS HÜBNER, F.C.S., Lecturer on Papermaking at the Manchester Municipal Technical School. With Illustrations and **157 patterns of paper dyed in the pulp.** Royal 8vo, 180 pp. 1901. Price 15s.; India and Colonies, 16s.; Other Countries, 20s.; strictly net. Limited edition.

Contents.

Behaviour of the Paper Fibres during the Process of Dyeing, Theory of the Mordant—Colour Fixing Mediums (Mordants)—Influence of the Quality of the Water Used—Inorganic Colours—Organic Colours—Practical Application of the Coal Tar Colours according to their Properties and their Behaviour towards the Different Paper Fibres—Dyed Patterns on Various Pulp Mixtures—Dyeing to Shade—Index.

Enamelling on Metal.

ENAMELS AND ENAMELLING. For Enamel Makers, Workers in Gold and Silver, and Manufacturers of Objects of Art. By PAUL RANDAU. Translated from the German. With Sixteen Illustrations. Demy 8vo. 180 pp. 1900. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Composition and Properties of Glass—Raw Materials for the Manufacture of Enamels—Substances Added to Produce Opacity—Fluxes—Pigments—Decolorising Agents—Testing the Raw Materials with the Blow-pipe Flame—Subsidiary Materials—Preparing the Materials for Enamel Making—Mixing the Materials—The Preparation of Technical Enamels, The Enamel Mass—Appliances for Smelting the Enamel Mass—Smelting the Charge—Composition of Enamel Masses—Composition of Masses for Ground Enamels—Composition of Cover Enamels—Preparing the Articles for Enamelling—Applying the Enamel—Firing the Ground Enamel—Applying and Firing the Cover Enamel or Glaze—Repairing Defects in Enamelled Ware—Enamelling Articles of Sheet Metal—Decorating Enamelled Ware—Specialities in Enamelling—Dial-plate Enamelling—Enamels for Artistic Purposes, Recipes for Enamels of Various Colours—Index.

THE ART OF ENAMELLING ON METAL. By W.

NORMAN BROWN. Twenty-eight Illustrations. Crown 8vo. 60 pp. 1900. Price 2s. 6d.; Abroad, 3s.; strictly net.

Silk Manufacture.

SILK THROWING AND WASTE SILK SPINNING.

By HOLLINS RAYNER. Demy 8vo. 170 pp. 117 Illus. 1903. Price 5s.; Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

The Silkworm—Cocoon Reeling and Qualities of Silk—Silk Throwing—Silk Wastes—The Preparation of Silk Waste for Degumming—Silk Waste Degumming, Schapping and Discharging—The Opening and Dressing of Wastes—Silk Waste "Drawing" or "Preparing" Machinery—Long Spinning—Short Spinning—Spinning and Finishing Processes—Utilisation of Waste Products—Noil Spinning—Exhaust Noil Spinning.

Books on Textile and Dyeing Subjects.

THE CHEMICAL TECHNOLOGY OF TEXTILE

FIBRES: Their Origin, Structure, Preparation, Washing, Bleaching, Dyeing, Printing and Dressing. By Dr. GEORG VON GEORGIEVICS. Translated from the German by CHARLES SALTER. 320 pp. Forty-seven Illustrations. Royal 8vo. 1902. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s. net.

Contents.

The Textile Fibres—Washing, Bleaching, Carbonising—Mordants and Mordanting—Dyeing—Printing—Dressing and Finishing.

POWER-LOOM WEAVING AND YARN NUMBERING,

According to Various Systems, with Conversion Tables. Translated from the German of ANTHON GRUNER. **With Twenty-six Diagrams in Colours.** 150 pp. 1900. Crown 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Power-Loom Weaving in General. Various Systems of Looms—Mounting and Starting the Power-Loom. English Looms—Tappet or Treadle Looms—Dobbies—General Remarks on the Numbering, Reeling and Packing of Yarn—Appendix—Useful Hints. Calculating Warps—Weft Calculations—Calculations of Cost Price in Hanks.

TEXTILE RAW MATERIALS AND THEIR CONVERSION INTO YARNS.

(The Study of the Raw Materials and the Technology of the Spinning Process.) By JULIUS ZIPSER. Translated from German by CHARLES SALTER. 302 Illustrations. 500 pp. Demy 8vo. 1901. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

PART I.—The Raw Materials Used in the Textile Industry.

MINERAL RAW MATERIALS. VEGETABLE RAW MATERIALS. ANIMAL RAW MATERIALS.

PART II.—The Technology of Spinning or the Conversion of Textile Raw Materials into Yarn.

SPINNING VEGETABLE RAW MATERIALS. Cotton Spinning—Installation of a Cotton Mill—Spinning Waste Cotton and Waste Cotton Yarns—Flax Spinning—Fine Spinning—Tow Spinning—Hemp Spinning—Spinning Hemp Tow String—Jute Spinning—Spinning Jute Line Yarn—Utilising Jute Waste.

PART III.—Spinning Animal Raw Materials.

Spinning Carded Woollen Yarn—Finishing Yarn—Worsted Spinning—Finishing Worsted Yarn—Artificial Wool or Shoddy Spinning—Shoddy and Mungo Manufacture—Spinning Shoddy and other Wool Substitutes—Spinning Waste Silk—Chappe Silk—Fine Spinning—Index.

THE TECHNICAL TESTING OF YARNS AND TEXTILE FABRICS. With Reference to Official Specifications. Translated from the German of Dr. J. HERZFELD. Second Edition. Sixty-nine Illustrations. 200 pp. Demy 8vo. 1902. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Yarn Testing. Determining the Yarn Number—Testing the Length of Yarns—Examination of the External Appearance of Yarn—Determining the Twist of Yarn and Twist—Determination of Tensile Strength and Elasticity—Estimating the Percentage of Fat in Yarn—Determination of Moisture (Conditioning)—Appendix.

DECORATIVE AND FANCY TEXTILE FABRICS.

By R. T. LORD. Manufacturers and Designers of Carpets, Damask Dress and all Textile Fabrics. 200 pp. 1898. Demy 8vo. 132 Designs and Illustrations. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

A Few Hints on Designing Ornamental Textile Fabrics—A Few Hints on Designing Ornamental Textile Fabrics (continued)—A Few Hints on Designing Ornamental Textile Fabrics (continued)—Hints for Ruled-paper Draughtsmen—The Jacquard Machine—Brussels and Wilton Carpets—Tapestry Carpets—Ingrain Carpets—Axminster Carpets—Damask and Tapestry Fabrics—Scarf Silks and Ribbons—Silk Handkerchiefs—Dress Fabrics—Mantle Cloths—Figured Plush—Bed Quilts—Calico Printing.

THEORY AND PRACTICE OF DAMASK WEAVING.

By H. KINZER and K. WALTER. Royal 8vo. Eighteen Folding Plates. Six Illustrations. Translated from the German. 110 pp. 1903. Price 8s. 6d.; Colonies, 9s.; Other Countries, 9s. 6d.; strictly net.

Contents.

The Various Sorts of Damask Fabrics—Drill (Ticking, Handloom-made)—Whole Damask for Tablecloths—Damask with Ground- and Connecting-warp Threads—Furniture Damask—Lampas or Hangings—Church Damasks—The Manufacture of Whole Damask—Damask Arrangement with and without Cross-Shedding—The Altered Cone-arrangement—The Principle of the Corner Lifting Cord—The Roller Principle—The Combination of the Jacquard with the so-called Damask Machine—The Special Damask Machine—The Combination of Two Tyings.

FAULTS IN THE MANUFACTURE OF WOOLLEN GOODS AND THEIR PREVENTION. By NICOLAS REISER.

Translated from the Second German Edition. Crown 8vo. Sixty-three Illustrations. 170 pp. 1903. Price 5s.; Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Improperly Chosen Raw Material or Improper Mixtures—Wrong Treatment of the Material in Washing, Carbonisation, Drying, Dyeing and Spinning—Improper Spacing of the Goods in the Loom—Wrong Placing of Colours—Wrong Weight or Width of the Goods—Breaking of Warp and Weft Threads—Presence of Doubles, Singles, Thick, Loose, and too Hard Twisted Threads as well as Tangles, Thick Knots and the Like—Errors in Cross-weaving—Inequalities, *i.e.*, Bands and Stripes—Dirty Borders—Defective Selvedges—Holes and Buttons—Rubbed Places—Creases—Spots—Loose and Bad Colours—Badly Dyed Selvedges—Hard Goods—Brittle Goods—Uneven Goods—Removal of Bands, Stripes, Creases and Spots.

SPINNING AND WEAVING CALCULATIONS, especially

relating to Woollens. From the German of N. REISER. Thirty-four Illustrations. Tables. 170 pp. Demy 8vo. 1904. Price 10s. 6d. India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Calculating the Raw Material—Proportion of Different Grades of Wool to Furnish a Mixture at a Given Price—Quantity to Produce a Given Length—Yarn Calculations—Yarn Number—Working Calculations—Calculating the Reed Count—Cost of Weaving, etc.

WATERPROOFING OF FABRICS. By Dr. S. MIERZINSKI.
Crown 8vo. 104 pp. 29 Illus. 1903. Price 5s.; Colonies, 5s. 6d.;
Other Countries, 6s.; strictly net.

Contents.

Introduction—Preliminary Treatment of the Fabric—Waterproofing with Acetate of Alumina—Impregnation of the Fabric—Drying—Waterproofing with Paraffin—Waterproofing with Ammonium Cuprate—Waterproofing with Metallic Oxides—Coloured Waterproof Fabrics—Waterproofing with Gelatine, Tannin, Caseinate of Lime and other Bodies—Manufacture of Tarpaulin—British Waterproofing Patents—Index.

HOW TO MAKE A WOOLLEN MILL PAY. By JOHN MACKIE. Crown 8vo. 76 pp. 1904. Price 3s. 6d.; Colonies, 4s.; Other Countries, 4s. 6d.; net.

Contents.

Blends, Piles, or Mixtures of Clean Scoured Wools—Dyed Wool Book—The Order Book—Pattern Duplicate Books—Management and Oversight—Constant Inspection of Mill Departments—Importance of Delivering Goods to Time, Shade, Strength, etc.—Plums.
(For "Textile Soaps" see p. 7.)

Dyeing, Colour Printing, Matching and Dye-stuffs.

THE COLOUR PRINTING OF CARPET YARNS. Manual for Colour Chemists and Textile Printers. By DAVID PATERSON, F.C.S. Seventeen Illustrations. 136 pp. Demy 8vo. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Structure and Constitution of Wool Fibre—Yarn Scouring—Scouring Materials—Water for Scouring—Bleaching Carpet Yarns—Colour Making for Yarn Printing—Colour Printing Pastes—Colour Recipes for Yarn Printing—Science of Colour Mixing—Matching of Colours—"Hank" Printing—Printing Tapestry Carpet Yarns—Yarn Printing—Steaming Printed Yarns—Washing of Steamed Yarns—Aniline Colours Suitable for Yarn Printing—Glossary of Dyes and Dye-wares used in Wood Yarn Printing—Appendix.

THE SCIENCE OF COLOUR MIXING. A Manual intended for the use of Dyers, Calico Printers and Colour Chemists. By DAVID PATERSON, F.C.S. Forty-one Illustrations, **Five Coloured Plates, and Four Plates showing Eleven Dyed Specimens of Fabrics.** 132 pp. Demy 8vo. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Colour a Sensation; Colours of Illuminated Bodies; Colours of Opaque and Transparent Bodies; Surface Colour—Analysis of Light; Spectrum; Homogeneous Colours; Ready Method of Obtaining a Spectrum—Examination of Solar Spectrum; The Spectroscope and Its Construction; Colourists' Use of the Spectroscope—Colour by Absorption; Solutions and Dyed Fabrics; Dichroic Coloured Fabrics in Gaslight—Colour Primaries of the Scientist *versus* the Dyer and Artist; Colour Mixing by Rotation and Lye Dyeing; Hue, Purity, Brightness; Tints; Shades, Scales, Tones, Sad and Sombre Colours—Colour Mixing; Pure and Impure Greens, Orange and Violets; Large Variety of Shades from few Colours; Consideration of the Practical Primaries: Red, Yellow and Blue—Secondary Colours; Nomenclature of Violet and Purple Group; Tints and Shades of Violet; Changes in Artificial Light—Tertiary Shades; Broken Hues; Absorption Spectra of Tertiary Shades—Appendix: Four Plates with Dyed Specimens Illustrating Text—Index.

DYERS' MATERIALS: An Introduction to the Examination, Evaluation and Application of the most important Substances used in Dyeing, Printing, Bleaching and Finishing. By PAUL HEERMAN, Ph.D. Translated from the German by A. C. WRIGHT, M.A. (Oxon.), B.Sc. (Lond.). Twenty-four Illustrations. Crown 8vo. 150 pp. 1901. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

COLOUR MATCHING ON TEXTILES. A Manual intended for the use of Students of Colour Chemistry, Dyeing and Textile Printing. By DAVID PATERSON, F.C.S. Coloured Frontispiece. Twenty-nine Illustrations and **Fourteen Specimens of Dyed Fabrics.** Demy 8vo. 132 pp. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Colour Vision and Structure of the Eye—Perception of Colour—Primary and Complementary Colour Sensations—Daylight for Colour Matching—Selection of a Good Pure Light—Diffused Daylight, Direct Sunlight, Blue Skylight, Variability of Daylight, etc., etc.—Matching of Hues—Purity and Luminosity of Colours—Matching Bright Hues—Aid of Tinted Films—Matching Difficulties Arising from Contrast—Examination of Colours by Reflected and Transmitted Lights—Effect of Lustre and Transparency of Fibres in Colour Matching—Matching of Colours on Velvet Pile—Optical Properties of Dye-stuffs. Dichroism, Fluorescence—Use of Tinted Mediums—Orange Film—Defects of the Eye—Yellowing of the Lens—Colour Blindness, etc.—Matching of Dyed Silk Trimmings and Linings and Bindings—Its Difficulties—Behaviour of Shades in Artificial Light—Colour Matching of Old Fabrics, etc.—Examination of Dyed Colours under the Artificial Lights—Electric Arc, Magnesium and Dufton, Gardner Lights, Welsbach, Acetylene, etc.—Testing Qualities of an Illuminant—Influence of the Absorption Spectrum in Changes of Hue under the Artificial Lights—Study of the Causes of Abnormal Modifications of Hue, etc.

COLOUR: A HANDBOOK OF THE THEORY OF COLOUR. By GEORGE H. HURST, F.C.S. **With Ten Coloured Plates** and Seventy-two Illustrations. 160 pp. Demy 8vo. 1900. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Colour and Its Production—Cause of Colour in Coloured Bodies—Colour Phenomena and Theories—The Physiology of Light—Contrast—Colour in Decoration and Design—Measurement of Colour.

Reissue of

THE ART OF DYEING WOOL, SILK AND COTTON.

Translated from the French of M. HELLOT, M. MACQUER and M. LE PILEUR D'APLIGNY. First Published in English in 1789. Six Plates. Demy 8vo. 446 pp. 1901. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Part I., The Art of Dyeing Wool and Woollen Cloth, Stuffs, Yarn, Worsted, etc. Part II., The Art of Dyeing Silk. Part III., The Art of Dyeing Cotton and Linen Thread, together with the Method of Stamping Silks, Cottons, etc.

THE CHEMISTRY OF DYE-STUFFS. By Dr. GEORG VON GEORGIEVICS. Translated from the Second German Edition. 412 pp. Demy 8vo. 1903. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Introduction—Coal Tar—Intermediate Products in the Manufacture of Dye-stuffs—The Artificial Dye-stuffs (Coal-tar Dyes)—Nitroso Dye-stuffs—Nitro Dye-stuffs—Azo Dye-stuffs—Substantive Cotton Dye-stuffs—Azoxystilbene Dye-stuffs—Hydrazones—Ketoneimides—Triphenylmethane Dye-stuffs—Rosolic Acid Dye-stuffs—Xanthene Dye-stuffs—Xanthone Dye-stuffs—Flavones—Oxyketone Dye-stuffs—Quinoline and Acridine Dye-stuffs—Quinonimide or Diphenylamine Dye-stuffs—The Azine Group: Eurhodines, Safranines and Indulines—Eurhodines—Safranines—Quinoxalines—Indigo—Dye-stuffs of Unknown Constitution—Sulphur or Sulphine Dye-stuffs—Development of the Artificial Dye-stuff Industry—The Natural Dye-stuffs—Mineral Colours—Index.

THE DYEING OF COTTON FABRICS: A Practical Handbook for the Dyer and Student. By FRANKLIN BEECH, Practical Colourist and Chemist. 272 pp. Forty-four Illustrations of Bleaching and Dyeing Machinery. Demy 8vo. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Structure and Chemistry of the Cotton Fibre—Scouring and Bleaching of Cotton—Dyeing Machinery and Dyeing Manipulations—Principles and Practice of Cotton Dyeing—Direct Dyeing; Direct Dyeing followed by Fixation with Metallic Salts: Direct Dyeing followed by Fixation with Developers; Direct Dyeing followed by Fixation with Couplers; Dyeing on Tannic Mordant; Dyeing on Metallic Mordant; Production of Colour Direct upon Cotton Fibres; Dyeing Cotton by Impregnation with Dye-stuff Solution—Dyeing Union (Mixed Cotton and Wool) Fabrics—Dyeing Half Silk (Cotton-Silk, Satin) Fabrics—Operations following Dyeing—Washing, Soaping, Drying—Testing of the Colour of Dyed Fabrics—Experimental Dyeing and Comparative Dye Testing—Index.

The book contains numerous recipes for the production on Cotton Fabrics of all kinds of a great range of colours.

THE DYEING OF WOOLLEN FABRICS. By FRANKLIN BEECH, Practical Colourist and Chemist. Thirty-three Illustrations. Demy 8vo. 228 pp. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d. net.

Contents.

The Wool Fibre—Structure, Composition and Properties—Processes Preparatory to Dyeing—Scouring and Bleaching of Wool—Dyeing Machinery and Dyeing Manipulations—Loose Wool Dyeing, Yarn Dyeing and Piece Dyeing Machinery—The Principles and Practice of Wool Dyeing—Properties of Wool Dyeing—Methods of Wool Dyeing—Groups of Dyes—Dyeing with the Direct Dyes—Dyeing with Basic Dyes—Dyeing with Acid Dyes—Dyeing with Mordant Dyes—Level Dyeing—Blacks on Wool—Reds on Wool—Mordanting of Wool—Orange Shades on Wool—Yellow Shades on Wool—Green Shades on Wool—Blue Shades on Wool—Violet Shades on Wool—Brown Shades on Wool—Mode Colours on Wool—Dyeing Union (Mixed Cotton Wool) Fabrics—Dyeing of Gloria—Operations following Dyeing—Washing, Soaping, Drying—Experimental Dyeing and Comparative Dye Testing—Testing of the Colour of Dyed Fabrics—Index.

Bleaching and Washing.

A PRACTICAL TREATISE ON THE BLEACHING OF LINEN AND COTTON YARN AND FABRICS. By L. TAILFER, Chemical and Mechanical Engineer. Translated from the French by JOHN GEDDES McINTOSH. Demy 8vo. 303 pp. Twenty Illusts. 1901. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

General Considerations on Bleaching—Steeping—Washing: Its End and Importance—Roller Washing Machines—Wash Wheel (Dash Wheel)—Stocks or Wash Mill—Squeezing—Lye Boiling—Lye Boiling with Milk of Lime—Lye Boiling with Soda Lyes—Description of Lye Boiling Keirs—Operations of Lye Boiling—Concentration of Lyes—Mather and Platt's Keir—Description of the Keir—Saturation of the Fabrics—Alkali used in Lye Boiling—Examples of Processes—Soap—Action of Soap in Bleaching—Quality and Quantity of Soaps to use in the Lye—Soap Lyes or Scalds—Soap Scouring Stocks—Bleaching on Grass or on the Bleaching Green or Lawn—Chemicking—Remarks on Chlorides and their Decolourising Action—Chemicking Cisterns—Chemicking—Strengths, etc.—Sours—Properties of the Acids—Effects Produced by Acids—Souring Cisterns—Drying—Drying by Steam—Drying by Hot Air—Drying by Air—Damages to Fabrics in Bleaching—Yarn Mildew—Fermentation—Iron Rust Spots—Spots from Contact with Wood—Spots incurred on the Bleaching Green—Damages arising from the Machines—Examples of Methods used in Bleaching—Linen—Cotton—The Valuation of Caustic and Carbonated Alkali (Soda) and General Information Regarding these Bodies—Object of Alkalimetry—Titration of Carbonate of Soda—Comparative Table of Different Degrees of Alkalimetric Strength—Five Problems relative to Carbonate of Soda—Caustic Soda, its Properties and Uses—Mixtures of Carbonated and Caustic Alkali—Note on a Process of Manufacturing Caustic Soda and Mixtures of Caustic

and Carbonated Alkali (Soda)—Chlorometry—Titration—Wagner's Chlorometric Method—Preparation of Standard Solutions—Apparatus for Chlorine Valuation—Alkali in Excess in Decolourising Chlorides—Chlorine and Decolourising Chlorides—Synopsis—Chlorine—Chloride of Lime—Hypochlorite of Soda—Brochoki's Chlorozone—Various Decolourising Hypochlorites—Comparison of Chloride of Lime and Hypochlorite of Soda—Water—Qualities of Water—Hardness—Dervaux's Purifier—Testing the Purified Water—Different Plant for Purification—Filters—Bleaching of Yarn—Weight of Yarn—Lye Boiling—Chemicking—Washing—Bleaching of Cotton Yarn—The Installation of a Bleach Works—Water Supply—Steam Boilers—Steam Distribution Pipes—Engines—Keirs—Washing—Machines—Stocks—Wash Wheels—Chemicking and Souring Cisterns—Various—Buildings—Addenda—Energy of Decolourising Chlorides and Bleaching by Electricity and Ozone—Energy of Decolourising Chlorides—Chlorides—Production of Chlorine and Hypochlorites by Electrolysis—Lunge's Process for increasing the intensity of the Bleaching Power of Chloride of Lime—Trilfer's Process for Removing the Excess of Lime or Soda from Decolourising Chlorides—Bleaching by Ozone.

Cotton Spinning and Combing.

COTTON SPINNING (First Year). By THOMAS THORNLEY, Spinning Master, Bolton Technical School. 160 pp. Eighty-four Illustrations. Crown 8vo. 1901. Price 3s.; Abroad, 3s. 6d.; strictly net.

Contents.

Syllabus and Examination Papers of the City and Guilds of London Institute—Cultivation, Classification, Ginning, Baling and Mixing of the Raw Cotton—Bale-Breakers, Mixing Lattices and Hopper Feeders—Opening and Scutching—Carding—Indexes.

COTTON SPINNING (Intermediate, or Second Year). By THOMAS THORNLEY. 180 pp. Seventy Illustrations. Crown 8vo. 1901. Price 5s.; India and British Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Syllabuses and Examination Papers of the City and Guilds of London Institute—The Combing Process—The Drawing Frame—Bobbin and Fly Frames—Mule Spinning—Ring Spinning—General Indexes.

COTTON SPINNING (Honours, or Third Year). By THOMAS THORNLEY. 216 pp. Seventy-four Illustrations. Crown 8vo. 1901. Price 5s.; India and British Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Syllabuses and Examination Papers of the City and Guilds of London Institute—Cotton—The Practical Manipulation of Cotton Spinning Machinery—Doubling and Winding—Reeling—Warping—Production and Costs—Main Driving—Arrangement of Machinery and Mill Planning—Waste and Waste Spinning—Indexes.

COTTON COMBING MACHINES. By THOS. THORNLEY, Spinning Master, Technical School, Bolton. Demy 8vo. 117 Illustrations. 300 pp. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d. net.

Contents.

The Sliver Lap Machine and the Ribbon Cap Machine—General Description of the Heilmann Comber—The Cam Shaft—On the Detaching and Attaching Mechanism of the Comber—Resetting of Combers—The Erection of a Heilmann Comber—Stop Motions; Various Calculations—Various Notes and Discussions—Cotton Combing Machines of Continental Make—Index.

Collieries and Mines.

RECOVERY WORK AFTER PIT FIRES. By ROBERT

LAMPRECHT, Mining Engineer and Manager. Translated from the German. Illustrated by Six large Plates, containing Seventy-six Illustrations. 175 pp., demy 8vo. 1901. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

Causes of Pit Fires—Preventive Regulations: (1) The Outbreak and Rapid Extension of a Shaft Fire can be most reliably prevented by Employing little or no Combustible Material in the Construction of the Shaft; (2) Precautions for Rapidly Localising an Outbreak of Fire in the Shaft; (3) Precautions to be Adopted in case those under 1 and 2 Fail or Prove Inefficient. Precautions against Spontaneous Ignition of Coal. Precautions for Preventing Explosions of Fire-damp and Coal Dust. Employment of Electricity in Mining, particularly in Fiery Pits. Experiments on the Ignition of Fire-damp Mixtures and Clouds of Coal Dust by Electricity—**Indications of an Existing or Incipient Fire—Appliances for Working in Irrespirable Gases:** Respiratory Apparatus; Apparatus with Air Supply Pipes; Reservoir Apparatus; Oxygen Apparatus—**Extinguishing Pit Fires:** (a) Chemical Means; (b) Extinction with Water. Dragging down the Burning Masses and Packing with Clay; (c) Insulating the Seat of the Fire by Dams. Dam Building. Analyses of Fire Gases. Isolating the Seat of a Fire with Dams; Working in Irrespirable Gases ("Gas-diving"); Air-Lock Work. Complete Isolation of the Pit. Flooding a Burning Section isolated by means of Dams. Wooden Dams; Masonry Dams. Examples of Cylindrical and Dome-shaped Dams. Dam Doors: Flooding the Whole Pit—**Rescue Stations:** (a) Stations above Ground; (b) Underground Rescue Stations—**Spontaneous Ignition of Coal in Bulk—Index.**

VENTILATION IN MINES. By ROBERT WABNER, Mining

Engineer. Translated from the German. Royal 8vo. Thirty Plates and Twenty-two Illustrations. 240 pp. 1903. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; strictly net.

Contents.

The Causes of the Contamination of Pit Air—The Means of Preventing the Dangers resulting from the Contamination of Pit Air—Calculating the Volume of Ventilating Current necessary to free Pit Air from Contamination—Determination of the Resistance Opposed to the Passage of Air through the Pit—Laws of Resistance and Formulae therefor—Fluctuations in the Temperament or Specific Resistance of a Pit—Means for Providing a Ventilating Current in the Pit—Mechanical Ventilation—Ventilators and Fans—Determining the Theoretical, Initial, and True (Effective) Depression of the Centrifugal Fan—New Types of Centrifugal Fan of Small Diameter and High Working Speed—Utilising the Ventilating Current to the utmost Advantage and distributing the same through the Workings—Artificially retarding the Ventilating Current—Ventilating Preliminary Workings—Blind Headings—Separate Ventilation—Supervision of Ventilation—INDEX.

HAULAGE AND WINDING APPLIANCES USED IN

MINES. By CARL VOLK. Translated from the German. Royal 8vo. With Six Plates and 148 Illustrations. 150 pp. 1903. Price 8s. 6d.; Colonies, 9s.; Other Countries, 9s. 6d.; strictly net.

Contents.

Haulage Appliances—Ropes—Haulage Tubs and Tracks—Cages and Winding Appliances—Winding Engines for Vertical Shafts—Winding without Ropes—Haulage in Levels and Inclines—The Working of Underground Engines—Machinery for Downhill Haulage.

Dental Metallurgy.

DENTAL METALLURGY: MANUAL FOR STUDENTS

AND DENTISTS. By A. B. GRIFFITHS, Ph.D. Demy 8vo. Thirty-six Illustrations. 1903. 200 pp. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Introduction—Physical Properties of the Metals—Action of Certain Agents on Metals—Alloys—Action of Oral Bacteria on Alloys—Theory and Varieties of Blowpipes—Fluxes—Furnaces and Appliances—Heat and Temperature—Gold—Mercury—Silver—Iron—Copper—Zinc—Magnesium—Cadmium—Tin—Lead—Aluminium—Antimony—Bismuth—Palladium—Platinum—Iridium—Nickel—Practical Work—Weights and Measures.

Engineering, Smoke Prevention and Metallurgy.

THE PREVENTION OF SMOKE. Combined with the Economical Combustion of Fuel. By W. C. POPPLEWELL, M.Sc., A.M.Inst., C.E., Consulting Engineer. Forty-six Illustrations. 190 pp. 1901. Demy 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Fuel and Combustion—Hand Firing in Boiler Furnaces—Stoking by Mechanical Means—Powdered Fuel—Gaseous Fuel—Efficiency and Smoke Tests of Boilers—Some Standard Smoke Trials—The Legal Aspect of the Smoke Question—The Best Means to be adopted for the Prevention of Smoke—Index.

GAS AND COAL DUST FIRING. A Critical Review of the Various Appliances Patented in Germany for this purpose since 1885. By ALBERT PÜTSCH. 130 pp. Demy 8vo. 1901. Translated from the German. With 103 Illustrations. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Generators—Generators Employing Steam—Stirring and Feed Regulating Appliances—Direct Generators—Burners—Regenerators and Recuperators—Glass Smelting Furnaces—Metallurgical Furnaces—Pottery Furnace—Coal Dust Firing—Index.

THE HARDENING AND TEMPERING OF STEEL IN THEORY AND PRACTICE. By FRIDOLIN REISER. Translated from the German of the Third Edition. Crown 8vo. 120 pp. 1903. Price 5s.; India and British Colonies, 5s. 6d.; Other Countries, 6s.; strictly net.

Contents.

Steel—Chemical and Physical Properties of Steel, and their Casual Connection—Classification of Steel according to Use—Testing the Quality of Steel—Steel-Hardening—Investigation of the Causes of Failure in Hardening—Regeneration of Steel Spoilt in the Furnace—Welding Steel—Index.

SIDEROLGY: THE SCIENCE OF IRON (The Constitution of Iron Alloys and Slags). Translated from German of HANNS FREIHERR V. JÜPTNER. 350 pp. Demy 8vo. Eleven Plates and Ten Illustrations. 1902. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; net.

Contents.

The Theory of Solution.—Solutions—Molten Alloys—Varieties of Solutions—Osmotic Pressure—Relation between Osmotic Pressure and other Properties of Solutions—Osmotic Pressure and Molecular Weight of the Dissolved Substance—Solutions of Gases—Solid Solutions—Solubility—Diffusion—Electrical Conductivity—Constitution of Electrolytes and Metals—Thermal Expansion. **Micrography.**—Microstructure—The Micrographic Constituents of Iron—Relation between Micrographical Composition, Carbon-Content, and Thermal Treatment of Iron Alloys—The Microstructure of Slags. **Chemical Composition of the Alloys of Iron.**—Constituents of Iron Alloys—Carbon—Constituents of the Iron Alloys, Carbon—Opinions and Researches on Combined Carbon—Opinions and Researches on Combined Carbon—Applying the Curves of Solution deduced from the Curves of Recalescence to the Determination of the Chemical Composition of the Carbon present in Iron Alloys—The Constituents of Iron—Iron—The Constituents of Iron Alloys—Manganese—Remaining Constituents of Iron Alloys—A Silicon—Gases. **The Chemical Composition of Slag.**—Silicate Slags—Calculating the Composition of Silicate Slags—Phosphate Slags—Oxide Slags—Appendix—Index.

EVAPORATING, CONDENSING AND COOLING APPARATUS.

Explanations, Formulæ and Tables for Use in Practice. By E. HAUSBRAND, Engineer. Translated by A. C. WRIGHT, M.A. (Oxon.), B.Sc. (Lond.). With Twenty-one Illustrations and Seventy-six Tables. 400 pp. Demy 8vo. 1903. Price 10s. 6d.; India and Colonies, 11s.; Other Countries, 12s.; net.

Contents.

ReCoefficient of Transmission of Heat, k , and the Mean Temperature Difference, θ_m —Parallel and Opposite Currents—Apparatus for Heating with Direct Fire—The Injection of Saturated Steam—Superheated Steam—Evaporation by Means of Hot Liquids—The Transference of Heat in General, and Transference by means of Saturated Steam in Particular—The Transference of Heat from Saturated Steam in Pipes (Coils) and Double Bottoms—Evaporation in a Vacuum—The Multiple-effect Evaporator—Multiple-effect Evaporators from which Extra Steam is Taken—The Weight of Water which must be Evaporated from 100 Kilos. of Liquor in order its Original Percentage of Dry Materials from 1-25 per cent. up to 20-70 per cent.—The Relative Proportion of the Heating Surfaces in the Elements of the Multiple Evaporator and their Actual Dimensions—The Pressure Exerted by Currents of Steam and Gas upon Floating Drops of Water—The Motion of Floating Drops of Water upon which Press Currents of Steam—The Splashing of Evaporating Liquids—The Diameter of Pipes for Steam, Alcohol, Vapour and Air—The Diameter of Water Pipes—The Loss of Heat from Apparatus and Pipes to the Surrounding Air, and Means for Preventing the Loss—Condensers—Heating Liquids by Means of Steam—The Cooling of Liquids—The Volumes to be Exhausted from Condensers by the Air-pumps—A Few Remarks on Air-pumps and the Vacua they Produce—The Volumetric Efficiency of Air-pumps—The Volumes of Air which must be Exhausted from a Vessel in order to Reduce its Original Pressure to a Certain Lower Pressure—Index.

Plumbing, Decorating, Metal Work, etc., etc.

EXTERNAL PLUMBING WORK. A Treatise on Lead Work for Roofs. By JOHN W. HART, R.P.C. 180 Illustrations. 272 pp. Demy 8vo. Second Edition Revised. 1902. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Cast Sheet Lead—Milled Sheet Lead—Roof Cesspools—Socket Pipes—Drips—Gutters—Gutters (continued)—Breaks—Circular Breaks—Flats—Flats (continued)—Rolls on Flats—Roll Ends—Roll Intersections—Seam Rolls—Seam Rolls (continued)—Tack Fixings—Step Flashings—Step Flashings (continued)—Secret Gutters—Soakers—Hip and Valley Soakers—Dormer Windows—Dormer Windows (continued)—Dormer Tops—Internal Dormers—Skylights—Hips and Ridging—Hips and Ridging (continued)—Fixings for Hips and Ridging—Ornamental Ridging—Ornamental Curb Rolls—Curb Rolls—Cornices—Towers and Finials—Towers and Finials (continued)—Towers and Finials (continued)—Domes—Domes (continued)—Ornamental Lead Work—Rain Water Heads—Rain Water Heads (continued)—Rain Water Heads (continued).

HINTS TO PLUMBERS ON JOINT WIPING, PIPE BENDING AND LEAD BURNING.

Third Edition, Revised and Corrected. By JOHN W. HART, R.P.C. 184 Illustrations. 313 pp. Demy 8vo. 1901. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Pipe Bending—Pipe Bending (continued)—Pipe Bending (continued)—Square Pipe Bendings—Half-circular Elbows—Curved Bends on Square Pipe—Bossed Bends—Curved Plinth Bends—Rain-water Shoes on Square Pipe—Curved and Angle Bends—Square Pipe Fixings—Joint-wiping—Substitutes for Wiped Joints—Preparing Wiped Joints—Joint Fixings—Plumbing Irons—Joint Fixings—Use of "Touch" in Soldering—Underhand Joints—Blown and Copper Bit Joints—Branch Joints—Branch Joints (continued)—Block Joints—Block Joints (continued)—Block Fixings—Astragal Joints—Pipe Fixings—Large Branch Joints—Large Underhand Joints—Solders—Autogenous Soldering or Lead Burning—Index.

WORKSHOP WRINKLES for Decorators, Painters, Paper-hangers and Others. By W. N. BROWN. Crown 8vo. 128 pp. 1901. Price 2s. 6d.; Abroad, 3s.; strictly net.

SANITARY PLUMBING AND DRAINAGE. By JOHN W. HART. Demy 8vo. With 208 Illustrations. 250 pp. 1904. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Sanitary Surveys—Drain Testing—Drain Testing with Smoke—Testing Drains with Water—Drain Plugs for Testing—Sanitary Defects—Closets—Baths and Lavatories—House Drains—Manholes—Iron Soil Pipes—Lead Soil Pipes—Ventilating Pipes—Water-closets—Flushing Cisterns—Baths—Bath Fittings—Lavatories—Lavatory Fittings—Sinks—Waste Pipes—Water Supply—Ball Valves—Town House Sanitary Arrangements—Drainage—Joining Pipes—Accessible Drains—Iron Drains—Iron Junctions—Index.

THE PRINCIPLES AND PRACTICE OF DIPPING, BURNISHING, LACQUERING AND BRONZING BRASS WARE. By W. NORMAN BROWN. 35 pp. Crown 8vo. 1900. Price 2s.; Abroad, 2s. 6d.; strictly net.

HOUSE DECORATING AND PAINTING. By W. NORMAN BROWN. Eighty-eight Illustrations. 150 pp. Crown 8vo. 1900. Price 3s. 6d.; India and Colonies, 4s.; Other Countries, 4s. 6d.; strictly net.

A HISTORY OF DECORATIVE ART. By W. NORMAN BROWN. Thirty-nine Illustrations. 96 pp. Crown 8vo. 1900. Price 2s. 6d.; Abroad, 3s.; strictly net.

A HANDBOOK ON JAPANING AND ENAMELLING FOR CYCLES, BEDSTEADS, TINWARE, ETC. By WILLIAM NORMAN BROWN. 52 pp. and Illustrations. Crown 8vo. 1901. Price 2s.; Abroad, 2s. 6d.; net.

THE PRINCIPLES OF HOT WATER SUPPLY. By JOHN W. HART, R.P.C. With 129 Illustrations. 1900. 177 pp., demy 8vo. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net.

Contents.

Water Circulation—The Tank System—Pipes and Joints—The Cylinder System—Boilers for the Cylinder System—The Kitcher System—The Combined Tank and Cylinder System—Combined Independent and Kitchen Boiler—Combined Cylinder and Tank System with Duplicate Boilers—Indirect Heating and Boiler Explosions—Pipe Boilers—Safety Valves—Safety Valves—The American System—Heating Water by Steam—Steam Kettles and Jets—Heating Power of Steam—Covering for Hot Water Pipes—Index.

Brewing and Botanical.

HOPS IN THEIR BOTANICAL, AGRICULTURAL AND TECHNICAL ASPECT, AND AS AN ARTICLE OF COMMERCE. By EMMANUEL GROSS, Professor at the Higher Agricultural College, Tetschen-Liebwerd. Translated from the German. Seventy-eight Illustrations. 1900. 340 pp. Demy 8vo. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; strictly net.

Contents.

HISTORY OF THE HOP—THE HOP PLANT—Introductory—The Roots—The Stem—and Leaves—Inflorescence and Flower: Inflorescence and Flower of the Male Hop; Inflorescence and Flower of the Female Hop—The Fruit and its Glandular Structure: The Fruit and Seed—Propagation and Selection of the Hop—Varieties of the Hop: (a) Red Hops; (b) Green Hops; (c) Pale Green Hops—Classification according to the Period of Ripening: Early August Hops; Medium Early Hops; Late Hops—Injuries to Growth—Leaves Turning Yellow, Summer or Sunbrand, Cones Dropping Off, Honey Dew, Damage from Wind, Hail

and Rain; Vegetable Enemies of the Hop; Animal Enemies of the Hop—Beneficial Insects on Hops—**CULTIVATION**—The Requirements of the Hop in Respect of Climate, Soil and Situation: Climate; Soil; Situation—Selection of Variety and Cuttings—Planting a Hop Garden: Drainage; Preparing the Ground; Marking-out for Planting; Planting; Cultivation and Cropping of the Hop Garden in the First Year—Work to be Performed Annually in the Hop Garden: Working the Ground; Cutting; The Non-cutting System; The Proper Performance of the Operation of Cutting: Method of Cutting: Close Cutting, Ordinary Cutting, The Long Cut, The Topping Cut; Proper Season for Cutting: Autumn Cutting, Spring Cutting; Manuring; Training the Hop Plant: Poled Gardens, Frame Training; Principal Types of Frames; Pruning, Cropping, Topping, and Leaf Stripping the Hop Plant; Picking, Drying and Bagging—Principal and Subsidiary Utilisation of Hops and Hop Gardens—Life of a Hop Garden; Subsequent Cropping—Cost of Production, Yield and Selling Prices.

Preservation and Storage—Physical and Chemical Structure of the Hop Cone—Judging the Value of Hops.

Statistics of Production—The Hop Trade—Index.

Timber and Wood Waste.

TIMBER: A Comprehensive Study of Wood in all its Aspects (Commercial and Botanical), showing the Different Applications and Uses of Timber in Various Trades, etc. Translated from the French of PAUL CHARPENTIER. Royal 8vo. 437 pp. 178 Illustrations. 1902. Price 12s. 6d.; India and Colonies, 13s. 6d.; Other Countries, 15s.; net.

Contents.

Physical and Chemical Properties of Timber—Composition of the Vegetable Bodies—Chief Elements—M. Fremy's Researches—Elementary Organs of Plants and especially of Forests—Different Parts of Wood Anatomically and Chemically Considered—General Properties of Wood—**Description of the Different Kinds of Wood**—Principal Essences with Caducous Leaves—Coniferous Resinous Trees—**Division of the Useful Varieties of Timber in the Different Countries of the Globe**—European Timber—African Timber—Asiatic Timber—American Timber—Timber of Oceania—**Forests**—General Notes as to Forests; their Influence—Opinions as to Sylviculture—Improvement of Forests—Unwooding and Rewooding—**Preservation of Forests**—Exploitation of Forests—Damage caused to Forests—Different Alterations—**The Preservation of Timber**—Generalities—Causes and Progress of Deterioration—History of Different Proposed Processes—Dessication—Superficial Carbonisation of Timber—Processes by Immersion—Generalities as to Antiseptics Employed—Injection Processes in Closed Vessels—The Boucherie System, Based upon the Displacement of the Sap—Processes for Making Timber Uninflammable—**Applications of Timber**—Generalities—Working Timber—Paving—Timber for Mines—Railway Traverses—Accessory Products—Gums—Works of M. Fremy—Resins—Barks—Tan—Application of Cork—The Application of Wood to Art and Dyeing—Different Applications of Wood—Hard Wood—Distillation of Wood—Pyroligneous Acid—Oil of Wood—Distillation of Resins—Index.

THE UTILISATION OF WOOD WASTE. Translated from the German of ERNST HUBBARD. Crown 8vo. 192 pp. 1902. Fifty Illustrations. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; net.

Contents.

General Remarks on the Utilisation of Sawdust—Employment of Sawdust as Fuel, with and without Simultaneous Recovery of Charcoal and the Products of Distillation—Manufacture of Oxalic Acid from Sawdust—Process with Soda Lye; Thorn's Process; Bohlig's Process—Manufacture of Spirit (Ethyl Alcohol) from Wood Waste—Patent Dyes (Organic Sulphides, Sulphur Dyes, or Mercapto Dyes)—Artificial Wood and Plastic Compositions from Sawdust—Production of Artificial Wood Compositions for Moulded Decorations—Employment of Sawdust for Blasting Powders and Gunpowders—Employment of Sawdust for Briquettes—Employment of Sawdust in the Ceramic Industry and as an Addition to Mortar—Manufacture of Paper Pulp from Wood—Casks—Various Applications of Sawdust and Wood Refuse—Calcium Carbide—Manure—Wood Mosaic Plaques—Bottle Stoppers—Parquetry—Fire-lighters—Carborundum—The Production of Wood Wool—Bark—Index.

Building and Architecture.

THE PREVENTION OF DAMPNESS IN BUILDINGS ;

with Remarks on the Causes, Nature and Effects of Saline, Efflorescences and Dry-rot, for Architects, Builders, Overseers, Plasterers, Painters and House Owners. By ADOLF WILHELM KEIM. Translated from the German of the second revised Edition by M. J. SALTER, F.I.C., F.C.S. Eight Coloured Plates and Thirteen Illustrations. Crown 8vo. 115 pp. 1902. Price 5s. ; India and Colonies, 5s. 6d. ; Other Countries, 6s. ; net.

Contents.

The Various Causes of Dampness and Decay of the Masonry of Buildings, and the Structural and Hygienic Evils of the Same—Precautionary Measures during Building against Dampness and Efflorescence—Methods of Remedying Dampness and Efflorescences in the Walls of Old Buildings—The Artificial Drying of New Houses, as well as Old Damp Dwellings, and the Theory of the Hardening of Mortar—New, Certain and Permanently Efficient Methods for Drying Old Damp Walls and Dwellings—The Cause and Origin of Dry-rot : its Injurious Effect on Health, its Destructive Action on Buildings, and its Successful Repression—Methods of Preventing Dry-rot to be Adopted During Construction—Old Methods of Preventing Dry-rot—Recent and More Efficient Remedies for Dry-rot—Index.

HANDBOOK OF TECHNICAL TERMS USED IN ARCHITECTURE AND BUILDING, AND THEIR ALLIED TRADES AND SUBJECTS.

By AUGUSTINE C. PASSMORE. Demy 8vo. 380 pp. 1904. Price 7s. 6d. ; India and Colonies, 8s. ; Other Countries, 8s. 6d. ; strictly net.

Foods and Sweetmeats.

THE MANUFACTURE OF PRESERVED FOODS AND SWEETMEATS.

By A. HAUSNER. With Twenty-eight Illustrations. Translated from the German of the third enlarged Edition. Crown 8vo. 225 pp. 1902. Price 7s. 6d. ; India and Colonies, 8s. ; Other Countries, 8s. 6d. ; net.

Contents.

The Manufacture of Conserves—Introduction—The Causes of the Putrefaction of Food—The Chemical Composition of Foods—The Products of Decomposition—The Causes of Fermentation and Putrefaction—Preservative Bodies—The Various Methods of Preserving Food—The Preservation of Animal Food—Preserving Meat by Means of Ice—The Preservation of Meat by Charcoal—Preservation of Meat by Drying—The Preservation of Meat by the Exclusion of Air—The Appert Method—Preserving Flesh by Smoking—Quick Smoking—Preserving Meat with Salt—Quick Salting by Air Pressure—Quick Salting by Liquid Pressure—Gamage's Method of Preserving Meat—The Preservation of Eggs—Preservation of White and Yolk of Egg—Milk Preservation—Condensed Milk—The Preservation of Fat—Manufacture of Soup Tablets—Meat Biscuits—Extract of Beef—The Preservation of Vegetable Foods in General—Compressing Vegetables—Preservation of Vegetables by Appert's Method—The Preservation of Fruit—Preservation of Fruit by Storage—The Preservation of Fruit by Drying—Drying Fruit by Artificial Heat—Roasting Fruit—The Preservation of Fruit with Sugar—Boiled Preserved Fruit—The Preservation of Fruit in Spirit, Acetic Acid or Glycerine—Preservation of Fruit without Boiling—Jam Manufacture—The Manufacture of Fruit Jellies—The Making of Gelatine Jellies—The Manufacture of "Sulzen"—The Preservation of Fermented Beverages—**The Manufacture of Candies**—Introduction—The Manufacture of Candied Fruit—The Manufacture of Boiled Sugar and Caramel—The Candying of Fruit—Caramelised Fruit—The Manufacture of Sugar Sticks, or Barley Sugar—Bonbon Making—Fruit-Drops—The Manufacture of Dragées—The Machinery and Appliances used in Candy Manufacture—Dyeing Candies and Bonbons—Essential Oils used in Candy Making—Fruit Essences—The Manufacture of Filled Bonbons, Liqueur Bonbons and Stamped Lozenges—Recipes for Jams and Jellies—Recipes for Bonbon Making—Dragées—Appendix—Index.

Dyeing Fancy Goods.

THE ART OF DYEING AND STAINING MARBLE, ARTIFICIAL STONE, BONE, HORN, IVORY AND WOOD, AND OF IMITATING ALL SORTS OF WOOD. A Practical Handbook for the Use of Joiners, Turners, Manufacturers of Fancy Goods, Stick and Umbrella Makers, Comb Makers, etc. Translated from the German of D. H. SOXHLET, Technical Chemist. Crown 8vo. 168 pp. 1902. Price 5s.; India and Colonies, 5s. 6d.; Other Countries, 6s.; net.

Contents.

Mordants and Stains—Natural Dyes—Artificial Pigments—Coal Tar Dyes—Staining Marble and Artificial Stone—Dyeing, Bleaching and Imitation of Bone, Horn and Ivory—Imitation of Tortoiseshell for Combs: Yellows, Dyeing Nuts—Ivory—Wood Dyeing—Imitation of Mahogany: Dark Walnut, Oak, Birch-Bark, Elder-Marquetry, Walnut, Walnut-Marquetry, Mahogany, Spanish Mahogany, Palisander and Rose Wood, Tortoiseshell, Oak, Ebony, Pear Tree—Black Dyeing Processes with Penetrating Colours—Varnishes and Polishes: English Furniture Polish, Vienna Furniture Polish, Amber Varnish, Copal Varnish, Composition for Preserving Furniture—Index.

Lithography, Printing and Engraving.

PRACTICAL LITHOGRAPHY. By ALFRED SEYMOUR. Demy 8vo. With Frontispiece and 33 Illus. 120 pp. 1903. Price 5s.; Colonies, 5s. 6d.; Other Countries, 6s.; net.

Contents.

Stones—Transfer Inks—Transfer Papers—Transfer Printing—Litho Press—Press Work—Machine Printing—Colour Printing—Substitutes for Lithographic Stones—Tin Plate Printing and Decoration—Photo-Lithography.

PRINTERS' AND STATIONERS' READY RECKONER AND COMPENDIUM. Compiled by VICTOR GRAHAM. Crown 8vo. 112 pp. 1904. Price 3s. 6d.; India and Colonies, 4s.; Other Countries, 4s. 6d.; strictly net, post free.

Contents.

Price of Paper per Sheet, Quire, Ream and Lb.—Cost of 100 to 1000 Sheets at various Sizes and Prices per Ream—Cost of Cards—Quantity Table—Sizes and Weights of Paper, Cards, etc.—Notes on Account Books—Discount Tables—Sizes of spaces—Leads to a lb.—Dictionary—Measure for Bookwork—Correcting Proofs, etc.

ENGRAVING FOR ILLUSTRATION. HISTORICAL AND PRACTICAL NOTES. By J. KIRKBRIDE. 72 pp. Two Plates and 6 Illustrations. Crown 8vo. 1903. Price 2s. 6d.; Abroad, 3s.; strictly net.

Contents.

Its Inception—Wood Engraving—Metal Engraving—Engraving in England—Etching—Mezzotint—Photo-Process Engraving—The Engraver's Task—Appreciative Criticism—Index.

Bookbinding.

PRACTICAL BOOKBINDING. By PAUL ADAM. Translated from the German. Crown 8vo. 180 pp. 127 Illustrations. 1903. Price 5s.; Colonies, 5s. 6d.; Other Countries, 6s.; net.

Contents.

Materials for Sewing and Pasting—Materials for Covering the Book—Materials for Decorating and Finishing—Tools—General Preparatory Work—Sewing—Forwarding, Cutting, Rounding and Backing—Forwarding, Decoration of Edges and Headbanding—Boarding—Preparing the Cover—Work with the Blocking Press—Treatment of Sewn Books, Fastening in Covers, and Finishing Off—Handtooling and Other Decoration—Account Books—School Books, Mounting Maps, Drawings, etc.—Index.

Sugar Refining.

THE TECHNOLOGY OF SUGAR: Practical Treatise on the Modern Methods of Manufacture of Sugar from the Sugar Cane and Sugar Beet. By JOHN GEDDES MCINTOSH. Demy 8vo. 83 Illustrations. 420 pp. Seventy-six Tables. 1903. Price 10s. 6d.; Colonies, 11s.; Other Countries, 12s.; net.

(See "Evaporating, Condensing, etc., Apparatus," p. 27.)

Contents.

Chemistry of Sucrose, Lactose, Maltose, Glucose, Invert Sugar, etc.—Purchase and Analysis of Beets—Treatment of Beets—Diffusion—Filtration—Concentration—Evaporation—**Sugar Cane:** Cultivation—Milling—Diffusion—Sugar Refining—Analysis of Raw Sugars—Chemistry of Molasses, etc.

Bibliography.

CLASSIFIED GUIDE TO TECHNICAL AND COMMERCIAL BOOKS. Compiled by EDGAR GREENWOOD.

Demy 8vo. 224 pp. 1904. Being a Subject-list of the Principal British and American Books in print; giving Title, Author, Size, Date, Publisher and Price. Price 7s. 6d.; India and Colonies, 8s.; Other Countries, 8s. 6d.; strictly net, post free.


Contents.

1. **Agriculture and Farming**—Agricultural Chemistry—Bee-keeping—Cattle, Pigs, Sheep—Dairy and Dairy Work—Feeding Animals—Forestry—Fruit Growing—Irrigation—Manures—Poultry Farming. 2. **Air, Aerial Navigation.** 3. **Architecture and Building.** 4. **Art**—Lettering—Modelling—Ornament—Painting—Perspective. 5. **Arts and Crafts, Amateur Work.** 6. **Auction Sales.** 7. **Banking.** 8. **Book and Newspaper Production, Paper-making, Printing**—Bookbinding—Bookselling—Copyright—Journalism—Lithography—Paper-making—Printing, Typography—Process Work—Stationery. 9. **Brewing and Distilling.** 10. **Cabinet-making.** 11. **Calculators, Ready Reckoners, Discount Tables.** 12. **Carpentry and Joinery.** 13. **Chemicals, Chemistry.** 14. **Coachbuilding.** 15. **Commerce, Business.** 16. **Dams, Docks, Harbours.** 17. **Dogs.** 18. **Domestic Economy**—Cookery—Dressmaking—Laundry—Millinery. 19. **Electricity**—Alternating Currents—Dynamos—Electric Heating—Electric Lighting—Electric Traction—Telegraphy—Telephones—Wireless Telegraphy. 20. **Elocution, Voice Production.** 21. **Engineering and Metal Work**—Architectural Engineering—Blacksmithing—Boilers—Bridges—Civil Engineering—Fuel, Smoke—Galvanising, Tinning—Gas, Oil and Air Engines—Hardware—Hydraulic Engineering—Indicators—Injectors—Iron and Steel—Ironfounding—Lathes, Tools—Locomotives—Machine Construction and Design—Marine Engineering—Mechanical Engineering—Metal Work—Pattern Making—Pipes—Power Transmission—Pumps—Refrigeration—Saw Filing—Screw Cutting—Steam Engine—Strains and Stresses—Turbines. 22. **Factories and Workshops.** 23. **Financial**—Investments—Stockbroking. 24. **Foods and Beverages**—Adulteration and Analysis—Bread—Cakes—Fish—Flour, Grain—Food and Drug Acts—Tea. 25. **Foreign Exchange Tables, Metric System.** 26. **Foreign Languages.** 27. **Gardening, Flowers.** 28. **Gas**—Acetylene—Gas Fitting—Gas Lighting and Supply. 29. **Glass.** 30. **Glues, Inks, Pastes.** 31. **Horses.** 32. **Hospitals, Nursing.** 33. **House Decoration.** 34. **Hygiene, Public Health**—Bacteriology—Hygiene—Public Health—Sanitary Inspection—Sewage and Sewerage. 35. **India-Rubber.** 36. **Insurance.** 37. **Jewellery, Silver and Goldsmith's Work.** 38. **Land, Property.** 39. **Leather Trades.** 40. **Legal**—Arbitration—Bankruptcy Law—Commercial Law—Contract Law—Solicitors—Stamp Duties—Trustee Law—Wills. 41. **Metallurgy.** 42. **Military.** 43. **Mining, Quarrying.** 44. **Motor Cars and Cycles.** 45. **Music.** 46. **Nautical, Navigation.** 46a. **Navy.** 47. **Oils, Fats.** 48. **Optical, Microscopy, Instruments.** 49. **Paints, Colours, Varnishes.** 50. **Patents, Trade Marks.** 51. **Photography.** 52. **Physics.** 53. **Physical Training.** 54. **Plumbing, Heating, Ventilation.** 55. **Pottery, China, Bricks.** 56. **Public Meetings, Elections, Taxes.** 57. **Railways and Tramways**—Construction of Railways—Carriage and Wagon Building—Law of Railways—Light Railways—Management. 58. **Rivers, Canals.** 59. **Roads, Highways.** 60. **Shopkeeping, Ticket Writing.** 61. **Shorthand, Typewriting.** 62. **Soaps, Candles.** 63. **Building, Co-operative and Friendly Societies.** 64. **Surveying.** 65. **Teaching, Education.** 66. **Telegraph Codes.** 67. **Textile Trades.** 68. **Timber.** 69. **Veterinary.** 70. **Watches, Clocks.** 71. **Water.** Subject Index.

SCOTT, GREENWOOD & Co. will forward these Books, *post free*, upon receipt of remittance at the published price, or they can be obtained through all Booksellers.

Full List of Contents of any of the books will be sent on application.

SCOTT, GREENWOOD & CO.,
 Technical Book Publishers,
 19 LUDGATE HILL, LONDON, E.C.



UNIVERSITY OF CALIFORNIA LIBRARY
BERKELEY

Return to desk from which borrowed.
This book is DUE on the last date stamped below.

2 Dec '52 ED

Dec. 31
renewed until
Feb. 2 '52

FEB 6 1953 LU

30 Apr '53 LU

APR 16 1955 LU

18 Mar '57 FE

REC'D LD

MAR 18 1957

APR 3 1977 2

REC'D LD APR 11 1973 - 1AM 36

REC. CIR. MAY 8 1977

NEQ425

S5

Seymour

152212

